INTERNATIONAL STANDARD

ISO 16283-2

First edition 2015-11-15

Acoustics — Field measurement of sound insulation in buildings and of building elements —

Part 2: **Impact sound insulation**

Acoustique — Mesurage in situ de l'isolation acoustique des bâtiments et des éléments de construction —

Partie 2: Isolation des bruits d'impacts





COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents			Page	
Fore	word		v	
Intro	ductio	n	vi	
1	Scon	e	1	
2	-	native references		
3	Term	Terms and definitions 2		
4		umentation		
	4.1	General		
	4.2 4.3	Calibration Verification		
5	_	uency range		
	5.1 5.2	Tapping machine as the impact sourceRubber ball as the impact source		
		•		
6	Gene	ral	6	
7	Defa	ult procedure for sound pressure level measurement	7	
	7.1	General		
	7.2	Generation of sound field		
		7.2.1 General T.2.2 Impact source positions for the tapping machine as impact source		
		 7.2.2 Impact source positions for the tapping machine as impact source 7.2.3 Impact source positions for the rubber ball as impact source 		
	7.3	Fixed microphone positions for the tapping machine or rubber ball as impact source.		
		7.3.1 General		
		7.3.2 Number of measurements		
		7.3.3 Tapping machine operated at more than one position	8	
	7.4	7.3.4 Rubber ball operated at more than one position		
	7.4	Mechanized continuously-moving microphone for the tapping machine as impact sou 7.4.1 General		
		7.4.2 Number of measurements		
		7.4.3 Tapping machine operated at more than one position		
	7.5	Manually-scanned microphone for the tapping machine as impact source		
		7.5.1 General		
		7.5.2 Number of measurements		
		7.5.3 Tapping machine operated at more than one position		
		7.5.5 Helix		
		7.5.6 Cylindrical-type		
		7.5.7 Three semicircles	11	
	7.6	Minimum distances for microphone positions		
	7.7	Averaging times for the tapping machine as impact source	12	
		7.7.1 Fixed microphone positions		
		7.7.2 Mechanized continuously-moving inicrophone		
	7.8	Calculation of energy-average sound pressure levels	12	
		7.8.1 Fixed microphone positions for the tapping machine as impact source		
		7.8.2 Mechanized continuously-moving microphone and manually-scanned		
		microphone for the tapping machine as impact source	13	
		7.8.3 Fixed microphone positions for the rubber ball as impact source	13	
8	Low-	frequency procedure for sound pressure level measurement for the tapping		
	mach	nine as impact source		
	8.1 8.2	General Generation of sound field		
	0.2	8.2.1 General		