



Institut luxembourgeois de la normalisation
de l'accréditation, de la sécurité et qualité
des produits et services

ILNAS-EN 60317-0-10:2017

**Specifications for particular types of
winding wires - Part 0-10: General
requirements - Polyester glass-fibre
wound fused, unvarnished, or resin or**

Spécifications pour types particuliers de
fils de bobinage - Partie 0-10: Exigences
générales - Fil de section circulaire en
cuivre nu ou émaillé, guipé de fibres de

Technische Lieferbedingungen für
bestimmte Typen von Wickeldrähten –
Teil 0-10: Allgemeine Anforderungen –
Runddrähte aus Kupfer, blank oder

08/2017



National Foreword

This European Standard EN 60317-0-10:2017 was adopted as Luxembourgish Standard ILNAS-EN 60317-0-10:2017.

Every interested party, which is member of an organization based in Luxembourg, can participate for FREE in the development of Luxembourgish (ILNAS), European (CEN, CENELEC) and International (ISO, IEC) standards:

- Participate in the design of standards
- Foresee future developments
- Participate in technical committee meetings

<https://portail-qualite.public.lu/fr/normes-normalisation/participer-normalisation.html>

THIS PUBLICATION IS COPYRIGHT PROTECTED

Nothing from this publication may be reproduced or utilized in any form or by any mean - electronic, mechanical, photocopying or any other data carries without prior permission!

ILNAS-EN 60317-0-10:2017

EUROPEAN STANDARD **EN 60317-0-10**

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2017

ICS 29.060.10

English Version

Specifications for particular types of winding wires -
Part 0-10: General requirements - Polyester glass-fibre wound
fused, unvarnished, or resin or varnish impregnated,
bare or enamelled round copper wire
(IEC 60317-0-10:2017)

Spécifications pour types particuliers de fils de bobinage -
Partie 0-10: Exigences générales - Fil de section circulaire
en cuivre nu ou émaillé, guipé de fibres de verre polyester
fondues, non vernies ou imprégnées de vernis ou de résine
(IEC 60317-0-10:2017)

Technische Lieferbedingungen für bestimmte Typen von
Wickeldrähten - Teil 0-10: Allgemeine Anforderungen -
Mit unbeschichteten Polyesterfasern umwickelt und
verschmolzen oder mit Harz oder Lack imprägnierter
blanker oder lackisolierter Runddraht aus Kupfer
(IEC 60317-0-10:2017)

This European Standard was approved by CENELEC on 2017-06-08. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

The text of document 55/1601/FDIS, future edition 1 of IEC 60317-0-10, prepared by IEC/TC 55 "Winding wires" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60317-0-10:2017.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2018-03-08
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2020-06-08

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60317-0-10:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60264	NOTE	Harmonized in EN 60264 series.
IEC 60317	NOTE	Harmonized in EN 60317 series.
IEC 60317-70	NOTE	Harmonized as EN 60317-70.
IEC 60317-71	NOTE	Harmonized as EN 60317-71.
IEC 60317-72	NOTE	Harmonized as EN 60317-72.
IEC 60851-6:2012	NOTE	Harmonized as EN 60851-6:2012 (not modified).

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60851	series	Winding wires - Test methods	EN 60851	series
IEC 60851-5	2008	Winding wires - Test methods - Part 5: Electrical properties	EN 60851-5	2008
ISO 3	-	Preferred numbers - Series of preferred numbers	-	-



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Specifications for particular types of winding wires –
Part 0-10: General requirements – Polyester glass-fibre wound fused,
unvarnished, or resin or varnish impregnated, bare or enamelled round copper
wire**

**Spécifications pour types particuliers de fils de bobinage –
Partie 0-10: Exigences générales – Fil de section circulaire en cuivre nu ou
émailé, guipé de fibres de verre polyester fondues, non vernies ou imprégnées
de vernis ou de résine**

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions, general notes and appearance	7
3.1 Terms and definitions.....	7
3.2 General notes	8
3.2.1 Methods of test.....	8
3.2.2 Winding wire.....	9
3.3 Appearance	9
4 Dimensions.....	9
4.1 Conductor diameter	9
4.2 Out of roundness of conductor	11
4.3 Minimum increase in diameter due to the covering	11
4.4 Maximum overall diameter	11
5 Electrical resistance	12
6 Elongation	12
7 Springiness	12
7.1 Nominal conductor diameters up to and including 1,600 mm	12
7.2 Nominal conductor diameters over 1,600 mm.....	12
8 Flexibility and adherence	12
8.1 Mandrel winding test.....	12
8.2 Adherence test.....	12
9 Heat shock	13
10 Cut-through	13
11 Resistance to abrasion	13
12 Resistance to solvents.....	13
13 Breakdown voltage	13
13.1 Polyester glass fibre covered bare round copper wire	13
13.2 Polyester glass fibre covered enamelled round copper wire	13
14 Continuity of insulation	14
15 Temperature index	14
16 Resistance to refrigerants.....	14
17 Solderability	14
18 Heat or solvent bonding.....	14
19 Dielectric dissipation factor.....	14
20 Resistance to transformer oil	14
21 Loss of mass	14
23 Pin hole test	15
30 Packaging	15
Annex A (informative) Diameters for intermediate nominal conductor diameters (R40).....	16
Annex B (informative) Resistance	18
B.1 Determination of nominal resistance	18
Annex C (informative) High temperature failure.....	19

Bibliography.....	20
Table 1 – Dimensional requirements of (single) polyester glass-fibre wound fused and unvarnished or resin or varnish impregnated over grade 1 or grade 2 enamelled round copper winding wire (R20)	10
Table 2 – Dimensional requirements of (double) polyester glass-fibre wound fused and unvarnished or resin or varnish impregnated over bare, grade 1, or grade 2 enamelled round copper winding wire (R20).....	11
Table 3 – Elongation	12
Table 4 – Mandrel winding	12
Table 5 – Breakdown voltage for bare round copper wire	13
Table 6 – Breakdown voltage for enamelled round copper wire	14
Table A.1 – Diameters for single polyester glass-fibre wound fused and unvarnished or resin or varnish impregnated over grade 1 or grade 2 enamelled round copper wire (R40)	16
Table A.2 – Diameters for double polyester glass-fibre wound fused and unvarnished or resin or varnish impregnated over bare, grade 1 or grade 2 enamelled round copper wire (R40).....	17
Table B.1 – Electrical resistance	18