

Institut luxembourgeois de la normalisation de l'accréditation, de la sécurité et qualité des produits et services

ILNAS-EN IEC 60079-0:2018

**Explosive atmospheres - Part 0: Equipment - General requirements** 

Explosionsgefährdete Bereiche - Teil 0: Betriebsmittel - Allgemeine Anforderungen

Atmosphères explosives - Partie 0:
Matériel - Exigences générales

#### **National Foreword**

This European Standard EN IEC 60079-0:2018 was adopted as Luxembourgish Standard ILNAS-EN IEC 60079-0:2018.

Every interested party, which is member of an organization based in Luxembourg, can participate for FREE in the development of Luxembourgish (ILNAS), European (CEN, CENELEC) and International (ISO, IEC) standards:

- Participate in the design of standards
- Foresee future developments
- Participate in technical committee meetings

https://portail-qualite.public.lu/fr/normes-normalisation/participer-normalisation.html

#### THIS PUBLICATION IS COPYRIGHT PROTECTED

Nothing from this publication may be reproduced or utilized in any form or by any mean - electronic, mechanical, photocopying or any other data carries without prior permission!

### EUROPEAN STANDARD LINAS-EN IEC 60079-0:2018 IEC 60079-0

### NORME EUROPÉENNE

**EUROPÄISCHE NORM** 

July 2018

ICS 29.260.20

Supersedes EN 60079-0:2012

#### **English Version**

# Explosive atmospheres - Part 0: Equipment - General requirements (IEC 60079-0:2017)

Atmosphères explosives - Partie 0: Matériel - Exigences générales (IEC 60079-0:2017)

Explosionsgefährdete Bereiche - Teil 0: Betriebsmittel -Allgemeine Anforderungen (IEC 60079-0:2017)

This European Standard was approved by CENELEC on 2017-12-04. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

#### **European foreword**

The text of document (31/1345/FDIS), future edition 7 of IEC 60079-0, prepared by IEC/TC 31 "Equipment for explosive atmospheres" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60079-0:2018.

The following dates are fixed:

| • | latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement | (dop) | 2019-01-06 |
|---|--|-------|------------|
| • | latest date by which the national  | (dow) | 2021-07-06 |

standards conflicting with the document have to be withdrawn

This document supersedes EN 60079-0:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

#### **Endorsement notice**

The text of the International Standard IEC 60079-0:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

| IEC/TS 60034-25 | NOTE | Harmonized as CLC/TS 60034-25. |
|-----------------|------|--------------------------------|
| IEC 60034-29    | NOTE | Harmonized as EN 60034-29.     |
| IEC 60079-2     | NOTE | Harmonized as EN 60079-2.      |
| IEC 60079-5     | NOTE | Harmonized as EN 60079-5.      |
| IEC 60079-6     | NOTE | Harmonized as EN 60079-6.      |
| IEC 60079-7     | NOTE | Harmonized as EN 60079-7.      |
| IEC 60079-10-1  | NOTE | Harmonized as EN 60079-10-1.   |
| IEC 60079-10-2  | NOTE | Harmonized as EN 60079-10-2.   |
| IEC 60079-11    | NOTE | Harmonized as EN 60079-11.     |
| IEC 60079-13    | NOTE | Harmonized as EN 60079-13.     |
| IEC 60079-14    | NOTE | Harmonized as EN 60079-14.     |
| IEC 60079-15    | NOTE | Harmonized as EN 60079-15.     |
| IEC 60079-17    | NOTE | Harmonized as EN 60079-17.     |
| IEC 60079-18    | NOTE | Harmonized as EN 60079-18.     |
| IEC 60079-19    | NOTE | Harmonized as EN 60079-19.     |
| IEC 60079-25    | NOTE | Harmonized as EN 60079-25.     |
| IEC 60079-28    | NOTE | Harmonized as EN 60079-28.     |
| IEC 60079-29-1  | NOTE | Harmonized as EN 60079-29-1.   |

| IEC 60079-29-4     | NOTE   | Harmonized as EN 60079-29-4.                  |
|--------------------|--------|---|
| IEC/IEEE 60079-30- | 1 NOTE | Harmonized as EN 60079-30-1.                  |
| IEC 60079-31       | NOTE   | Harmonized as EN 60079-31.                    |
| IEC/TS 60079-32-1  | NOTE   | Harmonized as CLC/TR 60079-32-1.              |
| IEC/TS 60079-39    | NOTE   | Harmonized as CLC/TS 60079-39 <sup>1</sup> ). |
| IEC 60254 (series) | NOTE   | Harmonized in EN 60254 series.                |
| IEC 60623          | NOTE   | Harmonized as EN 60623.                       |
| IEC 60896-11       | NOTE   | Harmonized as EN 60896-11.                    |
| IEC 60896-21       | NOTE   | Harmonized as EN 60896-21.                    |
| IEC 60952 (series) | NOTE   | Harmonized in EN 60952 series.                |
| IEC 61056-1        | NOTE   | Harmonized in EN 61056-1.                     |
| IEC 61427 (series) | NOTE   | Harmonized in EN 61427 series.                |
| IEC 61951-1        | NOTE   | Harmonized as EN 61951-1.                     |
| IEC 61951-2        | NOTE   | Harmonized as EN 61951-2.                     |
| IEC 61960 (series) | NOTE   | Harmonized in EN 61960 series.                |
| ISO/IEC 80079-20-2 | NOTE   | Harmonized as EN ISO/IEC 80079-20-2.          |
| ISO/IEC 80079-34   | NOTE   | Harmonized as EN ISO/IEC 80079-34.            |
| ISO/IEC 80079-36   | NOTE   | Harmonized as EN ISO/IEC 80079-36.            |
| ISO/IEC 17000      | NOTE   | Harmonized as EN ISO/IEC 17000.               |

 $<sup>^{\</sup>mbox{\tiny 1}})$  Under preparation. Stage at the time of publication: CLC/FprTS 60079-39:2017.

#### **Annex ZA**

(normative)

## Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

| <u>Publication</u>       | <u>Year</u> | <u>Title</u>  | EN/HD                                      | <u>Year</u>  |
|--------------------------|-------------|---|--|--------------|
| IEC 60034-1              | -           | Rotating electrical machines - Part 1: Rating and performance   | EN 60034-1 <sup>2</sup> )                  | -            |
| IEC 60034-5              | -           | Rotating electrical machines - Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) - Classification                             | EN 60034-5                                 | 2001         |
| IEC 60079-1              | -           | Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"   | EN 60079-1                                 | 2014         |
| IEC 60079-20-1           | -           | Explosive atmospheres - Part 20-1: Material characteristics for gas and vapour classification - Test methods and data   | EN 60079-20-1                              | 2010         |
| IEC 60079-26             | -           | Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga   | nEN 60079-26                               | 2015         |
| IEC 60079-35-1           | -           | Explosive atmospheres - Part 35-1: Caplights for use in mines susceptible to firedamp - General requirements - Construction and testing in relation to the risk of explosion        | EN 60079-35-1                              | 2011         |
| .=                       |             | ·   | +AC  | 2011         |
| IEC 60086-1<br>IEC 60192 | -           | Primary batteries - Part 1: General Low pressure sodium vapour lamps - Performance specifications   | EN 60086-1<br>EN 60192                     | 2015<br>2001 |
| IEC 60216-1              | -           | Electrical insulating materials - Thermal endurance properties - Part 1: Ageing procedures and evaluation of test results   | EN 60216-1                                 | 2013         |
| IEC 60216-2              | -           | Electrical insulating materials - Thermal endurance properties - Part 2: Determination of thermal endurance properties of electrical insulating materials - Choice of test criteria | EN 60216-2                                 | 2005         |
| IEC 60243-1              | -           | Electric strength of insulating materials - Test methods - Part 1: Tests at power frequencies   | EN 60243-1                                 | 2013         |
| IEC 60423                | -           | Conduit systems for cable management - Outside diameters of conduits for electrical installations and threads for conduits and fittings   | EN 60423                                   | 2007         |
| IEC 60529                | -           | Degrees of protection provided by enclosures (IF Code)  |  | 1991         |
|                          |             |   | +EN<br>60529:1991/corrig<br>endum May 1993 | 1993         |

<sup>&</sup>lt;sup>2</sup>) Under preparation. Stage at the time of publication: FprEN 60034-1:2017.

| IEC 60662 (mod)  | -      | High pressure sodium vapour lamps -                | EN 60662        | 2012   |
|------------------|--------|--|-----------------|--------|
|                  |        | Performance specifications                         |                 |        |
|                  |        |  | +prAA           | 2017   |
| IEC 60664-1      | -      | Insulation coordination for equipment within low-  | EN 60664-1      | 2007   |
|                  |        | voltage systems - Part 1: Principles,              |                 |        |
|                  |        | requirements and tests                             |                 |        |
| IEC 60947-1      | _      | Low-voltage switchgear and controlgear - Part 1:   | FN 60947-1      | 2007   |
| 120 000 11 1     |        | General rules                                      | 2.1.0001.       |        |
| IEC 62626-1      | _      | Low-voltage switchgear and controlgear             | EN 62626-1      | 2014   |
| 120 02020-1      |        | enclosed equipment - Part 1: Enclosed switch       | LIV 02020-1     | 2017   |
|                  |        |  |                 |        |
|                  |        | outside the scope of IEC 60947-3 for various       |                 |        |
|                  |        | applications, to provide isolation of electrical   |                 |        |
| 100.40           |        | equipment during repair and maintenance work       |                 |        |
| ISO 48           | -      | Rubber, vulcanized or thermoplastic                | -               | -      |
|                  |        | Determination of hardness (hardness between 10     | 0               |        |
|                  |        | IRHD and 100 IRHD)                                 |                 |        |
| ISO 178          | -      | Plastics - Determination of flexural properties    | EN ISO 178      | 2010   |
| ISO 179          | series | Plastics - Determination of Charpy impact          | EN ISO 179      | series |
|                  |        | properties   |                 |        |
| ISO 262          | _      | ISO general purpose metric screw threads-          | _               | _      |
|                  |        | Selected sizes for screws, bolts and nuts          |                 |        |
| ISO 273          | _      | Fasteners - Clearance holes for bolts and screws   | s FN 20273      | 1991   |
| ISO 527-2        | _      | Plastics - Determination of tensile properties -   | EN ISO 527-2    | 2012   |
| 100 321-2        |        | Part 2: Test conditions for moulding and           | LIV 100 321-2   | 2012   |
|                  |        |  |                 |        |
| ICO 00E 4        |        | extrusion plastics                                 |                 |        |
| ISO 965-1        | -      | ISO general purpose metric screw threads -         | -               | -      |
| 100 00 0         |        | Tolerances – Part 1: Principles and basic data     |                 |        |
| ISO 965-3        | -      | ISO general purpose metric screw threads-          | -               | -      |
|                  |        | Tolerances – Part 3: Deviations for constructiona  | al              |        |
|                  |        | screw threads                                      |                 |        |
| ISO 3601-1       | -      | Fluid power systems - O-rings – Part 1: Inside     | -               | -      |
|                  |        | diameters, cross-sections, tolerances and          |                 |        |
|                  |        | designation codes                                  |                 |        |
| ISO 3601-2       | _      | Fluid power systems - O-rings - Part 2: Housing    | _               | _      |
|                  |        | dimensions for general applications                |                 |        |
| ISO 4014         | _      | Hexagon head bolts - Product grades A and B        | EN ISO 4014     | 2011   |
| ISO 4017         | _      | Fasteners - Hexagon head screws - Product          | EN ISO 4017     | 2014   |
| 100 4017         |        | grades A and B                                     | LIV 100 4017    | 2017   |
| ISO 4026         |        | Hexagon socket set screws with flat point          | EN ISO 4026     | 2003   |
|                  | -      |  |                 |        |
| ISO 4027         | -      | Hexagon socket set screws with cone point          | EN ISO 4027     | 2003   |
| ISO 4028         | -      | Hexagon socket set screws with dog point           | EN ISO 4028     | 2003   |
| ISO 4029         | -      | Hexagon socket set screws with cup point           | EN ISO 4029     | 2003   |
| ISO 4032         | -      | Hexagon regular nuts (style 1) - Product grades    | EN ISO 4032     | 2012   |
|                  |        | A and B  |                 |        |
| ISO 4762         | -      | Hexagon socket head cap screws                     | EN ISO 4762     | 2004   |
| ISO 4892-2       | -      | Plastics - Methods of exposure to laboratory light | t EN ISO 4892-2 | 2013   |
|                  |        | sources - Part 2: Xenon-arc lamps                  |                 |        |
| ISO 7380         | _      | Hexagon socket button head screws                  | EN ISO 7380     | 2011   |
| ISO 14583        | _      | Hexalobular socket pan head screws                 | EN ISO 14583    | 2011   |
| ANSI/UL 746B     | _      | Polymeric Materials - Long-Term Property           | -               | _      |
|                  |        | Evaluations  |                 |        |
| ANSI/UL 746C     | _      | Standard for Polymeric Materials - Use in          | _               | _      |
| / ((NO)/OL / TOO | _      | Electrical Equipment Evaluations                   |                 | _      |
| ACTM D FOGA      |        |  |                 |        |
| ASTM D 5964      | -      | Standard Practice for Rubber IRM 901, IRM 902,     |                 | -      |
|                  |        | and IRM 903 Replacement Oils for ASTM No. 1,       |                 |        |
|                  |        | ASTM No. 2, ASTM No. 3 Oils, and IRM 905           |                 |        |
|                  |        | formerly ASTM No. 5 Oil                            |                 |        |

### Annex ZY

(informative)

#### Additional Information relating to the European ATEX Directive 2014/34/EU

#### **ZY.1** Equipment Groups and Categories

In all cases Equipment Protection Levels (EPL) as defined by EN IEC 60079-0 are related to the corresponding Equipment Groups and Equipment Categories according to table ZY.1. The same applies if a standard makes reference to the intended use of equipment in Zones according to the definitions in EN 60079-10-1 and EN 60079-10-2.

Table ZY.1

| EN IEC 60079-0 |           | Directive 2 | EN 60079-10-X         |                |
|----------------|-----------|-------------|-----------------------|----------------|
| EPL            | EPL Group |             | Equipment<br>Category | Zones          |
| Ма             | ,         | ,           | M1                    | Not Applicable |
| Mb             | 1         | ,           | M2                    | ]              |
| Ga             |           |             | 1G                    | 0              |
| Gb             | 11        |             | 2G                    | 1              |
| Gc             |           |             | 3G                    | 2              |
| Da             |           |             | 1D                    | 20             |
| Db             | III       |             | 2D                    | 21             |
| Dc             |           |             | 3D                    | 22             |

#### **ZY.2** Instructions

The manufacturer or his authorized representative in the Community is to draw up the instructions for use in the required Community languages.

In clause 30.1 under: "instructions for safety addressing the following areas – installation and erection:"

"Information other than the general requirements given in IEC 60079-14"

Is replaced by

"Information other than the general requirements given in EN 60079-14 and EN 50628"

NOTE EN 50628 - Erection of electrical installations in underground mines

#### ZY.3 Marking

#### **ZY.3.1**

The marking according to this standard is to be supplemented by the marking according to Directive 2014/34/EU. Examples are given below.

European marking examples

| Direc | ctive part | Standard part | Equipment example |
|-------|------------|---------------|-------------------|
| ⟨£x⟩  | I M2       | Ex db I Mb    | Mining equipment, |

Type of Protection flameproof enclosure "d"

**Ex eb IIB T4 Gb** Gas explosion protected equipment

Type of Protection increased safety "e"

II 1D Ex ma IIIC 120°C Da Dust explosion protected equipment,

Type of Protection encapsulation "m"

NOTE 1 Attention is drawn to the requirement in 29.3 f):

"The Ex marking for explosive gas atmospheres and explosive dust atmospheres shall be separate and not combined:"

Alternatively, the directive part of the marking may be combined and the standard part of the marking kept separate, as follows:

NOTE 2 For Ex Equipment intended to be put on the market in the EEA, CE marking is applicable. For Ex Components intended to be put on the market in the EEA, CE marking is not applicable.

#### **ZY.3.2**

Contrary to 29.3 a) the marking is to always include the manufacturer's name (not trademark) and address. The address is to be sufficient to identify the physical location of the manufacturer. An address used for postal purposes, without identifying the physical location, is not sufficient.

#### ZY.4 Fans

Clause 17.2.5 "Room ventilating fans" is to be supplemented by the requirements given in EN 14986 "Design of fans working in potentially explosive atmospheres"

### ZY.5 Significant changes between this European Standard and EN 60079-0:2012+A11:2013

This European Standard supersedes EN 60079-0:2012+A11:2013.

Table ZY.2 - Significant changes with respect to EN 60079-0:2012+A11:

|   |          | Туре                                 |           |                               |
|---|----------|--------------------------------------|-----------|-------------------------------|
| Explanation of the significance of the changes  | Clause   | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |
| Throughout document, "electrical equipment" replaced by "equipment" where appropriate.  | Multiple | X                                    |           |                               |
| Scope List of "Type of "Protection" and "Product" standards combined into one list.   | 1        | Х                                    |           |                               |
| Definitions used in multiple sub-parts added. Definitions harmonized across sub-parts and added to 60079-0 where appropriate. Battery definitions updated | 3        | Х                                    |           |                               |

|   |                 | Туре                                 |           |                               |
|---|-----------------|--------------------------------------|-----------|-------------------------------|
| Explanation of the significance of the changes  | Clause          | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |
| Clarification of the way that information on process temperature influences can be expressed.   | 5.1.2           | X                                    |           |                               |
| Clarification regarding the determination of service temperatures when dust layers are present  | 5.2             | X                                    |           |                               |
| Clarification on the need to provide service temperature information for Ex Components in the Schedule of Limitations   | 5.2             | Х                                    |           |                               |
| Relocation of EPL Da dust layer requirements from IEC 60079-18 & IEC 60079-31   | 5.3.2.3.1       | A1                                   |           |                               |
| Clarified that for EPL Db, a maximum specified dust layer of greater than 200 mm is not permitted as thicker layers have no additional effect on maximum surface temperature. | b)              | X                                    |           |                               |
| Added for EPL Db, a dust layer in a specified orientation, marked as $T_{\rm L}$  | c)              |                                      | X         |                               |
| Clarified that for EPL Dc, no dust layer tests are required.  | 5.3.2.3.3       | Х                                    |           |                               |
| Clarified that the "temperature" is the temperature of the air surrounding the component  | 5.3.3           | Х                                    |           |                               |
| Subdivided section dealing with higher permitted surface temperatures for "smooth" surfaces.  Corrected area from 1 000 mm <sup>2</sup> to 10 000 mm <sup>2</sup> .           | 5.3.4           | X                                    |           |                               |
| Clarified that the "Ex" requirements of IEC 60079 supplement those of the relevant industrial standards.  | 6.1             | Х                                    |           |                               |
| Added requirement that where an adhesive is used to secure a gasket, it shall be used within its COT and shall comply with the requirements for cements.                      | 6.5             |                                      |           | C1                            |
| Requirements relocated to IEC 60079-28  | former<br>6.6.2 | A2                                   |           |                               |
| Ultrasonic requirements updated based on latest research work   | 6.6.3           |                                      | X         |                               |
| Added reference to IEC 60079-28   | 6.6.4           | A2                                   |           |                               |
| Material identification parameters have been revised to reflect reasonably obtainable information   | 7.1.2.2         | Х                                    |           |                               |
| "RTI-mechanical" has been clarified to include "RTI-mechanical strength" and "RTI-mechanical impact"  | 7.1.2.2         | X                                    |           |                               |
| Material identification parameters have been revised to reflect reasonably obtainable information   | 7.1.2.3         | X                                    |           |                               |
| Relocated information on "cements" from Clause 12.  | 7.1.2.4         | Х                                    |           |                               |
| "RTI-mechanical" has been clarified to include "RTI-mechanical strength" and "RTI-mechanical  | 7.2.2           | Х                                    |           |                               |

| Explanation of the significance of the changes  | Clause               | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |
|---|----------------------|--------------------------------------|-----------|-------------------------------|
| impact". Requirements for cements aligned with the requirements for elastomers.   |                      |                                      |           |                               |
| Relocation of 10 K margin for EPL Gc or Dc from IEC 60079-15, IEC 60079-18 & IEC 60079-31   | 7.2.2                | A3                                   |           |                               |
| Added clarification with respect to gaskets and seals where only the outer edge is potentially exposed to light.                        | 7.3                  | X                                    |           |                               |
| Clarification added that one or more of the described techniques may be used  | 7.4.2                | X                                    |           |                               |
| Added additional relaxation for the case where a surface is in contact with an earthed surface on only two of four sides.               | 7.4.2 b)             |                                      | Х         |                               |
| Added reference to IEC 60243-1 and IEC 60243-2 for test method to require a 4 kV DC test.   | 7.4.2.c)             |                                      |           | C2                            |
| Additional guidance added with respect to the possible Specific Conditions of Use   | 7.4.2 e)             | Х                                    |           |                               |
| New option added for portable, mains-powered equipment with earth-connected guard   | 7.4.2 f)             |                                      | х         |                               |
| Added option for determination of maximum transferred charge.   | 7.4.2 g)<br>Table 10 |                                      | х         |                               |
| Added missing limits (same as 7.4.2)  | 7.4.3 a)             | Х                                    |           |                               |
| Clarified that it is a dc test that is conducted  | 7.4.3 b)             | Х                                    |           |                               |
| Clarified that this requirement is not applied to personal or portable equipment  | 7.5                  | Х                                    |           |                               |
| Clarified Group I limits  | 8.2                  | Х                                    |           |                               |
| Clarified Group II, EPL Ga limits   | 8.3                  | Х                                    |           |                               |
| Added limitation for external surfaces of >65% copper   | 8.5                  |                                      |           | C3                            |
| Added clarification as to what is considered a tool   | 9.1                  | Х                                    |           |                               |
| Clarified that the tolerance class of the set screw is not critical, only that it not protrude from the threaded hole after tightening. | 9.4                  | Х                                    |           |                               |
| Information on cements transferred to Clause 7  | 12                   | Х                                    |           |                               |
| Required that Ex Component Certificates require a Schedule of Limitations in all cases  | 13.5                 |                                      | х         |                               |
| Revised to clarified that all connection facilities may not be a "Compartment".   | 14                   | Х                                    |           |                               |
| Sub-clause split to separate the requirements for protective earthing and equipotential bonding into separate sections                  | 15.3<br>15.4         | Х                                    |           |                               |
| Section split to separate secureness of electrical connections from the internal earth continuity plate.                                | 15.6<br>15.7         | Х                                    |           |                               |
| Non-threaded Group I cable glands are no longer required to be Ex Components.   | 16.3                 |                                      | Х         |                               |
| Non-threaded Group I blanking elements are no   | 16.4                 |                                      | Х         |                               |

|   |                          |                                      | Туре      |                               |
|---|--------------------------|--------------------------------------|-----------|-------------------------------|
| Explanation of the significance of the changes  | Clause                   | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |
| longer required to be Ex Components.  |                          |                                      |           |                               |
| Scope of Clause 17 clarified to define applicability  | 17                       | X                                    |           |                               |
| Additional guidance notes added to address bearings   | 17.3                     | X                                    |           |                               |
| Clarified applicability to disconnectors, interlocks, and maintenance switches.   | 18.2                     | Х                                    |           |                               |
| Fuse requirements deleted as they are addressed in the individual sub-parts   | 19                       | Х                                    |           |                               |
| Added requirements for EPL Gc and Dc  | 20.1                     |                                      |           | C4                            |
| The test circuit requirements for a flameproof connection have been removed as they are more completely specified in IEC 60079-1. | 20.2                     | Х                                    |           |                               |
| The impact test requirements for luminaires are relocated to Table 15   | 21.1<br>Table 15         | Х                                    |           |                               |
| Clarified interlock switch operation for flameproof luminaires  | 21.2                     | Х                                    |           |                               |
| Clarified that some Types of Protection permit connection of cells in parallel  | 23.2                     | Х                                    |           |                               |
| New cell types and data added based on latest available data  | Table 13                 |                                      | Х         |                               |
| New cell types and data added based on latest available data  | Table 14                 |                                      |           | C5                            |
| Clarification of what documentation is to be prepared regarding the explosion safety aspects of the equipment                     | 24                       | X                                    |           |                               |
| Clarification that the type tests are to take into consideration the installation instructions                                    | 26.2                     | Х                                    |           |                               |
| Clarification that the "glass" requirements also apply to "ceramic" parts   | 26.4.1.1                 | Х                                    |           |                               |
| Added a permission to interchange the order of tests at the "lower test temperature" and the "upper test temperature".            | 26.4.1.2.2<br>26.4.1.2.3 | X                                    |           |                               |
| Clarified the construction of the impact test fixture   | 26.4.2                   | X                                    |           |                               |
| Clarified the impact tests for glass parts  | 26.4.2                   | Х                                    |           |                               |
| Added clarification to deal with the new IPX9 ratings   | 26.4.5.1                 |                                      | Х         |                               |
| Clarified the test voltage for maximum surface temperature  | 26.5.1.3                 | Х                                    |           |                               |
| Relocation of EPL Da dust layer requirements from IEC 60079-18 & IEC 60079-31   | 26.5.1.3                 | A1                                   |           |                               |
| Relocation of EPL Db specified dust layer requirements from IEC 60079-31  | 26.5.1.3                 | A4                                   |           |                               |
| Added for EPL Db, a dust layer in a specified orientation, marked as $T_{L}$  | 26.5.1.3                 |                                      | B1        |                               |

|  |                 | <u></u>                              | Туре      |                               |  |  |
|--|-----------------|--------------------------------------|-----------|-------------------------------|--|--|
| Explanation of the significance of the changes   | Clause          | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |  |  |
| Clarified that for EPL Dc, the testing is conducted without a dust layer.  | 26.5.1.3        | X                                    |           |                               |  |  |
| Relocation of thermal endurance to heat 10K relaxation for Gc equipment from IEC 60079-15, IEC 60079-18, & IEC 60079-31  | Table 17        | Х                                    |           |                               |  |  |
| Clarification of a consistent way to address elastomeric materials exposed to ultraviolet light  | 26.10           | Х                                    |           |                               |  |  |
| Replacement of "oil No. 2" with the revised designation of "oil IRM 902".  | 26.11           | Х                                    |           |                               |  |  |
| Option added for testing at lower voltages when low resistance materials are encountered   | 26.13           |                                      | Х         |                               |  |  |
| Transferred charge test added based on IEC TS 60079-32-2   | 26.17           |                                      | Х         |                               |  |  |
| The reference to a specific instruction document instead of an "X" condition relocated to e) instead of a note giving a permission   | 29.3 e)         | Х                                    |           |                               |  |  |
| Updated to reflect the additional levels of protection already shown in the sub-parts: "da", "dc", "eb", "ec", "oc", "op is", "op pr", "op sh", "pxb", "pyb", "pzc", "qb", "sa", "sb", and "sc". | 29.4 b)         | Х                                    |           |                               |  |  |
| Text added to address marking of "Ex associated equipment"   | 29.4            |                                      | Х         |                               |  |  |
| Updated to reflect the additional levels of protection already shown in the sub-parts: "ic", "op is", "op pr", "op sh", "pxb", "pyb", "pzc", "sa", "sb", and "sc".                               | 29.5 b)         | Х                                    |           |                               |  |  |
| Clarified marking of EPL Da, EPL Db with no dust layer, EPL Db with a specified dust layer, and EPL Dc.  | 29.5 d)         | Х                                    |           |                               |  |  |
| Introduced marking for EPL Db with a dust layer in a specified orientation   | 29.5 d)         |                                      | Х         |                               |  |  |
| Text added to address marking of "Ex associated equipment"   | 29.5            |                                      | Х         |                               |  |  |
| Text added to address marking of equipment intended to be installed in a boundary wall.  | 29.9            |                                      | X         |                               |  |  |
| The marking of Ex Component enclosure was aligned with the marking requirements of IEC 60079-1 and IEC 60079-7   | 29.10           | Х                                    |           |                               |  |  |
| The alternate marking of EPL has been deleted.   | former<br>29.13 |                                      |           | C6                            |  |  |
| Marking for electric machines operated with a converter clarified  | 29.15           | Х                                    |           |                               |  |  |
| Instruction material guidance clarified  | 30.1            | Х                                    |           |                               |  |  |
| Additional instruction material for electric machines added  | 30.3            |                                      |           | C7                            |  |  |
| Additional instruction material for cable glands added   | 30.5<br>A.5     |                                      |           | C8                            |  |  |

|   |                              |                                      | Type      |                               |
|---|------------------------------|--------------------------------------|-----------|-------------------------------|
| Explanation of the significance of the changes                | Clause                       | Minor<br>and<br>editorial<br>changes | Extension | Major<br>technical<br>changes |
| Allow ISO 10807 hose assemblies to be used with cable glands. | A.1                          |                                      | Х         |                               |
| Clarify testing with stainless steel mandrels                 | A.3                          | Х                                    |           |                               |
| Reduction of the time / slippage permitted                    | A.3.1.1                      |                                      | Х         |                               |
| Clarify impact testing of cable glands                        | A.3.3<br>Figure A.3          | Х                                    |           |                               |
| Clarified the order of tests                                  | A.3.4                        | Х                                    |           |                               |
| Clarified remarks   | Annex B                      | Х                                    |           |                               |
| Aligned Figure with text                                      | Figure C.1                   | Х                                    |           |                               |
| Clarified operation of electric machines from converters      | Annex D (informative )       | Х                                    |           |                               |
| Clarified temperature testing of electric machines            | Annex E<br>(informative      | Х                                    |           |                               |
| Flowchart for Cable Gland testing                             | Annex G<br>(informative<br>) | Х                                    |           |                               |
| Guidance of electric machine shaft voltages                   | Annex H (informative         | Х                                    |           |                               |

NOTE The technical changes referred to include the significance of technical changes in the revised IEC Standard, but they do not form an exhaustive list of all modifications from the previous version. More guidance may be found by referring to the Redline Version of the standard.

#### **Explanations:**

#### A) Definitions

Minor and editorial changes clarification

decrease of technical requirements

minor technical change editorial corrections

These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement.

#### **Extension** addition of technical options

These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore, these will not have to be considered for products in conformity with the preceding edition.

Major technical changesaddition of technical requirementsincrease of technical requirements

These are changes to technical requirements (addition, increase of the level or removal) made in a way that a product in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for

products in conformity with the preceding edition. For these changes additional information is provided in clause B) below.

NOTE These changes represent current technological knowledge. However, these changes should not normally have an influence on equipment already placed on the market.

#### B) Information about the background of changes

- A1 The dust layer requirements for EPL Da are unchanged from what previously existed in IEC 60079-18, Ed 4 and IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- A2 IEC 60079-28 now includes all requirements for optical radiation for all EPLs.
- A3 The COT requirements for EPL Gc or Dc are unchanged from what previously existed in IEC 60079-15, Ed 4, IEC 60079-18, Ed 4, and IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- A4 The dust layer requirements for EPL Db with a specified dust layer depth are unchanged from what previously existed in IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- B1 Dust layer requirements for EPL Db with a dust layer in a specified orientation have been added.
- C1 It is recognized that the new requirements were, in many cases, already applied. The change is to ensure that they are uniformly and consistently applied.
- C2 Require that the test be conducted at 4 kV DC.
- C3 The limitation applies to external surfaces of other than cable glands, blanking elements, thread adapters and bushings.
- C4 The added requirements for tool securing and marking are consistent with the approach in IEC 60079-15
- C5 Voltage values were changed following additional research due to the complicated assessment and sometimes unspecified construction of Li/Ion-cells. It was found that some voltage values previously stated were too low.
- C6 The now required EPL marking may be other than that permitted by the Level of Protection to account for limiting restrictions of material or plastic material surface area.
- C7 Additional instruction material for electric machines required to facilitate selection, installation, and maintenance.
- C8 Additional instruction material for cable glands required to facilitate selection and installation.

### Annex ZZ (informative)

### Relationship between this European Standard and the Essential Requirements of 2014/34/EU [2014 OJ L96] aimed to be covered

This European Standard has been prepared under a Commission's standardisation request M/BC/CEN/92/46 to provide one voluntary means of conforming to Essential Requirements of 2014/34/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to equipment and protective systems intended for use in potentially explosive atmospheres (recast).

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZZ.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of that Directive, and associated EFTA regulations.

Table ZZ.1 – Correspondence between this European Standard and Annex II of Directive 2014/34/EU [2014 OJ L96]

| Essential Requirements of 2014/34/EU | Clause(s) / sub-clause(s)<br>of this EN         | Remarks / Notes  |
|--------------------------------------|---|--|
| 1.0.1.                               | Entire standard                                 | Second indent only   |
| 1.0.2.                               | Entire standard including Annex ZY              | By reference to appropriate EPLs   |
| 1.0.3.                               | 3.84 and related references throughout document | In particular, use of "X" marking and related Specific Conditions of Use for Ex Equipment or Schedule of Limitations for Ex Components |
| 1.0.4.                               | 5 / 6.1   |  |
| 1.0.5.                               | 28.3 / 29 / Annex ZY                            |  |
| 1.0.6.                               | 30  |  |
| 1.1.1.                               | 7 / 8   |  |
| 1.1.2.                               | 8.5   |  |
| 1.1.3.                               | 6.3 / 7 / 8                                     |  |
| 1.2.1.                               | Entire standard                                 |  |
| 1.2.2.                               | Entire standard                                 |  |
| 1.2.3.                               | Not covered                                     |  |
| 1.2.4.                               | 5.3.2.3   |  |
| 1.2.5.                               | Not covered                                     |  |
| 1.2.6.                               | 6.3   |  |
| 1.2.7.                               | 6.1   |  |
| 1.2.8.                               | Not covered                                     |  |
| 1.2.9.                               | Not covered                                     | See EN 60079-1   |

| Essential Requirements of 2014/34/EU | Clause(s) / sub-clause(s)<br>of this EN | Remarks / Notes                             |
|--------------------------------------|---|---|
| 1.3.1.                               | (in part) 5 / 6.6                       |   |
| 1.3.2.                               | 7.4                                     |   |
| 1.3.3.                               | 6.4                                     |   |
| 1.3.4.                               | Not covered                             | See EN ISO 80079-36                         |
| 1.3.5.                               | Not covered                             |   |
| 1.4.1.                               | 6.1                                     |   |
| 1.4.2.                               | 6.1                                     |   |
| 1.5.                                 | Not covered                             |   |
| 1.6.1.                               | Not covered                             |   |
| 1.6.2.                               | Not covered                             |   |
| 1.6.3.                               | Not covered                             |   |
| 1.6.4.                               | 15 / Annex A                            |   |
| 1.6.5.                               | Not covered                             |   |
| 2.0.1.                               | Throughout document                     | Multiple requirements for Group I, EPL Ma   |
| 2.0.2.                               | Throughout document                     | Multiple requirements for Group I, EPL Mb   |
| 2.1.1.                               | Throughout document                     | Multiple requirements for Group II, EPL Ga  |
| 2.1.2.                               | Throughout document                     | Multiple requirements for Group III, EPL Da |
| 2.2.1.                               | Throughout document                     | Multiple requirements for Group II, EPL Gb  |
| 2.2.2                                | Throughout document                     | Multiple requirements for Group III, EPL Db |
| 2.3.1.                               | Throughout document                     | Multiple requirements for Group II, EPL Gc  |
| 2.3.2.                               | Throughout document                     | Multiple requirements for Group III, EPL Dc |
| 3.                                   | Not covered                             |   |

NOTE To confer a presumption of conformity with the relevant essential requirements of Directive 2014/34/EU, this standard has to be applied together with at least one of the supplemental standards giving the requirements for a specific Type of Protection. See Clause 1.

**WARNING 1**: Presumption of conformity stays valid only as long as a reference to this European standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

**WARNING 2**: Other Union legislation may be applicable to the product(s) falling within the scope of this standard.



IEC 60079-0

Edition 7.0 2017-12

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

**Explosive atmospheres –** 

Part 0: Equipment - General requirements

Atmosphères explosives -

Partie 0: Matériel - Exigences générales



### CONTENTS

| F | DREWO | RD  | 8  |
|---|-------|---|----|
| 1 | Scop  | e   | 15 |
| 2 | Norm  | ative references  | 16 |
| 3 | Term  | s and definitions   | 18 |
| 4 | Equip | oment grouping  | 36 |
|   | 4.1   | General   |    |
|   | 4.2   | Group I   |    |
|   | 4.3   | Group II  | 36 |
|   | 4.4   | Group III   | 36 |
|   | 4.5   | Equipment for a particular explosive gas atmosphere                                   | 37 |
| 5 | Tem   | peratures   | 37 |
|   | 5.1   | Environmental influences  | 37 |
|   | 5.1.1 | Ambient temperature   | 37 |
|   | 5.1.2 | External source of heating or cooling   | 37 |
|   | 5.2   | Service temperature   |    |
|   | 5.3   | Maximum surface temperature   |    |
|   | 5.3.1 |   |    |
|   | 5.3.2 | •   | 38 |
|   | 5.3.3 | Small component temperature for Group I or Group II electrical equipment              | 39 |
|   | 5.3.4 | Component temperature of smooth surfaces for Group I or Group II electrical equipment | 40 |
| 6 | Regi  | irements for all equipment  |    |
| Ü | 6.1   | General   |    |
|   | 6.2   | Mechanical strength of equipment  |    |
|   | 6.3   | Opening times   |    |
|   | 6.4   | Circulating currents in enclosures (e.g. of large electric machines)                  |    |
|   | 6.5   | Gasket retention  |    |
|   | 6.6   | Electromagnetic and ultrasonic energy radiating equipment                             |    |
|   | 6.6.1 |   |    |
|   | 6.6.2 | Radio frequency sources   | 42 |
|   | 6.6.3 | Ultrasonic sources  | 43 |
|   | 6.6.4 | Lasers, luminaires, and other non-divergent continuous wave optical sources           | 44 |
| 7 | Non-  | metallic enclosures and non-metallic parts of enclosures                              | 44 |
|   | 7.1   | General   | 44 |
|   | 7.1.1 | Applicability   | 44 |
|   | 7.1.2 | Specification of materials  | 44 |
|   | 7.2   | Thermal endurance   | 45 |
|   | 7.2.1 | Tests for thermal endurance   | 45 |
|   | 7.2.2 |   |    |
|   | 7.2.3 | 1   |    |
|   | 7.3   | Resistance to ultraviolet light   |    |
|   | 7.4   | Electrostatic charges on external non-metallic materials                              |    |
|   | 7.4.1 | 11 ,  |    |
|   | 7.4.2 | Avoidance of a build-up of electrostatic charge for Group I or Group II               | 47 |

|     | 7.4.3 | Avoidance of a build-up of electrostatic charge for Group III | 49 |
|-----|-------|---|----|
|     | 7.5   | Attached external conductive parts                            | 50 |
| 8   | Meta  | llic enclosures and metallic parts of enclosures              | 51 |
|     | 8.1   | Material composition  |    |
|     | 8.2   | Group I   |    |
|     | 8.3   | Group II  |    |
|     | 8.4   | Group III   |    |
|     | 8.5   | Copper Alloys   |    |
| 9   |       | eners   |    |
|     |       |   |    |
|     | 9.1   | General   |    |
|     | 9.2   | Special fasteners   |    |
|     | 9.3   | Holes for special fasteners                                   |    |
|     | 9.3.1 | 3 3   |    |
|     | 9.3.2 |   |    |
|     | 9.4   | Hexagon socket set screws                                     |    |
| 10  |       | ocking devices  |    |
| 11  | Bush  | ings  | 54 |
| 12  | (Rese | erved for future use)   | 54 |
| 13  | Ex C  | omponents   | 54 |
|     | 13.1  | General   |    |
|     | 13.2  | Mounting  |    |
|     | 13.3  | Internal mounting   |    |
|     | 13.4  | External mounting   |    |
|     | 13.4  | Ex Component certificate                                      |    |
| 11  |       | •   |    |
| 14  |       | ection facilities   |    |
|     | 14.1  | General   |    |
|     | 14.2  | Type of protection  |    |
|     | 14.3  | Creepage and clearance  |    |
| 15  | Conn  | ection facilities for earthing or bonding conductors          |    |
|     | 15.1  | Equipment requiring earthing or bonding                       | 56 |
|     | 15.1. | 1 Internal earthing   | 56 |
|     | 15.1. | 2 External bonding  | 56 |
|     | 15.2  | Equipment not requiring earthing                              | 56 |
|     | 15.3  | Size of protective earthing conductor connection              | 56 |
|     | 15.4  | Size of equipotential bonding conductor connection            | 57 |
|     | 15.5  | Protection against corrosion                                  | 57 |
|     | 15.6  | Secureness of electrical connections                          | 57 |
|     | 15.7  | Internal earth continuity plate                               | 57 |
| 16  | Entri | es into enclosures  |    |
|     | 16.1  | General   |    |
|     | 16.2  | Identification of entries                                     |    |
|     | 16.2  | Cable glands  |    |
|     |       |   |    |
|     | 16.4  | Blanking elements   |    |
|     | 16.5  | Thread adapters   |    |
|     | 16.6  | Temperature at branching point and entry point                |    |
| . – | 16.7  | Electrostatic charges of cable sheaths                        |    |
| 17  |       | lementary requirements for electric machines                  |    |
|     | 17.1  | General   | 60 |

|     | 17.2  | Ventilation   | 60 |
|-----|-------|---|----|
|     | 17.2. | 1 Ventilation openings  | 60 |
|     | 17.2. | 2 Materials for external fans   | 60 |
|     | 17.2. | 3 Cooling fans of rotating electric machines  | 60 |
|     | 17.2. | 4 Auxiliary motor cooling fans  | 61 |
|     | 17.2. | 5 Room ventilating fans   | 61 |
|     | 17.3  | Bearings  | 62 |
| 18  | Supp  | olementary requirements for switchgear  | 62 |
|     | 18.1  | Flammable dielectric  | 62 |
|     | 18.2  | Disconnectors   | 62 |
|     | 18.3  | Group I – Provisions for locking  | 63 |
|     | 18.4  | Doors and covers  | 63 |
| 19  | Rese  | erved for future use  | 63 |
| 20  |       | plementary requirements for external plugs, socket outlets and connectors for wiring connection | 63 |
|     | 20.1  | General   |    |
|     | 20.1  | Explosive gas atmospheres   |    |
|     | 20.2  | Explosive dust atmospheres  |    |
|     | 20.4  | Energized plugs   |    |
| 21  |       | plementary requirements for luminaires  |    |
| _ ' | 21.1  | General   |    |
|     | 21.1  | Covers for luminaires of EPL Mb, EPL Gb, or EPL Db  |    |
|     | 21.2  | Covers for luminaires of EPL Gc or EPL Dc   |    |
|     | 21.3  | Sodium lamps  |    |
| วว  |       | plementary requirements for caplights and handlights  |    |
| 22  |       |   |    |
|     | 22.1  | Group I caplights   |    |
| ~~  | 22.2  | Group II and Group III caplights and handlights   |    |
| 23  |       | pment incorporating cells and batteries   |    |
|     | 23.1  | General   |    |
|     | 23.2  | Interconnection of cells to form batteries  |    |
|     | 23.3  | Cell types  |    |
|     | 23.4  | Cells in a battery  |    |
|     | 23.5  | Ratings of batteries  |    |
|     | 23.6  | Interchangeability  | 69 |
|     | 23.7  | Charging of primary batteries   |    |
|     | 23.8  | Leakage   |    |
|     | 23.9  | Connections   |    |
|     | 23.10 | Orientation   |    |
|     | 23.11 | Replacement of cells or batteries   |    |
|     | 23.12 | Replaceable battery pack  |    |
| 24  | Docu  | ımentation  | 70 |
| 25  | Com   | pliance of prototype or sample with documents   | 70 |
| 26  | Туре  | tests   | 70 |
|     | 26.1  | General   | 70 |
|     | 26.2  | Test configuration  |    |
|     | 26.3  | Tests in explosive test mixtures  |    |
|     | 26.4  | Tests of enclosures   |    |
|     | 26.4. |   |    |
|     |       |   |    |

#### IEC 60079-0:2017 © IEC 2017

#### **- 5 -**

| 26.4.   | 2 Resistance to impact   | 73 |
|---------|--|----|
| 26.4.   | 3 Drop test  | 74 |
| 26.4.   | 4 Acceptance criteria  | 75 |
| 26.4.   | 5 Degree of protection (IP) by enclosures                                | 75 |
| 26.5    | Thermal tests  | 76 |
| 26.5.   | 1 Temperature measurement  | 76 |
| 26.5.   | 2 Thermal shock test   | 78 |
| 26.5.   | 3 Small component ignition test (Group I and Group II)                   | 78 |
| 26.6    | Torque test for bushings   | 79 |
| 26.6.   | 1 Test procedure   | 79 |
| 26.6.   | 2 Acceptance criteria  | 80 |
| 26.7    | Non-metallic enclosures or non-metallic parts of enclosures              | 80 |
| 26.7.   | 1 General  | 80 |
| 26.7.   | 2 Test temperatures  | 80 |
| 26.8    | Thermal endurance to heat  | 80 |
| 26.9    | Thermal endurance to cold  | 81 |
| 26.10   | Resistance to UV light   | 81 |
| 26.10   | 0.1 General  | 81 |
| 26.10   | 0.2 Light exposure   | 82 |
| 26.10   | 0.3 Acceptance criteria  | 82 |
| 26.11   | Resistance to chemical agents for Group I equipment                      | 82 |
| 26.12   | Earth continuity   | 83 |
| 26.13   | Surface resistance test of parts of enclosures of non-metallic materials | 84 |
| 26.14   | Measurement of capacitance   | 85 |
| 26.14   | 4.1 General  | 85 |
| 26.14   | 4.2 Test procedure   | 85 |
| 26.15   | Verification of ratings of ventilating fans                              | 86 |
| 26.16   | Alternative qualification of elastomeric sealing O-rings                 | 86 |
| 26.17   | Transferred charge test  | 86 |
| 26.17   | 7.1 Test equipment   | 86 |
| 26.17   | 7.2 Test sample  | 87 |
| 26.17   | 7.3 Test procedure   | 87 |
| 27 Rout | ine tests  | 88 |
| 28 Manu | ufacturer's responsibility   | 88 |
| 28.1    | Conformity with the documentation  | 88 |
| 28.2    | Certificate  |    |
| 28.3    | Responsibility for marking   |    |
| 29 Mark | ing  | 89 |
| 29.1    | Applicability  | 89 |
| 29.2    | Location   |    |
| 29.3    | General  |    |
| 29.4    | Ex marking for explosive gas atmospheres                                 |    |
| 29.5    | Ex marking for explosive dust atmospheres                                |    |
| 29.6    | Combined types (or levels) of protection                                 |    |
| 29.7    | Multiple types of protection   |    |
| 29.8    | Ga equipment using two independent Gb types (or levels) of protection    |    |
| 29.9    | Boundary wall  |    |
| 29.10   | Ex Components  |    |
|         | Small Ex Equipment and small Ex Components                               | 96 |

| 29.12      | Extremely small Ex Equipment and extremely small Ex Components  | 96  |
|------------|---|-----|
| 29.13      | Warning markings  | 96  |
| 29.14      | Cells and batteries   | 97  |
| 29.15      | Electric machines operated with a converter   | 97  |
| 29.16      | Examples of marking   | 98  |
| 30 Instru  | uctions   | 101 |
| 30.1       | General   | 101 |
| 30.2       | Cells and batteries   | 102 |
| 30.3       | Electric machines   | 103 |
| 30.4       | Ventilating fans  | 103 |
| 30.5       | Cable glands  |     |
| Annex A (  | normative) Supplementary requirements for cable glands  | 105 |
| A.1        | General   | 105 |
| A.2        | Constructional requirements   | 105 |
| A.2.1      | Cable sealing   | 105 |
| A.2.2      | Filling compounds   | 106 |
| A.2.3      | Clamping  | 106 |
| A.2.4      | Lead-in of cable  | 106 |
| A.2.5      | Release by a tool   | 107 |
| A.2.6      | Fixing  | 107 |
| A.2.7      | Degree of protection  | 107 |
| A.3        | Type tests  | 107 |
| A.3.1      | Tests of clamping of non-armoured and braided cables  | 107 |
| A.3.2      | 1 0   |     |
| A.3.3      | Type test for resistance to impact  | 111 |
| A.3.4      | 0 1 7 9   |     |
| A.4        | Marking   |     |
| A.4.1      | ğ ğ   |     |
| A.4.2      |   |     |
| A.5        | Instructions  |     |
| Annex B (  | normative) Requirements for Ex Components   | 115 |
| Annex C (  | informative) Example of rig for resistance to impact test   | 118 |
| Annex D (  | informative) Electric machines connected to converters  | 119 |
| Annex E (  | informative) Temperature evaluation of electric machines  | 120 |
|            | informative) Guidance flowchart for tests of non-metallic enclosures or non-<br>arts of enclosures (26.4) | 123 |
| •          | (informative) Guidance flowchart for tests of cable glands  |     |
|            | informative) Shaft voltages resulting in motor bearing or shaft brush                                     | 127 |
|            | Discharge energy calculation  | 125 |
| H.1        | General   | 125 |
| H.2        | Assessment of the risk of ignition using ignition energy calculation                                      | 125 |
| H.3        | Shaft voltage determination for a rotating machine  | 126 |
| H.4        | Capacitance "C" calculation for a rotating machine  | 126 |
| H.5        | Energy "E" calculation for a rotating machine   | 129 |
| H.6        | Assessment using reference curves   | 129 |
| Bibliograp | hy  | 131 |
|            |   |     |
| Figure 1 - | - Typical hattery examples  | 20  |

#### IEC 60079-0:2017 © IEC 2017

|   | 7 |   |
|---|---|---|
| _ | - | _ |

| Figure 2 – Typical battery compartment   | 21  |
|--|-----|
| Figure 3 – Typical replaceable battery pack  | 22  |
| Figure 4 – Tolerances and clearance for threaded fasteners   | 53  |
| Figure 5 – Contact surface under head of fastener with a reduced shank   | 54  |
| Figure 6 – Cable gland   | 59  |
| Figure 7 – Conduit entry   | 59  |
| Figure 8 – Assembly of test sample for earth-continuity test   | 84  |
| Figure 9 – Test piece with painted electrodes  | 85  |
| Figure 10 – Compression set of an O-ring   | 86  |
| Figure A.1 – Illustration of the terms used for cable glands   | 106 |
| Figure A.2 – Rounded edge of the point of entry of the flexible cable  | 107 |
| Figure A.3 – Example of rig for resistance to impact test  | 112 |
| Figure C.1 – Example of rig for resistance to impact test  | 118 |
| Figure F.1 – Non-metallic enclosures or non-metallic parts of enclosures   | 123 |
| Figure H.1 – Capacitance stored in bearing clearance of sleeve bearing Between journal and outer bearing housing | 128 |
| Figure H.2 – Air-gap between stator and rotor  | 128 |
| Figure H.3 – Typical surfaces that form capacitors from the motor shaft to ground                                | 129 |
| Figure H.4 – Capacitive ignition curves  | 130 |
| Table 1 – Ambient temperatures in service and additional marking   | 37  |
| Table 2 – Classification of maximum surface temperatures for Group II electrical equipment                       | 38  |
| Table 3 – Assessment of temperature classification according to component size                                   |     |
| Table 4 – Assessment of temperature classification Component surface area $\geq$ 20 mm <sup>2</sup> .            | 40  |
| Table 5 – Threshold power  | 43  |
| Table 6 – Threshold energy   | 43  |
| Table 7 – Limitation of surface areas  | 48  |
| Table 8 – Maximum diameter or width  | 49  |
| Table 9 – Limitation of thickness of non-metallic layer  | 49  |
| Table 10 – Maximum acceptable transferred charge   | 49  |
| Table 11 – Maximum capacitance of unearthed conductive parts   | 51  |
| Table 12 – Minimum cross-sectional area of PE conductors   | 57  |
| Table 13 – Primary cells   | 66  |
| Table 14 – Secondary cells   | 68  |
| Table 15 – Tests for resistance to impact  | 74  |
| Table 16 – Torque to be applied to the stem of bushing used for connection facilities                            | 79  |
| Table 17 – Thermal endurance test  | 80  |
| Table 18 – Text of warning markings  | 97  |
| Table 19 – Example of type-test converter parameters   | 103 |
| Table B.1 – Applicability of clauses to Ex Components  | 115 |
| Table H.1 – Maximum permitted energy   | 126 |