## INTERNATIONAL STANDARD

ISO 16283-2

Third edition 2020-07

# Acoustics — Field measurement of sound insulation in buildings and of building elements —

### Part 2: **Impact sound insulation**

Acoustique — Mesurage in situ de l'isolation acoustique des bâtiments et des éléments de construction —

Partie 2: Isolation des bruits d'impacts





### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Coı	Contents							
Fore	word			<b>v</b>				
Intro	oductio	n		vi				
1	Scop	e		1				
2	-	•						
		native references 1						
3	Terms and definitions							
4	Instr	nstrumentation						
	4.1		1					
	4.2		ition					
	4.3	ation						
5	Frequency range							
	5.1	F F O F F						
	5.2 Rubber ball as the impact source							
6	General							
7	Defa	Default procedure for sound pressure level measurement						
	7.1		1					
	7.2	Genera	ition of sound field	7				
		7.2.1	General					
		7.2.2	Impact source positions for the tapping machine as impact source					
	7.2	7.2.3	Impact source positions for the rubber ball as impact source					
	7.3	7.3.1	nicrophone positions for the tapping machine or rubber ball as impact source  General					
		7.3.1	Number of measurements					
		7.3.3	Tapping machine operated at more than one position					
		7.3.4	Rubber ball operated at more than one position	9				
	7.4	Mecha	nized continuously moving microphone for the tapping machine as impact so					
		7.4.1	General					
		7.4.2	Number of measurements					
	7 -	7.4.3	Tapping machine operated at more than one position					
	7.5	мапиа 7.5.1	lly scanned microphone for the tapping machine as impact source					
		7.5.1	Number of measurements					
		7.5.3	Tapping machine operated at more than one position					
		7.5.4	Circle					
		7.5.5	Helix					
		7.5.6	Cylindrical-type					
	<b>5</b> (	7.5.7	Three semicircles					
	7.6 7.7	Minimum distances for microphone positions						
	7.7	7.7.1	ing times for the tapping machine as impact sourceFixed microphone positions	12				
		7.7.2	Mechanized continuously moving microphone	13				
		7.7.3	Manually scanned microphone	13				
	7.8	Calcula	ation of energy-average sound pressure levels	13				
		7.8.1	Fixed microphone positions for the tapping machine as impact source	13				
		7.8.2	Mechanized continuously moving microphone and manually scanned	4.0				
		702	microphone for the tapping machine as impact source.	13				
		7.8.3	Fixed microphone positions for the rubber ball as impact source	14				
8	Low-	frequen	cy procedure for sound pressure level measurement for the tapping					
			npact source					
	8.1 8.2		ıltion of sound field					
	0.2	8.2.1						

### ISO 16283-2:2020(E)

			8.2.2 Impact source positions				
		8.3 8.4 8.5	Microphone positions				
			Averaging timeCalculation of low-frequency energy-average impact sound pressure levels				
	0						
	9	<b>Back</b> 9.1	ground noise (default and low-frequency procedure)  General				
		9.2	Correction to the signal level for background noise				
	10	Reverberation time in the receiving room (default and low-frequency procedure)					
		10.1	General	18			
		10.2	Generation of sound field				
		10.3 10.4	Default procedure				
Copy via ILNAS e-Shop		10.4	Interrupted noise method				
		10.6	Integrated impulse response method				
	11	Conversion to octave bands		19			
	12	Expression of results					
	13	Uncertainty					
	14	Test report					
	Annex	nex A (normative) Impact sources					
	Annex B (normative) Requirements for loudspeakers used for reverberation time						
v yc	measurements measurements for following used for reverberation time						
	Annex C (informative) Forms for the expression of results						
yluc	Annex	Annex D (informative) Additional guidance					
Annex E (informative) Horizontal measurements — Examples of suitable impact source							
ević		and n	nicrophone positions	36			
SO 16283-2:2020 - Preview only	Annex	Annex F (informative) Vertical measurements — Examples of suitable impact source and					
020		micro	phone positions	40			
-2:2	Bibliography						
283							
) 16							
ISC							

### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 126, *Acoustic properties of building elements and of buildings*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 16283-2:2018), which has been technically revised.

The main changes compared to the previous edition are as follows:

- a) <u>Clause 6</u>, Note 3 removed;
- b) in the helical path (7.5.5) distance of the microphone position to the ceiling changed to minimum 0,5 m;
- c)  $L'_{iA.Fmax.VT}$  added to the expression of results and to Figure C.3.

A list of all parts in the ISO 16283 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

### Introduction

ISO 16283 (all parts) describes procedures for field measurements of sound insulation in buildings. Airborne, impact and façade sound insulation are described in ISO 16283-1, this document (ISO 16283-2) and ISO 16283-3, respectively.

Field sound insulation measurements that were described previously in ISO 140-4<sup>1)</sup>, ISO 140-5<sup>2)</sup>, and ISO 140-7<sup>3)</sup> were a) primarily intended for measurements where the sound field could be considered to be diffuse, and b) not explicit as to whether operators could be present in the rooms during the measurement. ISO 16283 (all parts) differs from ISO 140-4, ISO 140-5, and ISO 140-7 in that:

- a) it applies to rooms in which the sound field may or may not approximate to a diffuse field;
- b) it clarifies how operators can measure the sound field using a hand-held microphone or sound level meter;
- c) it includes additional guidance that was previously contained in ISO 140-14<sup>4</sup>).

NOTE Survey test methods for field measurements of airborne and impact sound insulation are dealt with in ISO 10052.

Two impact sources are described: the tapping machine and the rubber ball. These impact sources do not exactly replicate all possible types of real impacts on floors or stairs in buildings.

The tapping machine can be used to assess a variety of light, hard impacts such as footsteps from walkers wearing hard-heeled footwear or dropped objects. A single number quantity can be calculated using the rating procedures in ISO 717-2. This single number quantity links the measured impact sound insulation using the tapping machine to subjective assessment of general impacts in dwellings that occur on floors or stairs in a building. The tapping machine is also well-suited to the prediction of impact sound insulation using ISO 12354-2. These two aspects facilitate the specification of impact sound insulation in national building requirements using only measurements with the tapping machine as an impact source.

The rubber ball can be used to assess heavy, soft impacts such as from walkers in bare feet or children jumping, as well as quantifying absolute values that can be related to human disturbance in terms of a Fast time-weighted maximum sound pressure level.

<sup>1)</sup> Withdrawn.

<sup>2)</sup> Withdrawn.

<sup>3)</sup> Withdrawn.

<sup>4)</sup> Withdrawn.

### Acoustics — Field measurement of sound insulation in buildings and of building elements —

### Part 2:

### **Impact sound insulation**

### 1 Scope

This document specifies procedures to determine the impact sound insulation using sound pressure measurements with an impact source operating on a floor or stairs in a building. These procedures are intended for room volumes in the range from  $10~\text{m}^3$  to  $250~\text{m}^3$  in the frequency range from 50~Hz to 5~000~Hz. The test results can be used to quantify, assess and compare the impact sound insulation in unfurnished or furnished rooms where the sound field may or may not approximate to a diffuse field.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3382-2, Acoustics — Measurement of room acoustic parameters — Part 2: Reverberation time in ordinary rooms

ISO 12999-1, Acoustics — Determination and application of measurement uncertainties in building acoustics — Part 1: Sound insulation

ISO 18233, Acoustics — Application of new measurement methods in building and room acoustics

ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories

IEC 60942, Electroacoustics — Sound calibrators

IEC 61183, Electroacoustics — Random-incidence and diffuse-field calibration of sound level meters

IEC 61260 (all parts), Electroacoustics — Octave-band and fractional-octave-band filters

IEC 61672-1, Electroacoustics — Sound level meters — Part 1: Specifications

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>