

Edition 1.0 2020-07

# PUBLICLY AVAILABLE SPECIFICATION

## **PRE-STANDARD**

Connectors for electrical and electronic equipment – Product requirements – Part 2-010: Circular connectors – Detail specification for push-pull connectors with locking mechanism, based on mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113



### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

**IEC Central Office** 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22,000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

### EC Glossary / std.iec.ch/glossary

67 000 electrotechnisal terminology entries in English and French extracted from the Terms and Definitions clause of EC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



Edition 1.0 2020-07

## PUBLICLY AVAILABLE SPECIFICATION

### **PRE-STANDARD**

Connectors for electrical and electronic equipment – Product requirements – Part 2-010: Circular connectors – Detail specification for push-pull connectors with locking mechanism, based on mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 31.220.10

ISBN 978-2-8322-8549-7

Warning! Make sure that you obtained this publication from an authorized distributor.

### CONTENTS

Г	JREWO	RD	5
IN	TRODU	CTION	7
1	Scop	e	8
2	Norm	ative references	8
3	Term	s and definitions	10
4	Tech	nical information	10
-	4.1	System of levels	
	4.1.1		
	4.1.2		10
	4.2	Classification into climatic categories	11
	4.3	Contact terminations	
	4.4	Available connector codings	11
	4.5	Ratings	12
	4.6	Ratings	12
	4.7	Safety aspects	
5	Dime	nsional information	12
	5.1	General	12
	5.2	GeneralSurvey of styles and variants	12
	5.2.1	General	12
	5.2.2	Fixed connectors	12
	5.2.3		19
	5.3	Interface dimension	28
	5.3.1	Outer push-pull locking: male fixed connector side view	28
	5.5.1	Outer phon-ball locking. Inale lixed connector side view	20
	5.3.2	Outer push-pull locking: female fixed connector side view with details	
	5.3.2	Outer push pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 .	
		Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 . Inner push-pull locking: female fixed connector side view and male free	28
	5.3.2 5.3.3	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both	28 31
6	5.3.2 5.3.3 5.4	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both	28 31 33
6	5.3.2 5.3.3 5.4 Char	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both Gauges	28 31 33 34
6	5.3.2 5.3.3 5.4 Char 6.1	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both Gauges acteristics	28 31 33 34 34
6	5.3.2 5.3.3 5.4 Char 6.1 6.2	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both Gauges classification into climatic category Electrical characteristics	28 31 33 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.1 6.2 6.2.1	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics	28 31 33 34 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.1 6.2 6.2.1 6.2.2	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree.	28 31 33 34 34 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof Rated voltage – Rated impulse voltage – Pollution degree Current-carrying capacity	28 31 33 34 34 34 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.1 6.2 6.2.1 6.2.2	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance.	28 31 33 34 34 34 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.1 6.2 6.2.1 6.2.2 6.2.3 6.2.4	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance.	28 31 34 34 34 34 34 34 34 34 34
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges	28 31 34 34 34 34 34 34 34 35
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 . Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance.	28 31 34 34 34 34 34 34 35 35 35
6	5.3.2 5.3.3 5.4 Char 6.1 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 . Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category . Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance. Mechanical characteristics Mating interface.	28 31 34 34 34 34 34 34 35 35 35 35
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 . Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance. Mechanical characteristics Mating interface.	28 31 34 34 34 34 34 34 35 35 35 35 35 35
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1 6.3.2	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics. Classification into climatic category . Electrical characteristics. Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance. Insulation resistance. Transmission performance. Mechanical characteristics Mating interface. Push-pull locking mechanism.	28 31 34 34 34 34 34 34 35 35 35 35 35 35 35 35 35
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1 6.3.2 6.4	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics. Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance. Mechanical characteristics Mating interface Push-pull locking mechanism. Other characteristics Vibration (sinusoidal).	28 31 34 34 34 34 34 34 35 35 35 35 35 35 35 36 37
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1 6.3.2 6.4 6.4.1	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance. Mechanical characteristics Mating interface. Push-pull locking mechanism. Other characteristics Vibration (sinusoidal). Shock	28 31 34 34 34 34 34 34 35 35 35 35 35 35 37 37
6	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1 6.3.2 6.4 6.4.1 6.4.2 6.4.3	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2. Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree. Current-carrying capacity. Contact resistance Insulation resistance. Transmission performance. Mechanical characteristics Mating interface. Push-pull locking mechanism. Other characteristics Vibration (sinusoidal). Shock	28 31 34 34 34 34 34 34 35 35 35 35 35 35 35 37 37 37
	5.3.2 5.3.3 5.4 Char 6.2 6.2.1 6.2.2 6.2.3 6.2.4 6.2.5 6.2.6 6.3 6.3.1 6.3.2 6.4 6.4.1 6.4.2 6.4.3	Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2 . Inner push-pull locking: female fixed connector side view and male free connector side view with details for both. Gauges acteristics Classification into climatic category Electrical characteristics Voltage proof. Rated voltage – Rated impulse voltage – Pollution degree Current-carrying capacity. Contact resistance Insulation resistance Transmission performance. Mechanical characteristics Mating interface Push-pull locking mechanism. Other characteristics Vibration (sinusoidal) Shock Degree of protection provided by enclosures (IP-code).	28 31 34 34 34 34 34 34 35 35 35 35 35 35 37 37 37 37

7.2.1	Test group P – Preliminary	
7.2.2	Test group AP – Dynamic/climatic	
7.2.3	Test group BP – Mechanical endurance	
7.2.4	Test group CP – Electrical load	
7.2.5	Test group DP – Chemical resistivity	
7.2.6	Test group EP – Connection method tests	
7.2.7	Test group FP – Electrical transmission requirements	
Annex A (info	rmative) Diameter of the female connector body	40
Bibliography		41

Figure 1 – Tube insert, male contacts, mounting without thread (thread on tube) and without outer push-pull locking	3
Figure 2 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, square flange front mounting	4
Figure 3 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,514	4
Figure 4 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5	5
Figure 5 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5	5
Figure 6 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5	6
Figure 7 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation	6
Figure 8 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5	7
Figure 9 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5	7
Figure 10 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5	8
Figure 11 – Kixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation	8
Figure 12 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5	9
Figure 13 – Rewireable connector, male contacts, straight version, with outer push- pull locking	0
Figure 14 – Rewireable connector, male contacts, angled version, with outer push-pull locking	0
Figure 15 – Non-rewireable connector, male contacts, straight version, with outer push-pull locking	1
Figure 16 – Non-rewireable connector, male contacts, angled version, with outer push- pull locking	2
Figure 17 – Rewireable connector, female contacts, straight version, with outer push- pull locking	2
Figure 18 – Rewireable connector, female contacts, angled version, with outer push- pull locking	3
Figure 19 – Non-rewireable connector, female contacts, straight version, with outer push-pull locking	4

Figure 20 – Non-rewireable connector, female contacts, angled version, with outer push-pull locking	25
Figure 21 – Rewireable connector, male contacts, straight version, with inner push-pull locking	25
Figure 22 – Rewireable connector, male contacts, angled version, with inner push-pull locking	26
Figure 23 – Non-rewireable connector, male contacts, straight version, with inner push- pull locking	27
Figure 24 – Non-rewireable connector, male contacts, angled version, with inner push- pull locking	27
Figure 25 – Outer push-pull locking: male fixed connector side view	28
Figure 26 – Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connector	30
Figure 27 – Inner push-pull-locking: female fixed connector side view and male free connector side view with details for both	32
Figure A.1 – Diameter of the female connector body	40
Table 1 – Available connector codings	11
Table 2 – Styles of fixed connectors	13
Table 3 – Styles of free connectors	19
Table 4 – Dimensions of style JM-OP, Figure 13	20
Table 5 – Dimensions of style KM-OP, Figure 14	21
Table 6 – Dimensions of style LM-OP, Figure 15	21
Table 7 – Dimensions of style MM-OP, Figure 16	22
Table 8 – Dimensions of style JF-OP, Figure 17	23
Table 9 – Dimensions of style KF-OP, Figure 18	23
Table 10 - Dimensions of style LF-OP, Figure 19	24
Table 11 - Dimensions of style MF-OR, Figure 20	25
Table 12 – Dimensions of style JM-IP, Figure 21	26
Table 13 – Dimensions of style KM-IP, Figure 22	26
Table 14 - Dimensions of style LM-IP, Figure 23	27
Table 15 – Dimensions of style MM-OP, Figure 24	27
Table 16 – Dimensions of fixed connector with push-pull housing and male contacts	28
Table 17 – Dimensions for Figure 17	30
Table 18 – Dimensions for Figure 27	33
Table 19 – Climatic category	34
Table 20 – Insertion and withdrawal forces for the locking mechanism	36
Table 21 – Number of test specimens	38
Table 22 – Test group BP	39
Table A.1 – Diameter of the female connector body, dimension X	40

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

### Part 2-010: Circular connectors – Detail specification for push-pull connectors with locking mechanism, based on mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 61076-2-010 has been processed by subcommittee 48B: Electrical connectors, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
48B/2796/DPAS	48B/2817/RVDPAS

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

An International Standard is under preparation by IEC SC48B, to be published as IEC 61076-2-010 (if approved). This PAS will be withdrawn upon publication of the International Standard.

A list of all parts in the IEC 61076 series, published under the general title Connectors for electrical and electronic equipment – Product requirements, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

### IEC PAS 61076-2-010:2020 © IEC 2020 - 7 -

### IEC SC 48B - Electrical connectors IEC PAS 61076-2-010 Ed. 1 Specification available from: IEC General secretariat or from the addresses shown on the inside cover. ELECTRONIC COMPONENTS DETAIL SPECIFICATION in accordance with IEC 61076-1 Circular M12 connectors with push-pull locking for power, signal and data transmission Fixed connectors with male and female contacts, mateable with M12 screw or push-pull plugs Free cable connectors with male of temale contacts with push-pull or screw locking Rewireable - Non-rewireable Fixed connectors, with front, rear or single hole mounting Straight and right-angled free cable connectors IEC

### INTRODUCTION