

English Version

Agricultural and forestry machinery - Environmental requirements for dusters

Matériel agricole et forestier - Exigences
environnementales relatives aux poudreuses

Land- und forstwirtschaftliche Maschinen -
Umweltanforderungen an Stäubegeräte

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 144.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword	3
Introduction	4
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions.....	5
4 Requirements.....	5
4.1 General.....	5
4.2 Hopper(s).....	6
4.3 Fan.....	7
4.4 Electrostatic discharge device.....	7
4.5 Measuring systems, controls and regulation systems.....	7
4.6 Outlets.....	7
5 Test methods	7
5.1 Test materials and equipment.....	7
5.2 Estimation of the hopper maximum capacity.....	8
5.3 Estimation of hopper graduation scale.....	8
5.4 Residual volume of the hopper	8
5.5 Control of the tightness of the hopper and the lid	9
5.6 Measurement of the fan rotation speed.....	9
5.7 Measurement of the air speed symmetry on the two sides of the duster.....	9
6 Operator manual.....	10
Annex A (informative) Check of the air speed symmetry on the two side of the duster	11
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2006/42/EC aimed to be covered	12
Bibliography	13

European foreword

This document (prEN 17744:2022) has been prepared by Technical Committee CEN/TC 144 “Tractors and machinery for agriculture and forestry”, the secretariat of which is held by AFNOR.

This document is currently submitted to the CEN Enquiry.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s) / Regulation(s).

For relationship with EU Directive(s) / Regulation(s), see informative Annex ZA, which is an integral part of this document.

Introduction

The Amendment of the Machinery Directive considers also the environmental requirements of the equipment for the pesticide application (PAE).

To allow to fulfil these requirements, the harmonized standard series EN 16119 has been produced. However, these standards do not include the dusters that are widely distributed in Europe and abroad.

This document defines the environmental requirements of the dusters and the methods to measure them.

It will help duster manufacturers in fulfilling the environmental requirements mentioned in the Amendment of the Machinery Directive.

This document is a type-C standard as stated in EN ISO 12100. This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document. The machinery concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document. When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

1 Scope

This document specifies general requirements and their test methods for dusters for applying formulated products in the form of dust with regard to minimizing the potential risk of environmental contamination during use.

Hand operated portable dusters (knapsack) are not included in this document.

This document deals with all the significant environmental hazards related to the duster.

This document is not applicable to dusters manufactured before the date of its publication.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5681:2020, *Equipment for crop protection — Vocabulary*

ISO 9357:1990, *Equipment for crop protection — Agricultural sprayers — Tank nominal volume and filling hole diameter*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5681:2020 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

duster

appliance for applying formulated products in the form of dust

3.2

device for dust extraction

mechanism which allows the transfer of the dust from the hopper to the outlets in a constant predetermined flow rate

3.3

hopper nominal capacity

volume indicated by the maximum filling level marked on the hopper when placed on a level horizontal surface

4 Requirements

4.1 General

Duster and their components shall be reliable and so designed that they can be used in accordance with their intended use as described in the operator manual, in order to minimize the potential risk of environmental contamination.

It shall be possible to connect the necessary measuring instruments to the duster to check its functioning.

Duster shall be designed so that a suitable distribution and deposition can be achieved. This shall be characterized by minimizing losses to non-target areas.

The duster shall be designed and constructed to minimize losses of plant protection products during application and after the application function has been switched off.

It shall be designed and constructed to facilitate the changing of worn parts without contaminating the environment.

Compliance shall be checked by (visual inspection, measurements, functional test, or testing) as appropriate according to Clause 5.

4.2 Hopper(s)

4.2.1 Filling opening

It shall be present a system able to minimize the risk that undesirable materials of more than 20 mm will cause blockages (for example presence of a grid, deflector) and influence the flow rate or transversal distribution in a negative way.

The filling hole diameter of the hopper shall at least comply with ISO 9357:1990.

It shall be present a system able to minimize the risk that undesirable materials of more than 20 mm will cause blockages (for example presence of a grid, deflector) and influence the flow rate or transversal distribution in a negative way.

The filling hole diameter of the hopper shall at least comply with ISO 9357:1990.

4.2.2 Capacity

The hopper's total capacity shall be at least 5 % more than its nominal capacity as determined in 5.2.

4.2.3 Level indicator

It shall be possible to determine the level of product that is in the hopper.

The scale shall cover at least 10 % to 100 % of the nominal volume and have a graduation for at least each 10 % of the nominal volume for hoppers with >600 l capacity.

Hoppers within 100 l to 600 l capacity shall have a graduation for each 20 % of the nominal volume.

Hoppers with <100 l capacity shall have a graduation for each 30 % of the nominal volume.

These requirements are not applied to hoppers with ≤ 30 l capacity as indicated in 5.3.

The accuracy of the graduation marks shall be within $\pm 15\%$ of the actual value as indicated in 5.3.

4.2.4 Lid

The hopper shall be equipped with a suitable lid that can close tightly to prevent any accidental opening and prevent the dispersion of material and protect the content against entry of water or dust.

In duster with pneumatic extraction system the lid shall be tight (pressure hopper).

This shall be checked following 5.5.

4.2.5 Accessibility

Hopper(s) shall be designed and mounted on the duster to be accessible in a safe way as indicated below.

The filling hole of the hopper shall be so positioned that the height from the ground or platform is not more than 1 250 mm.

The horizontal reach between the rim of the hole and the outer edge of any part of the sprayer which could hinder the operator shall not be more than 300 mm at the operator filling position.