

DRAFT INTERNATIONAL STANDARD

ISO/DIS 21771-1.2

ISO/TC 60/SC 1

Secretariat: BSI

Voting begins on:
2023-12-21

Voting terminates on:
2024-02-15

Cylindrical involute gears and gear pairs —

Part 1: Concepts and geometry

ICS: 21.200

ISO/DIS 21771-1.2 - Preview only Copy via ILNAS e-Shop

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number
ISO/DIS 21771-1.2:2023(E)

© ISO 2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols, subscripts and units	1
3.1 Terms and definitions	1
3.2 Symbols	1
3.3 Subscripts	8
3.4 Units and conventions	9
3.4.1 Units	9
3.4.2 Conventions	9
3.5 Definitions	10
3.5.1 Basic rack tooth profile for involute gear teeth	10
3.5.2 Counterpart rack tooth profile	10
3.5.3 Tip alteration coefficient, k	10
4 Individual cylindrical gears	10
4.1 General	10
4.2 Concepts for an individual gear	10
4.2.1 Gear, cylindrical gear, external gear and internal gear	10
4.2.2 Tooth system, external teeth and internal teeth	10
4.2.3 Tooth and space	11
4.2.4 Tooth system parameters	11
4.2.5 Number of teeth and sign of number of teeth	11
4.2.6 Tooth number	11
4.2.7 Top land and bottom land	12
4.2.8 Tooth flanks and flank sections	12
4.3 Reference surfaces, datum lines and reference quantities	13
4.3.1 Reference surface, datum face	13
4.3.2 Reference rack	13
4.3.3 Basic rack tooth profile for involute gear teeth	14
4.3.4 Reference cylinder, reference circle, reference diameter	15
4.3.5 Gear axis	15
4.3.6 Sections through a cylindrical gear	15
4.3.7 Module	16
4.3.8 Diametral pitch	16
4.3.9 Facewidth	16
4.3.10 Profile shift, profile shift coefficient and sign of profile shift	17
4.4 Involute helicoids	18
4.4.1 Generator of involute helicoids	18
4.4.2 Base cylinder, base circle, base diameter	19
4.4.3 Transverse pressure angle at a point, transverse pressure angle	19
4.4.4 Normal pressure angle at a point, normal pressure angle	20
4.4.5 Involute function	21
4.4.6 Lead	21
4.4.7 Helix angle, lead angle	21
4.4.8 Flank direction	22
4.4.9 Roll angle of the involute	23
4.4.10 Radius of curvature of the involute, length of roll	23
4.4.11 Length of involute profile, L_{yt}	23
4.5 Angular pitch and pitches	23
4.5.1 Angular pitch	23
4.5.2 Pitches on the reference cylinder	23
4.5.3 Pitches on any cylinder	25
4.5.4 Axial pitch	25

4.5.5	Base pitch.....	25
4.6	Diameters of gear teeth.....	26
4.6.1	General.....	26
4.6.2	V-cylinder, V-circle diameter.....	26
4.6.3	Y-cylinder, Y-circle diameter.....	26
4.6.4	Tip alteration coefficient.....	26
4.6.5	Tip cylinder, tip circle, tip diameter.....	26
4.6.6	Profile control diameter, d_{cf}	26
4.6.7	Root cylinder, root circle, root diameter.....	27
4.7	Gear tooth depth.....	27
4.7.1	Tooth depth.....	27
4.7.2	Addendum, working addendum, dedendum, working dedendum.....	27
4.8	Tooth thickness, space width.....	27
4.8.1	General.....	27
4.8.2	Transverse tooth thickness.....	28
4.8.3	Transverse tooth thickness half angle.....	28
4.8.4	Space width.....	29
4.8.5	Transverse space width half angle.....	30
4.8.6	Normal tooth thickness.....	30
4.8.7	Normal space width.....	30
4.9	Radii of curvature of the tooth flanks in different planes.....	30
4.10	Tilt angle of contact line.....	32
5	Parallel axis cylindrical gear pairs.....	33
5.1	General.....	33
5.2	Concepts for a gear pair.....	33
5.2.1	Mating gear, mating flank.....	33
5.2.2	Working flank, non-working flank.....	33
5.2.3	External gear pair.....	33
5.2.4	Internal gear pair.....	34
5.3	Mating quantities.....	34
5.3.1	Gear ratio.....	34
5.3.2	Driving gear, driven gear, transmission ratio.....	34
5.3.3	Line of centres, centre distance.....	34
5.3.4	Working transverse pressure angle.....	35
5.3.5	Working pitch point, pitch cylinders, pitch circles, pitch diameter, pitch axis.....	35
5.3.6	Working helix angles.....	37
5.3.7	Working depth.....	37
5.3.8	Tip clearance.....	37
5.3.9	Calculation of tip alteration coefficient k (for parallel axis gear).....	38
5.4	Calculation of the sum of the profile shift coefficients.....	38
5.5	Tooth engagement.....	39
5.5.1	General.....	39
5.5.2	Active area of the tooth flanks, start of active profile and active tip diameters.....	39
5.5.3	Plane of action, zone of action, contact line.....	41
5.5.4	Line of action, path of contact, point of contact.....	41
5.5.5	Form over dimension.....	42
5.5.6	Designations and values relating to the line of action.....	42
5.5.7	Radii of curvature of the tooth flanks in a transverse plane.....	43
5.5.8	Tooth interference.....	43
5.5.9	Mesh geometry parameters.....	45
5.5.10	Contact line, sum of the contact line lengths.....	48
5.6	Backlash.....	50
5.6.1	General.....	50
5.6.2	Transverse backlash.....	50
5.6.3	Circumferential backlash.....	50
5.6.4	Normal backlash.....	50
5.6.5	Radial backlash.....	50

5.6.6	Angular Backlash.....	51
5.7	Velocities and sliding conditions at the tooth flanks.....	52
5.7.1	Angular velocity.....	52
5.7.2	Circumferential velocity.....	52
5.7.3	Normal velocity.....	52
5.7.4	Rolling velocity.....	53
5.7.5	Sliding velocity.....	53
5.7.6	Sliding factor.....	55
5.7.7	Specific sliding.....	55
6	Crossed axis cylindrical gear pairs.....	55
6.1	General.....	55
6.2	Concepts for a gear pair.....	56
6.3	Mating quantities.....	57
6.3.1	Gear ratio.....	57
6.3.2	Driving gear, driven gear, transmission ratio.....	57
6.3.3	Working pitch surfaces, working pitch point.....	57
6.3.4	Line of centres, working centre distance.....	57
6.3.5	Skew angle.....	58
6.3.6	Intermeshing racks at working pitch cylinders.....	58
6.3.7	Working transverse pressure angles.....	60
6.3.8	Working transverse tooth thicknesses.....	60
6.3.9	Basic rack profile to generate each part of the gear pair.....	61
6.3.10	Profile shift coefficients.....	61
6.3.11	Base space width half angle.....	61
6.3.12	Working conditions at minimum centre distance.....	62
6.3.13	Working conditions with backlash.....	62
6.3.14	Working depth.....	63
6.3.15	Tip clearance.....	63
6.3.16	Calculation of tip alteration coefficient k (for crossed axis gear).....	63
6.4	Tooth engagement.....	63
6.4.1	General.....	63
6.4.2	Line of action, path of contact, point of contact.....	63
6.4.3	Active area of the tooth flanks, start of active profile and active tip diameters.....	65
6.4.4	Form over dimension.....	66
6.4.5	Designations and values relating to the line of action.....	66
6.4.6	Tooth interference.....	67
6.4.7	Mesh geometry parameters.....	67
6.5	Backlash.....	68
6.5.1	General.....	68
6.5.2	Normal base backlash.....	68
6.5.3	Backlash angle, circumferential backlash.....	69
6.6	Sliding conditions at the tooth flanks.....	69
6.6.1	General.....	69
6.6.2	Angular velocities vectors.....	70
6.6.3	Velocity vectors of a point of contact along path of contact.....	72
6.6.4	Sliding velocity.....	72
7	Principal radii of curvature of the tooth flanks.....	72
7.1	General.....	72
7.2	Angle between principal radius of curvature at point of contact.....	74
7.3	Particularities for crossed axis helical involute gear:.....	74
7.4	Equivalent radii of curvature at point of contact.....	75
8	Tooth flank modifications.....	76
8.1	General.....	76
8.2	Tooth modifications which restrict the usable flank.....	76
8.2.1	Pre-finish flank undercut.....	76
8.2.2	Tip corner chamfering, tip corner rounding.....	77

8.3	Transverse profile modifications.....	78
8.3.1	General.....	78
8.3.2	Tip and root relief.....	78
8.3.3	Transverse profile slope modification, $C_{H\alpha}$	79
8.3.4	Profile crowning (barrelling), C_{α}	79
8.4	Flank line (helix) modifications.....	80
8.4.1	Flank line end relief.....	80
8.4.2	Helix angle modification, $C_{H\beta}$	81
8.4.3	Flank line (helix) crowning, C_{β}	81
8.5	Flank face modifications.....	82
8.5.1	Topographical modifications.....	82
8.5.2	Triangular end relief.....	83
8.5.3	Flank twist.....	83
8.6	Descriptions of modifications by functions.....	84
9	Geometrical limits.....	85
9.1	General.....	85
9.2	Counterpart rack tooth profile and rack tool profile.....	85
9.2.1	Counterpart rack tooth profile.....	85
9.2.2	Rack tool profile.....	88
9.3	Machining allowance.....	92
9.4	Limits of normal tooth thickness.....	92
9.5	Generating profile shift, generating profile shift coefficient.....	93
9.6	Generated root diameter.....	95
9.7	Usable area of the tooth flank, tip and root form diameter.....	95
9.8	Undercut.....	97
9.9	Overcut.....	97
9.10	Minimum tooth thickness at the tip circle of a gear.....	97
10	Start of involute for hob or rack type cutters.....	98
10.1	Formulae of involute and trochoid.....	98
10.2	Undercut conditions.....	99
10.3	Determination of start of involute.....	100
10.4	Determination of radius of curvature of trochoid.....	101
11	Start of involute calculation in case of pinion-type cutter.....	104
11.1	Geometry of pinion-type cutter.....	104
11.1.1	Pinion-type cutter without protuberance.....	104
11.1.2	Pinion-type cutter with protuberance.....	106
11.2	Undercut condition.....	108
11.3	Determination of start of involute when no undercut exists.....	108
11.4	Start of involute when there is undercut.....	108
11.4.1	Residual fillet undercut (transverse plane).....	108
11.4.2	Angle centre line of gear pair to centre point of tooth tip rounding: ω_0	108
11.4.3	Point Q (tangent point of cutter tip fillet and generated gear root fillet).....	109
11.4.4	Determination of start of involute.....	109
11.4.5	Determination of radius of curvature of trochoid.....	113
Annex A (informative) Calculation of form diameters for tooth tip corner radius and tooth root fillet radius in the transverse plane for involute cylindrical gears.....		115
Annex B (informative) Tip form radius when tooth tip corner radius is defined in normal plane.....		123
Annex C (informative) Supplementary information for crossed axes cylindrical gears.....		131
Annex D (informative) Geometry of surfaces in contact.....		138
Annex E (informative) Projection of transverse profile of the tooth to other planes.....		148
Annex F (informative) Interface for geometry of worms defined with ISO/TR 10828.....		156
Bibliography.....		159