



**International
Standard**

ISO 7745

**Hydraulic fluid power — Fire-
resistant fluids — Requirements
and guidelines for use**

*Transmissions hydrauliques — Fluides difficilement inflammables
— Exigences et recommandations pour leur utilisation*

**Third edition
2024-02**

ISO 7745:2024 - Preview only Copy via II.N.A.S. e-Shop



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword..... v

Introduction..... vi

1 Scope..... 1

2 Normative references..... 1

3 Terms and definitions..... 1

4 Hydraulic systems — Fire hazards..... 1

4.1 General..... 1

4.2 Fault conditions..... 1

4.3 Sources of ignition..... 2

5 Requirements for fire-resistant fluids..... 2

5.1 General fluid requirements..... 2

5.1.1 General..... 2

5.1.2 Viscosity..... 2

5.1.3 Lubrication..... 3

5.1.4 Compatibility..... 3

5.1.5 Chemical and thermal stability..... 3

5.1.6 Air release and foaming..... 3

5.1.7 Shear stability..... 3

5.2 Other fluid properties which may impact upon system design..... 3

5.2.1 General..... 3

5.2.2 Filterability..... 3

5.2.3 Density..... 3

5.2.4 Vapour pressure..... 3

6 Characteristics of fire-resistant hydraulic fluids and factors affecting their selection..... 4

6.1 General..... 4

6.1.1 Composition..... 4

6.1.2 Classification of fire-resistance fluids..... 4

6.1.3 Fluid mixing..... 4

6.2 Characteristics of fluids in different categories..... 5

6.2.1 HFAE — Oil in water emulsions (thickened and un-thickened)..... 5

6.2.2 HFAS — Chemical solutions in water (thickened and un-thickened)..... 7

6.2.3 HFB — Water-in-oil emulsions (invert emulsions)..... 9

6.2.4 HFC — Water polymer solutions..... 11

6.2.5 HFDR — Synthetic fluids containing no water and consisting of phosphate esters..... 12

6.2.6 HFDU — Synthetic fluids containing no water and of other composition..... 14

7 Hydraulic systems — General precautions..... 15

7.1 Assembly work..... 15

7.2 Pipework and hoses..... 15

7.3 Seals and gaskets..... 15

7.4 High fluid temperatures..... 16

8 Hydraulic circuit requirements for fire-resistant fluids..... 16

8.1 Reservoir..... 16

8.2 Pipework and hoses..... 16

8.3 Pump suction..... 16

8.4 Strainers and filters..... 16

8.5 Equipment performance..... 17

9 Changing the fluid in a hydraulic system..... 17

9.1 General..... 17

9.2 Draining and cleaning the circuit..... 17

9.3 Flushing and draining the circuit..... 18

9.4 Filling and re-commissioning the circuit..... 19

ISO 7745:2024(en)

9.5	Appropriate flushing fluids.....	19
10	Handling	22
10.1	Safety data sheets.....	22
10.2	Handling procedures.....	22
10.3	Storage.....	22
	Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*, Subcommittee SC 4, *Classifications and specifications*.

This third edition cancels and replaces the second edition (ISO 7745:2010), which has been technically revised.

The main changes are as follows:

- addition of [Clause 2](#) “Normative references” and renumbering of subsequent clauses accordingly;
- update of [Table 2](#);
- update of the dated references.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. The most widely used liquid for hydraulic power systems is mineral oil which has the advantages of excellent lubricity, availability in a wide range of viscosities and reasonable cost.

While not readily ignited in bulk, mineral oil is nevertheless flammable and the high pressures associated with hydraulic systems can lead to a release of fluid which is easily ignited. In circumstances where ignition is likely, such as in a steel mill, or where the released fluid must not propagate a fire, such as in a coal mine, an alternative fire-resistant fluid must be used. Fire-resistance and physical properties such as viscosity and lubricity vary widely among the several types of fluid available. It is therefore important to select a fire-resistant fluid which matches its proposed application and the perceived hazards in use.