

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

**Specification for radio disturbance and immunity measuring apparatus and methods –
Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus**

**Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-1: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Appareils de mesure**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

**Specification for radio disturbance and immunity measuring apparatus and methods –
Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus**

**Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-1: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Appareils de mesure**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XC**
CODE PRIX

ICS 33.100.10

ISBN 978-2-88910-010-1

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms and definitions.....	10
4 Quasi-peak measuring receivers for the frequency range 9 kHz to 1 000 MHz.....	13
4.1 General.....	13
4.2 Input impedance.....	13
4.3 Sine-wave voltage accuracy.....	13
4.4 Response to pulses.....	13
4.4.1 Amplitude relationship (absolute calibration).....	13
4.4.2 Variation with repetition frequency (relative calibration).....	14
4.5 Selectivity.....	18
4.5.1 Overall selectivity (passband).....	18
4.5.2 Intermediate frequency rejection ratio.....	19
4.5.3 Image frequency rejection ratio.....	19
4.5.4 Other spurious responses.....	20
4.6 Limitation of intermodulation effects.....	21
4.7 Limitation of receiver noise and internally generated spurious signals.....	22
4.7.1 Random noise.....	22
4.7.2 Continuous wave.....	22
4.8 Screening effectiveness.....	22
4.8.1 General.....	22
4.8.2 Limitation of radio-frequency emissions from the measuring receiver.....	23
4.9 Facilities for connection to a discontinuous disturbance analyzer.....	23
5 Measuring receivers with peak detector for the frequency range 9 kHz to 18 GHz.....	23
5.1 General.....	23
5.2 Input impedance.....	23
5.3 Fundamental characteristics.....	24
5.3.1 Bandwidth.....	24
5.3.2 Charge and discharge time constants ratio.....	24
5.3.3 Overload factor.....	25
5.4 Sine-wave voltage accuracy.....	25
5.5 Response to pulses.....	25
5.6 Selectivity.....	25
5.7 Intermodulation effects, receiver noise, and screening.....	26
6 Measuring receivers with average detector for the frequency range 9 kHz to 18 GHz.....	27
6.1 General.....	27
6.2 Input impedance.....	27
6.3 Fundamental characteristics.....	27
6.3.1 Bandwidth.....	27
6.3.2 Overload factor.....	27
6.4 Sine-wave voltage accuracy.....	28
6.5 Response to pulses.....	28
6.5.1 General.....	28

6.5.2	Amplitude relationship	28
6.5.3	Variation with repetition frequency.....	29
6.5.4	Response to intermittent, unsteady and drifting narrowband disturbances.....	29
6.6	Selectivity	31
6.7	Intermodulation effects, receiver noise, and screening	31
7	Measuring receivers with rms-average detector for the frequency range 9 kHz to 18 GHz.....	31
7.1	General.....	31
7.2	Input impedance.....	31
7.3	Fundamental characteristics.....	32
7.3.1	Bandwidth	32
7.3.2	Overload factor.....	32
7.4	Sine-wave voltage accuracy	33
7.5	Response to pulses.....	33
7.5.1	Construction details.....	33
7.5.2	Amplitude relationship	33
7.5.3	Variation with repetition frequency.....	34
7.5.4	Response to intermittent, unsteady and drifting narrowband disturbances.....	34
7.6	Selectivity	35
7.7	Intermodulation effects, receiver noise, and screening.....	35
8	Measuring receivers for the frequency range 1 GHz to 18 GHz with amplitude probability distribution (APD) measuring function.....	35
9	Disturbance analyzers.....	36
9.1	General.....	36
9.2	Fundamental characteristics.....	37
9.3	Test method for the validation of the performance check for the click analyzer.....	43
9.3.1	Basic requirements.....	43
9.3.2	Additional requirements.....	44
Annex A (normative)	Determination of response to repeated pulses of quasi-peak and rms-average measuring receivers (See 3.6, 4.4.2, 7.3.2 and 7.5.1)	45
Annex B (normative)	Determination of pulse generator spectrum (See 4.4, 5.5, 6.5, 7.5).....	51
Annex C (normative)	Accurate measurements of the output of nanosecond pulse generators (See 4.4, 5.5, 6.5, 7.5)	53
Annex D (normative)	Influence of the quasi-peak measuring receiver characteristics on its pulse response (See 4.4.2).....	55
Annex E (normative)	Response of average and peak measuring receivers (See 6.3.1)	56
Annex F (normative)	Performance check of the exceptions from the definitions of a click according to 4.2.3 of CISPR 14-1	65
Annex G (informative)	Rationale for the specifications of the APD measuring function.....	72
Annex H (informative)	Characteristics of a quasi-peak measuring receiver.....	75
Annex I (informative)	Example of EMI receiver and swept spectrum analyzer architecture.....	76
Bibliography.....		78
Figure 1 – Pulse response curves		17

Figure 2 – Limits of overall selectivity	20
Figure 3 – Arrangement for testing intermodulation effects	21
Figure 4 – Limits for the overall selectivity – pass band (Band E).....	26
Figure 5 – Block diagram of an average detector.	30
Figure 6 – Screenshot showing response of the meter-simulating network to an intermittent narrowband signal.....	30
Figure 7 – Example of a disturbance analyzer.....	38
Figure 8 – A graphical presentation of test signals used in the test of the analyzer for the performance check against the definition of a click according to Table 14	39
Figure E.1 – Correction factor for estimating the ratio B_{imp}/B_6 for other tuned circuits	57
Figure E.2 – Pulse rectification coefficient P	59
Figure E.3 – Example (spectrum screenshot) of a pulse-modulated signal with a pulse width of 200 ns	60
Figure E.4 – Pulse-modulated RF signal applied to a measuring receiver	61
Figure E.5 – Filtering with a B_{imp} much smaller than the prf.....	61
Figure E.6 – Filtering with a B_{imp} much wider than the prf.....	62
Figure E.7 – Calculation of the impulse bandwidth	62
Figure E.8 – Example of a normalized linear selectivity function	64
Figure F.1 – A graphical presentation of the test signals used for the performance check of the analyzer with the additional requirements according to Table F.1.....	71
Figure G.1 – Block diagram of APD measurement circuit without A/D converter.....	73
Figure G.2 – Block diagram of APD measurement circuit with A/D converter.....	73
Figure G.3 – Example of display of APD measurement	74
Figure I.1 – Example block diagram of EMI receiver consisting of swept spectrum analyzer with added preselector, preamplifier and quasi-peak/average detector	76
Table 1 – Test pulse characteristics for quasi-peak measuring receivers (see 4.4.1)	13
Table 2 – Pulse response of quasi-peak measuring receivers	18
Table 3 – Combined selectivity of CISPR measuring receiver and high-pass filter.....	19
Table 4 – Bandwidth characteristics for intermodulation test of quasi-peak measuring receivers (see 4.6).....	22
Table 5 – VSWR requirements for receiver input impedance.....	24
Table 6 – Bandwidth requirements for measuring receivers with peak detector	24
Table 7 – Relative pulse response of peak and quasi-peak measuring receivers for the same bandwidth (frequency range 9 kHz to 1 000 MHz).....	25
Table 8 – Bandwidth requirements for measuring receivers with average detector	27
Table 9 – Relative pulse response of average and quasi-peak measuring receivers for the same bandwidth (frequency range 9 kHz to 1 GHz).....	28
Table 10 – Maximum reading of average measuring receivers for a pulse-modulated sine-wave input in comparison with the response to a continuous sine wave having the same amplitude	30
Table 11 – VSWR requirements of input impedance.....	32
Table 12 – Bandwidth requirements for measuring receivers with rms-average detector	32
Table 13 – Minimum pulse repetition rate without overload	32
Table 14 – Relative pulse response of rms-average and quasi-peak measuring receivers.....	33

Table 15 – Pulse response of rms-average measuring receiver	34
Table 16 – Maximum reading of rms-average measuring receivers for a pulse-modulated sine-wave input in comparison with the response to a continuous sine wave having the same amplitude	35
Table 17 – Disturbance analyzer performance test – Test signals used for the check against the definition of a click.....	40
Table B.1 – Pulse generator characteristics	51
Table E.1 – B_{imp} and A_{imp} values for a peak measuring receiver	58
Table E.2 – Carrier level for pulse-modulated signal of 1,4 nVs	60
Table F.1 – Disturbance analyzer test signals ^a	66
Table H.1 – Characteristics of quasi-peak measuring receivers	75

Withdrawn