CISPR 16-1-1

Edition 3.0 2014-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

AMENDMENT 2
AMENDEMENT 2

Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Partie 1-1: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Appareils de mesure

CISPR 16-1-1:2010-01/AMD2:2014-06(en-fr)

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org
Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

CISPR 16-1-1

Edition 3.0 2014-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

AMENDMENT 2
AMENDEMENT 2

Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Partie 1-1: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Appareils de mesure

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE
CODE PRIX

N

ICS 33.100.10

ISBN 978-2-8322-1655-2

FOREWORD

This amendment has been prepared by subcommittee CIS/A: Radio-interference measurements and statistical methods, of IEC technical committee CISPR: International special committee on radio interference.

The text of this amendment is based on the following documents:

FDIS	Report on voting
CIS/A/1070/FDIS	CIS/A/1075/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

4.4.1 Amplitude relationship (absolute calibration)

Add, after the existing first paragraph, the following new text:

When external preamplifiers are used, refer to Annex J for applicable requirements.

7.5.2 Amplitude relationship

Add, after the existing paragraph and Note, the following new text:

When external preamplifiers are used, refer to Annex J for applicable requirements.

Add, after the existing Annex I, the following new annex:

Annex J
(normative)

Requirements when using an external preamplifier with a measuring receiver

J.1 General

Using an external preamplifier at the input of a measuring receiver shall be considered carefully as, while it improves system sensitivity, it may invalidate the system's compliance with the overload requirements of this standard. Further, an external preamplifier may invalidate the usability of a spectrum analyzer without preselection for the measurement of impulsive signals with pulse repetition frequencies down to 20 Hz using the quasi-peak detector as specified in 4.4.2.

Therefore the operator of a measuring system that includes an external preamplifier shall determine the limitations of the system and shall apply linearity checks for the test system. Automated measurement results with external preamplifiers need to be verified using a final manual linearity check. The information given in this annex provides guidance for the user of emission measurement systems.

J.2 Considerations for optimum emission measurement system design

Internally, measuring receivers are designed to achieve optimum sensitivity while avoiding overload. Built-in preselection in the measuring receiver avoids overload by impulsive signals. In spite of preselection, measuring receivers usually have no linearity reserve for quasi-peak measurements of a single pulse above the specified indication range. Missing preselection in measuring receivers causes problems with quasi-peak detection of impulsive signals with low PRF.

The use of an external broadband preamplifier shall be considered only after all other possible measures for improving the system sensitivity have been exhausted, e.g. using measuring receivers with built-in preamplifiers, using antennas of sufficient gain, or using low loss connecting cables. An external preamplifier need only be added when the disturbance limit and all of the emissions expected and emissions to be measured are very close to the system noise level, e.g. for compliance with Class 5 radiated disturbance limits of CISPR 25 [17]. If high emission signals or high ambients are expected, external preamplifiers are not recommended.

From experience, external preamplifiers are not needed for radiated disturbance measurements to Class B limits of CISPR 11, CISPR 22 [16] and CISPR 32 [18], either at 3 m or at 10 m measurement distance, when measuring receivers with built-in preamplifiers including preselection and low-loss antenna cables are used. The same situation applies for radiated disturbance measurements to CISPR 14-1, CISPR 15 [15], and the generic emission standards, as well as for disturbance power measurements.

External preamplifiers are not recommended for conducted disturbance measurements below 30 MHz; their use may cause harmonics in the presence of high-level disturbance at frequencies below 150 kHz, where many emission standards do not specify disturbance limits.

If an external preamplifier is added for improved sensitivity, the following needs to be considered:

a) preamplifiers have a wide bandwidth, i.e. they are susceptible to overload by impulsive signals and high level narrowband signals;

b) preamplifiers may produce intermodulation products and harmonics; this is especially important when measurements are made on an OATS and/or in the presence of radio transmission equipment;

c) preamplifiers increase the signal level at the receiver input and thus may overload the receiver input stages, a condition which cannot be avoided entirely by the receiver's built-in preselection;

d) the gain in sensitivity will be less than the gain in signal level, thus limiting the dynamic range of the preamplifier/receiver combination;

NOTE 1 The gain in sensitivity is understood as the difference between the noise figure without preamplifier and the system noise figure with preamplifier.

e) for maximum sensitivity in the frequency range above 1 GHz, the preamplifier is mounted/connected directly to the measurement antenna;

f) use of an external preamplifier requires that an accurate gain versus frequency characterization be accounted for in the measurement result;

g) the uncertainty of the gain as a function of temperature and aging, as well as the additional mismatch uncertainty between the preamplifier output port and the receiver input port, shall be included in the uncertainty budget for the measurement; the input impedance shall, as far as possible, comply with the requirements for the measuring receiver and shall be included in the uncertainty budget;

h) for CISPR Band E, a system consisting of an external preamplifier and a measuring receiver shall be designed such that it cannot be overloaded by signals of lower frequency bands, and/or by any signal whose out-of-band or spurious signals are to be measured; e.g. the ISM signal of a microwave oven shall not drive the system into overload.

The gain in sensitivity is determined using the following quantities and equations:

$$F = \frac{P_{\text{ie}}}{kT_0B} \text{ and,} \tag{J.1}$$

$$\text{for an amplifier, } F = \frac{P_{\text{o}}}{gkT_0B} \tag{J.2}$$

where

F is the noise factor, with 10 lg$F$ = noise figure (often denoted by the symbol NF);

P_{ie} is the equivalent noise input power;

P_{o} is the noise output power;

g is calculated from the gain, G = 10 lg$g$, respectively $g = 10^{G/10}$

k is Boltzmann's constant = 1,38 × 10^{-23} Ws/K and kT_0 = 4 × 10^{-21} W/Hz

T_0 is the absolute reference room temperature (293 K);

B is the noise bandwidth (e.g. of the measuring receiver).