

INTERNATIONAL STANDARD

Cable networks for television signals, sound signals and interactive services –
Part 5: Headend equipment

Withhold



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



IEC 60728-5

Edition 2.0 2007-08

INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services –
Part 5: Headend equipment**

Withhold@wv

IEC 60728-5 Ed. 2.0 - Preview only Copy via ILNAS e-Shop

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XC**

ICS 33.060.40

ISBN 2-8318-9263-5

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references.....	13
3 Terms, definitions, symbols and abbreviations.....	14
3.1 Terms and definitions.....	14
3.2 Symbols.....	19
3.3 Abbreviations.....	19
4 Methods of measurement.....	21
4.1 Methods of measurement for digitally modulated signals.....	21
4.1.1 Introduction.....	21
4.1.2 Basic assumptions and measurement interfaces.....	21
4.1.3 Signal level for digitally modulated signals.....	21
4.2 Single-channel intermodulation specification for channel amplifier and frequency converter.....	23
4.3 Three-carrier intermodulation measurement.....	24
4.4 Two carrier intermodulation measurements for second- and third-order products.....	25
4.4.1 Introduction.....	25
4.4.2 Intermodulation products with test signals at frequencies f_a and f_b	26
4.4.3 Signal levels.....	26
4.5 Carrier-to-spurious signal ratio at the output.....	26
4.5.1 Carrier-to-spurious signal ratio at the output of equipment for AM-TV systems.....	26
4.5.2 Carrier-to-spurious signal ratio at the output of equipment for FM-TV systems.....	27
4.5.3 Shoulder attenuation.....	28
4.6 Signal-to-noise measurement.....	29
4.6.1 Television carrier-to-noise ratio (analogue modulated signals).....	29
4.6.2 RF signal-to-noise ratio ($S_{D,RF}/N$) for digitally modulated signals.....	32
4.7 Differential gain and phase for PAL/SECAM signals.....	34
4.7.1 Introduction.....	34
4.7.2 Differential gain (for PAL/SECAM only).....	34
4.7.3 Differential phase.....	35
4.8 Group delay measurements.....	38
4.8.1 Group delay variation of analogue TV signals.....	38
4.8.2 Procedure for the measurement of group delay variation on DVB channel converters.....	39
4.9 Phase noise of an RF carrier.....	42
4.9.1 Introduction.....	42
4.9.2 Equipment required.....	42
4.9.3 Connection of the equipment.....	42
4.9.4 Measurement procedure.....	43
4.9.5 Presentation of the results.....	43
4.10 Hum modulation of carrier.....	44
4.10.1 Definition.....	44

4.10.2	Description of the method of measurement	45
4.10.3	Measuring Procedure	46
4.10.4	Calculating the hum modulation ratio	47
4.11	2T-pulse response, <i>K</i> -factor	48
4.12	Chrominance-luminance delay inequalities (20T-pulse method).....	49
4.13	Luminance non-linearity	50
4.14	Intermodulation distortion (FM stereo radio)	51
4.14.1	Introduction	51
4.14.2	Equipment required	52
4.14.3	Connection of equipment.....	52
4.14.4	Measurement.....	52
4.15	Decoding margin (Teletext)	53
4.15.1	Definition.....	53
4.15.2	Method of measurement and measuring set-up (Figure 29)	53
4.15.3	Applicability of measuring set-up	53
5	Performance requirements and recommendations	54
5.1	Safety	54
5.2	Electromagnetic compatibility	54
5.3	Environmental	54
5.4	Marking	55
5.4.1	Marking of equipment.....	55
5.4.2	Marking of ports	55
6	Equipment characteristics required to be met	55
6.1	General.....	55
6.2	Power supply voltage	56
6.3	RF signal requirements	56
6.3.1	Impedance (input).....	56
6.3.2	Impedance (output).....	56
6.3.3	Return loss (input, output) of equipment	56
6.3.4	Return loss (output) of headend	56
6.3.5	Typical back off for digital against analogue signals	57
6.3.6	Immunity against other signals in the FM radio and TV range	57
6.3.7	Carrier-to-spurious-signals ratio at output in the frequency range of 40 MHz to 862 MHz	57
6.3.8	Image rejection for AM TV and FM radio.....	57
6.3.9	Carrier to local oscillator signal ratio at the output for AM TV and FM radio.....	58
6.3.10	Frequency stability	58
6.3.11	Phase noise of digital modulated signals at the output of the headend	59
6.3.12	In-channel group delay variation for digital modulated signals	60
6.3.13	In-channel peak-to-peak amplitude response variation for digitally modulated signals.....	60
6.3.14	Stability of sound intercarrier	60
6.3.15	Stability of residual carrier amplitude.....	61
6.3.16	Frequency stability – SAT IF/IF converter	61
6.3.17	Typical modulation error ratio (MER) for a QAM signal	61
6.3.18	Minimum <i>C/N</i> values at the output of the headend	61
6.4	Composite video signal requirements	62
6.4.1	Impedance.....	62

6.4.2	Return loss	62
6.4.3	Signal voltage	62
6.4.4	Polarity	62
6.4.5	Offset voltage	62
6.5	Audio signal requirements	62
6.5.1	Input impedance	62
6.5.2	Output impedance	62
6.5.3	Signal level	63
6.6	Requirements for decoding margin (teletext)	63
6.7	IF signal requirements (AM-TV)	63
6.7.1	Impedance	63
6.7.2	Return loss	63
6.8	Antennas for terrestrial reception	63
6.8.1	Impedance	63
6.8.2	Return loss	63
6.9	Antenna amplifier	63
7	Equipment characteristics required to be published	64
7.1	General	64
7.2	Environmental conditions	64
7.3	Maximum permissible output level	64
7.4	Operating range for output level	65
7.5	TV standard	65
7.6	Clamp	65
7.7	Noise figure	65
7.7.1	Equipment without AGC	65
7.7.2	Equipment with AGC	66
7.8	Data control signals, description of interface	66
7.9	Output level stability for TV modulators, TV converters and pilot generators	66
7.10	Pilot signal	66
7.11	Differential gain and phase	67
7.11.1	Differential gain	67
7.11.2	Differential phase	67
7.12	Group delay variation for analogue TV signals	67
7.13	Luminance non-linearity	68
7.14	2T-pulse	68
7.15	20T-pulse	68
7.16	Hum modulation	68
7.17	Television carrier-to-noise ratio	68
7.18	Audio in TV	68
7.19	Processing units for FM radio	69
7.19.1	Audio input	69
7.19.2	Stereo crosstalk	69
7.19.3	Total harmonic distortion	69
7.19.4	Intermodulation distortion	69
7.19.5	Deviation, pre-emphasis	69
7.20	Antennas for terrestrial reception	69
7.20.1	Antenna gain	69
7.20.2	Sidelobe suppression	69
7.20.3	Return loss of antennas	69

7.21 Control signals for outdoor units.....	70
Annex A (normative) Definition of the specified test frequency range for return loss and noise figure.....	71
Annex B (informative) Audio connector for European system.....	73
Annex C (informative) Selectivity diagram for adjacent channel transmission.....	74
Annex D (informative) Differences in some countries.....	79
Annex E (normative) Correction factors for noise.....	80
Annex F (informative) Digital signal level and bandwidth.....	82
Annex G (informative) Minimum frequency distance of converted satellite signals in the IF range.....	85
Annex H (informative) Measurement errors which occur due to mismatched equipment.....	86
Annex I (normative) Correction factor for spectrum analyser.....	87
Bibliography.....	88
Figure 1 – Example of headend.....	12
Figure 2 – Frequencies and levels of test carriers.....	24
Figure 3 – Test carrier and interfering products in the pass band.....	25
Figure 4 – Example showing products formed when $2f_a > f_b$	26
Figure 5 – Carrier-to-spurious signal ratio in the output.....	27
Figure 6 – Carrier-to spurious signal ratio at the output.....	28
Figure 7 – Shoulder attenuation.....	28
Figure 8 – Arrangement of test equipment for carrier-to-noise ratio measurement.....	29
Figure 9 – Arrangement of test equipment for measurement of differential gain and phase.....	37
Figure 10 – Signal D2 waveform.....	37
Figure 11 – Example of modified staircase.....	37
Figure 12 – Measuring set-up for determining the group delay variation.....	38
Figure 13 – RF signal (time domain) amplitude-modulated with a split-frequency signal.....	39
Figure 14 – Spectral presentation of the group delay measurement.....	40
Figure 15 – Description of the measuring set-up.....	41
Figure 16 – Choices of measuring aperture (value of the split frequency) for various measurement tests.....	41
Figure 17 – Test set-up for phase noise measurement.....	43
Figure 18 – Mask for phase noise measurements.....	44
Figure 19 – Carrier/hum ratio.....	45
Figure 20 – Test set-up for equipment with built-in power supply.....	46
Figure 21 – Test set-up for equipment with external power supply.....	46
Figure 22 – Oscilloscope display.....	47
Figure 23 – K-factor mask for Quality Grade 2.....	48
Figure 24 – Generation of 20T-pulse.....	49
Figure 25 – Example of amplitude and delay error using 20T-pulse.....	50
Figure 26 – Staircase signal for measurement of luminance non-linearity before and after differentiation.....	51