

INTERNATIONAL STANDARD

IEC 60335-2-67

2002

AMENDMENT 1
2005-09

Amendment 1

**Household and similar electrical appliances –
Safety –**

**Part 2-67:
Particular requirements for floor treatment
and floor cleaning machines, for industrial
and commercial use**

© IEC 2005 Droits de reproduction réservés — Copyright - all rights reserved

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

K

For price, see current catalogue

FOREWORD

This amendment has been prepared by subcommittee 61J: Electrical motor-operated cleaning appliances for industrial use, of IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61J/196/FDIS	61J/209/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

FOREWORD

Add the following item to the list of differences existing in some countries:

- Clause 7.12 No requirements for sound and vibration markings exist (USA)

INTRODUCTION

Replace the second sentence of the second paragraph by the following:

It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

2 Normative references

Add the following reference:

ISO 6344-2, *Coated abrasives – Grain size analysis – Part 2: Determination of grain size distribution of macrogrits P12 to P220*

3 Definitions

3.1.9 Add, after the 1st paragraph, the following paragraph:

Power outlets for accessories are loaded with a resistive load in accordance with the marking.

Add the following new definitions:

3.101

water-suction cleaning appliance

appliance for aspirating an aqueous solution that may contain foaming detergent

3.102

motorized cleaning head


accessory containing a motor that is supplied from the appliance and which is attached to the end of a hand-held hose or tube

NOTE The main cleaning head permanently attached is not regarded as a motorized cleaning head.

7 Marking and instructions

Add the following subclause:

7.6 Addition:



[symbol IEC 60417-5935 (DB:2002-10)] motorized cleaning head for water-suction cleaning

7.12 Replace the existing text by the following:

Addition:

The front cover of the instruction manual shall include the substance of the following:

CAUTION: Read the instruction manual before using the appliance.

This wording may be replaced by symbols 0434 and 1641 of ISO 7000. If these symbols are used, their meaning is to be explained in the instructions for use.

The instruction manual shall include the substance of the following warnings, as applicable.

- **CAUTION:** This appliance is not suitable for picking up hazardous dust.
- **CAUTION:** This appliance is for dry use only and is not to be used or stored outdoors in wet conditions.
- **WARNING:** Only use the brushes provided with the appliance or those specified in the instruction manual. The use of other brushes may impair safety.

The instruction manual shall give details regarding the following, as applicable:

- the precautions to be taken when using the appliance under specific conditions such as handling flammable liquids or dust, and dust hazardous to health;

- a statement that the appliance is to be disconnected from its power source during cleaning or maintenance and when replacing parts or converting the appliance to another function:
 - for mains operated appliances, the plug is to be removed from the socket-outlet;
 - for battery operated appliances, the key of the supply switch is to be removed or an equivalent disconnection is to be made;
- a statement that doors and covers are to be positioned as indicated in the instruction manual before using the appliance;
- the precautions to be taken when changing brushes or other attachments which require the appliance to be energized;
- the intended use of brushes which are specified for the appliance;
- a warning that large diameter brushes provided specifically for dry buffing are not intended for general polishing.

The instruction manual shall state

- the A-weighted sound pressure level L_{PA} in dB(A) emitted by the appliance. If the A-weighted sound pressure level exceeds 85 dB(A), it shall also state the sound power level L_{WA} in dB(A) and that appropriate ear protection has to be used.

NOTE 101 The sound level is measured in accordance with IEC 60704-1.
- the weighted r.m.s. acceleration value to which the operators' arms are subjected in m/s^2 , separately for each arm (if applicable).

NOTE 102 The weighted r.m.s. acceleration value is measured in accordance with ISO 5349 for arm vibrations, the appliance being supplied at **rated voltage** or at the maximum **rated voltage** for machine with a range of voltages

The instruction manual shall include the substance of the following:

This appliance is suitable for commercial use, for example in hotels, schools, hospitals, factories, shops, offices and rental businesses.

The instruction manual for mains operated appliances shall include the substance of the following:

- do not allow the rotating brushes to come into contact with the supply cord;
- regularly examine the supply cord for damage, such as cracking or ageing. If damage is found, replace the cord before further use;
- only replace the supply cord with the type specified in the instruction manual;
- only use the socket outlet on the appliance for purposes specified in the instruction manual.

The instructions for appliances having a current-carrying hose operating at other than **safety extra-low voltage** shall include the substance of the following:

CAUTION: This hose contains electrical connections:

- do not use to collect water;
- do not immerse in water for cleaning;
- the hose should be checked regularly and must not be used if damaged.

If the symbol IEC 60417-5935 is used, its meaning shall be explained.

Add the following subclause:

7.14 Addition:

The height of symbol IEC 60417-5935 shall be at least 15 mm.

Compliance is checked by measurement.

7.101 Motorized cleaning heads shall be marked with

- **rated voltage** or **rated voltage range** in volts;
- **rated power input** in watts;
- name, trade mark or identification mark of the manufacturer or responsible vendor;
- model or type reference.

Motorized cleaning heads for water-suction cleaning appliances, except those of **class III construction** having a **working voltage** up to 24 V shall be marked with symbol IEC 60417-5935.

NOTE This symbol is an information sign and, except for the colours, the rules of ISO 3864-1 apply.

Compliance is checked by inspection.

7.102 Appliance outlets for accessories shall be marked with the maximum load in watts.

NOTE This marking may be on the appliance close to the appliance outlet.

Compliance is checked by inspection.

10 Power input and current

Replace the existing text of this clause by the following:

This clause of Part 1 is applicable except as follows.

10.1 Addition:

The power input of **motorized cleaning heads** is measured separately.

15 Moisture resistance

15.2 *Replace the text after Note 101 by the following new text:*

Motorized cleaning heads of water-suction cleaning appliances are placed in a container, the base of which is level with the surface supporting the appliance. The container is filled with a detergent solution to a level of 5 mm above its base, this level being maintained throughout the test. The solution consists of 20 g of NaCl and 1 ml of a solution of 28 % by mass of dodecyl sodium sulphate in each 8 l of water.

The appliance is operated until its liquid container is completely full and for a further 5 min.

NOTE 102 The solution is to be stored in a cool atmosphere and used within seven days of its preparation.

NOTE 103 The chemical designation of dodecyl sodium sulphate is C₁₂H₂₅NaSO₄.

After each of these tests, the appliance shall withstand the electric strength test of 16.3.

*Inspection shall show that there is no trace of liquid on insulation that could result in a reduction of **clearances** or **creepage distances** below the values specified in Clause 29.*