

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 1-4: Assessment of conductor heating in bundled cables due to the
deployment of remote powering**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.



IEC 61156-1-4

Edition 1.0 2018-10

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 1-4: Assessment of conductor heating in bundled cables due to the
deployment of remote powering**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-5968-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and symbols.....	6
3.1 Terms and definitions.....	6
3.2 Symbols.....	7
4 Testing procedure.....	8
4.1 General.....	8
4.2 Bundling of cables	8
4.3 Testing current and measurement accuracy	10
4.4 Test conditions	10
4.5 Environmental conditions	10
4.6 Assessment of the concatenated loop resistance of all pairs	13
4.7 Data submission	13
4.8 Expression of results	14
Annex A (informative) Modelling of cable bundle heating [3]	15
A.1 Cable heating model	15
A.2 Evaluation of recorded data	18
Bibliography.....	19
Figure 1 – Bundle of cables under test.....	9
Figure 2 – Thermocouple placement	9
Figure 3 – Free air	11
Figure 4 – Open conduit (Tray)	11
Figure 5 – Conduit	12
Figure 6 – Sealed conduit.....	13
Table 1 – Supporting information	14
Table 2 – Test data format.....	14

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 1-4: Assessment of conductor heating in bundled cables
due to the deployment of remote powering**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-1-4 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

This first edition cancels and replaces IEC PAS 61156-1-4, published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Several test arrangements are considered;
- b) The mathematical approach was revised

The text of this document is based on the following documents:

CDV	Report on voting
46C/1089/CDV	46C/1098A/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61156 series, published under the general title: *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The use of remote powering causes a temperature rise in cables installed in bundles.

This document specifies a method to assess the temperature increase in cable bundles by measuring the temperature change using thermocouples placed on the sheath of the cable at the centre of the bundle.

Several test arrangements are considered as well as current values.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 1-4: Assessment of conductor heating in bundled cables due to the deployment of remote powering

1 Scope

This document specifies a method to assess the thermal behaviour of cables arranged in bundles, for digital communications. A method is described to determine the temperature increase in cable bundles for certain remote powering currents as a basis to analyse the expected performance under several test arrangements described in standards dealing with the installation of cabling systems (e.g. [1]¹, [2]).

It is only intended to provide guidance to assess the thermal behaviour of cables for digital communications in reference environmental conditions and arrangements. It is therefore not intended to become a type of test method.

The following test arrangements are considered:

- c) free air;
- d) cable tray;
- e) conduits;
- f) conduit with sealed ends.

Even though this document covers four-pair data grade cables, the same principles can be applied to other cable types.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61156-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

¹ Numbers in square brackets refer to the Bibliography.

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1**current carrying capacity
ampacity**

maximum amount of current that a conductor can carry while remaining within the maximum allowable temperature for the cable insulation

3.1.2**PoE****power over Ethernet**

technology describing a system to pass electrical power safely, along with data, on Ethernet cabling

3.1.3**PoEP****power over Ethernet Plus**

evolution of PoE to allow higher power

3.1.4**remote powering**

supply of power to application-specific equipment via balanced cabling

3.1.5**temperature rise**

difference in temperature (°C) between the initial temperature of the conductor surface without power and the final temperature at the surface of the powered conductor at steady state

3.2 Symbols

For the purposes of this document, the following symbols are used.

d	cable diameter (m)
i_c	current per conductor (A)
M	number of layers surrounding the centre cable
N	number of cables carrying remote powering current
n_c	number of conductors per cable carrying remote powering current i_c
R_{amb}	average DC resistance per unit length (Ω/m) of conductors carrying remote powering current at ambient temperature
$R(T)$	average DC resistance per unit length (Ω/m) of conductors carrying remote powering current at temperature T
T_{amb}	ambient temperature (°C)
T_c	temperature at the centre of the bundle (°C)
T_s	temperature of the outer surface of the bundle (°C)
ΔT	total temperature rise in reference to the ambient temperature
α	temperature coefficient of resistance
ρ_{th}	specific constant relating to cable construction
ρ_u	specific constant relating to environmental conditions
k_{th}	global constant relating to cable construction
k_u	global constant relating to environmental conditions