

INTERNATIONAL STANDARD

IEC
60384-3

QC 300800

Third edition
2006-10

Fixed capacitors for use in electronic equipment –

Part 3:

**Sectional specification: Surface mount fixed
tantalum electrolytic capacitors with manganese
dioxide solid electrolyte**



Reference number
IEC 60384-3:2006(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60384-3

QC 300800

Third edition
2006-10

Fixed capacitors for use in electronic equipment –

Part 3:

Sectional specification: Surface mount fixed tantalum electrolytic capacitors with manganese dioxide solid electrolyte

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

U

For price, see current catalogue

CONTENTS

FOREWORD.....	4
1 General.....	6
1.1 Scope.....	6
1.2 Object.....	6
1.3 Normative references.....	6
1.4 Information to be given in a detail specification.....	6
1.5 Terms and definitions.....	7
1.6 Marking.....	8
2 Preferred ratings and characteristics.....	9
2.1 Preferred characteristics.....	9
2.2 Preferred values of ratings.....	10
3 Quality assessment procedures.....	11
3.1 Primary stage of manufacture.....	11
3.2 Structurally similar components.....	11
3.3 Certified records of released lots.....	11
3.4 Qualification approval.....	11
3.5 Quality conformance inspection.....	12
4 Test and measurement procedures.....	13
4.1 Preliminary drying.....	13
4.2 Measuring conditions.....	13
4.3 Mounting.....	13
4.4 Visual examination and check of dimensions.....	14
4.5 Electrical tests.....	14
4.6 Resistance to soldering heat.....	15
4.7 Solderability.....	16
4.8 Shear test.....	16
4.9 Substrate bending test.....	17
4.10 Rapid change of temperature.....	17
4.11 Climatic sequence (applicable to Style 1 capacitors only).....	17
4.12 Damp heat, steady state (applicable to Style 1 capacitors only).....	18
4.13 Characteristics at high and low temperature.....	18
4.14 Surge.....	18
4.15 Endurance.....	19
4.16 Reverse voltage (if required by the detail specification).....	19
4.17 Component solvent resistance (if required by the detail specification).....	20
4.18 Solvent resistance of the marking (if required by the detail specification).....	20
4.19 High surge current (if required by the detail specification).....	20
Annex A (normative) Test plans for assessment level EZ.....	21
Annex B (normative) Test schedule for assessment level EZ.....	24

Table 1 – Category voltages 10

Table 2 – Test temperatures 19

Table A.1 – Test plan for qualification approval – Assessment level EZ 21

Table A.2 – Test plan for quality conformance inspection – Lot-by-lot tests –
Assessment level EZ 22

Table A.3 – Test plan for quality conformance inspection – Periodic tests –
Assessment level EZ 23

Table B.1 – Test schedule for qualification approval – Assessment level EZ 24

Withdrawn

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 3: Sectional specification: Surface mount fixed tantalum electrolytic capacitors with manganese dioxide solid electrolyte

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-3 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This third edition cancels and replaces the second edition published in 1989 and constitutes a minor revision related to tables, figures and references.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1771/FDIS	40/1789/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The QC numbers that appear on the front cover of this publication are the specification numbers in the IEC Quality Assessment System for Electronic Components (IECQ).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60384 series, under the (new) general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of January 2007 have been included in this copy.

Withdrawn

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 3: Sectional specification: Surface mount fixed tantalum electrolytic capacitors with manganese dioxide solid electrolyte

1 General

1.1 Scope

This specification applies to surface mount tantalum solid electrolyte capacitors. These capacitors are primarily intended to be mounted directly onto substrates for hybrid circuits or onto printed boards.

The following two styles are considered:

- Style 1: protected capacitors;
- Style 2: unprotected capacitors.

1.2 Object

The object of this standard is to prescribe preferred ratings and characteristics and to select from IEC 60384-1:1999, the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor.

1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60063, *Preferred number series for resistors and capacitors*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60384-1, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60410, *Sampling plans and procedures for inspection by attributes*

ISO 3, *Preferred numbers – Series of preferred numbers*

1.4 Information to be given in a detail specification

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example, by an asterisk.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.1 Outline drawing and dimensions

The detail specification shall give an illustration of the capacitor as an aid to easy recognition and for comparison of the capacitor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given. All dimensions are to be stated in mm.

NOTE The information given in 1.4.1 may for convenience be presented in tabular form.

Normally, the numerical values shall be given for the length, width and height of the body. When necessary, for example, when a number of case sizes are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor.

1.4.2 Mounting

The detail specification shall give guidance on methods of mounting for normal use. Mounting for test and measurement purposes (if required) shall be in accordance with 4.3.

1.4.3 Ratings and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification, together with the following.

1.4.3.1 Rated capacitance range

See 2.2.1.

NOTE When products approved to the detail specification have different ranges, the following statement should be added: "The range of values available in each voltage range is given in the qualified products list (QPL).".

1.4.3.2 Particular characteristics

Additional characteristics may be listed, when they are considered necessary, to specify adequately the component for design and application purposes.

1.4.3.3 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability test and the resistance to soldering heat test.

1.4.4 Marking

The detail specification shall specify the content of the marking on the capacitor and on the package. Deviations from 1.5 of this sectional specification shall be specifically stated.

1.5 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60384-1, as well as the following, apply.

1.5.1

surface mount capacitor

capacitor whose small dimensions and nature or shape of terminations make it suitable for surface mounting in hybrid circuits and on printed boards