

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Integrated circuits – Measurement of electromagnetic emissions –
Part 1: General conditions and definitions**

**Circuits intégrés – Mesure des émissions électromagnétiques –
Partie 1: Conditions générales et définitions**





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



IEC 61967-1

Edition 2.0 2018-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Integrated circuits – Measurement of electromagnetic emissions –
Part 1: General conditions and definitions**

**Circuits intégrés – Mesure des émissions électromagnétiques –
Partie 1: Conditions générales et définitions**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.200

ISBN 978-2-8322-6284-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

- FOREWORD..... 4
- 1 Scope..... 6
- 2 Normative references 6
- 3 Terms and definitions 6
- 4 Test conditions 10
 - 4.1 General..... 10
 - 4.2 Ambient conditions..... 10
 - 4.2.1 General 10
 - 4.2.2 Ambient temperature 11
 - 4.2.3 Ambient RF field strength 11
 - 4.2.4 Other ambient conditions 11
 - 4.2.5 IC stability over time 11
- 5 Test equipment..... 11
 - 5.1 General..... 11
 - 5.2 Shielding..... 11
 - 5.3 RF measuring instrument 11
 - 5.3.1 General 11
 - 5.3.2 Measuring receiver 11
 - 5.3.3 Spectrum analyser 12
 - 5.3.4 Other RBW for narrowband emissions 12
 - 5.3.5 Emission type, detector type and sweep speed 12
 - 5.3.6 Video bandwidth 12
 - 5.3.7 Verification of calibration for the RF measuring instrument 12
 - 5.4 Frequency range..... 13
 - 5.5 Preamplifier or attenuator 13
 - 5.6 System gain 13
 - 5.7 Other components 13
- 6 Test set-up 13
 - 6.1 General..... 13
 - 6.2 Test circuit board 13
 - 6.3 IC pin loading..... 13
 - 6.4 Power supply requirements – Test board power supply 14
 - 6.5 IC specific considerations 14
 - 6.5.1 IC supply voltage 14
 - 6.5.2 IC decoupling 14
 - 6.5.3 Activity of IC 14
 - 6.5.4 Guidelines regarding IC operation 14
- 7 Test procedure 15
 - 7.1 Ambient RF noise check 15
 - 7.2 Operational check 15
 - 7.3 Specific procedures 15
- 8 Test report..... 15
 - 8.1 General..... 15
 - 8.2 Ambient RF noise 15
 - 8.3 Description of device 15
 - 8.4 Description of set-up 16

8.5	Description of software	16
8.6	Data presentation	16
8.6.1	General	16
8.6.2	Graphical presentation.....	16
8.6.3	Measurement data	16
8.6.4	Data processing.....	16
8.7	RF emission limits.....	16
8.8	Interpretation of results	16
8.8.1	Comparison between IC(s) using the same test method.....	16
8.8.2	Comparison between different test methods	16
8.8.3	Correlation to module test methods	16
Annex A (informative)	Test method comparison tables.....	17
Annex B (informative)	Flow chart of a counter test code.....	19
Annex C (informative)	Description of worst-case application software	20
Annex D (informative)	General test board description	21
D.1	General.....	21
D.2	Board description – Mechanical	21
D.3	Board description – Electrical.....	21
D.4	Ground planes	21
D.5	Package pins	22
D.5.1	General	22
D.5.2	DIL packages	22
D.5.3	SOP, PLCC, QFP packages.....	22
D.5.4	PGA packages.....	22
D.5.5	BGA packages.....	22
D.6	Via diameters.....	22
D.7	Via distance	22
D.8	Additional components	22
D.9	Supply decoupling.....	22
D.9.1	General	22
D.9.2	IC decoupling capacitors	23
D.9.3	Power supply decoupling for the test board	23
D.10	I/O load.....	23
Bibliography	25
Figure B.1	– Test code flow chart.....	19
Figure D.1	– Example of an emission test board	24
Table 1	– Measuring receiver bands and resolution bandwidth (RBW) default settings.....	11
Table 2	– Spectrum analyser bands and RBW default settings.....	12
Table 3	– IC pin loading recommendations	14
Table A.1	– Conducted emission.....	17
Table A.2	– Radiated emission	18
Table D.1	– Position of vias over the board.....	21

INTERNATIONAL ELECTROTECHNICAL COMMISSION

—————

**INTEGRATED CIRCUITS –
MEASUREMENT OF ELECTROMAGNETIC EMISSIONS –**
Part 1: General conditions and definitions**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61967-1 has been prepared by subcommittee 47A: Integrated circuits, of IEC technical committee 47: Semiconductor devices.

This second edition cancels and replaces the first edition published in 2002. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the frequency range of 150 kHz to 1 GHz has been deleted from the title;
- b) the frequency step above 1 GHz has been added to Table 1, Table 2 and to 5.4;
- c) Table A.1 has been divided into two tables, and IEC 61967-8 has been added to Table A.2 of Annex A;
- d) the general test board description has been moved to Annex D.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
47A/1062/FDIS	47A/1066/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61967 series, under the general title *Integrated circuits – Measurement of electromagnetic emissions*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTEGRATED CIRCUITS – MEASUREMENT OF ELECTROMAGNETIC EMISSIONS –

Part 1: General conditions and definitions

1 Scope

This part of IEC 61967 provides general information and definitions on the measurement of conducted and radiated electromagnetic disturbances from integrated circuits. It also provides a description of measurement conditions, test equipment and set-up as well as the test procedures and content of the test reports. Test method comparison tables are included in Annex A to assist in selecting the appropriate measurement method(s).

The object of this document is to describe general conditions in order to establish a uniform testing environment and to obtain a quantitative measure of RF disturbances from integrated circuits (IC). Critical parameters that are expected to influence the test results are described. Deviations from this document are noted explicitly in the individual test report. The measurement results can be used for comparison or other purposes.

Measurement of the voltage and current of conducted RF emissions or radiated RF disturbances, coming from an integrated circuit under controlled conditions, yields information about the potential for RF disturbances in an application of the integrated circuit.

The applicable frequency range is described in each part of IEC 61967.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and Methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

artificial network

AN

network presenting a reference load impedance (simulated) to the DUT (e.g. extended power or communication lines) across which the RF disturbance voltage is measured and which isolates the apparatus from the power supply or loads in a given frequency range

Note 1 to entry: This note applies to the French language only.

3.2

associated equipment

transducers (e.g. probes, networks and antennae) connected to a measuring receiver or test generator, also transducers used in the signal or disturbance transmission path between a DUT and measuring equipment or a (test-) signal generator

3.3

broadband disturbance

broadband emission

electromagnetic disturbance which has a bandwidth greater than that of a particular measuring apparatus, receiver or susceptible device

Note 1 to entry: For some purposes, particular spectral components of a broadband disturbance may be considered as narrowband disturbances.

Note 2 to entry: Emission that has a bandwidth greater than that of a particular measuring apparatus or receiver.

[SOURCE: IEC 60050-161:1990, 161-06-11, modified – Note 2 to entry and the second preferred term "broadband emission" have been added.]

3.4

common mode voltage

asymmetrical disturbance voltage

mean of the phasor voltages appearing between each conductor and a specified reference, usually earth or frame

[SOURCE: IEC 60050-161:1990, 161-04-09, modified – The word "disturbance" has been added to the admitted term.]

3.5

common mode current

vector sum of the currents flowing through two or more conductors at a specified cross-section of a mathematical plane intersected by these conductors

3.6

conducted emission

transient and/or other disturbance observed on the external terminals of a device during its normal operation

3.7

continuous disturbance

electromagnetic disturbance the effects of which on a particular device or equipment cannot be resolved into a succession of distinct effects

Note 1 to entry: RF disturbance with a duration of more than 200 ms at the IF-output of a measuring receiver that causes a deflection on the meter of a measuring receiver in quasi-peak detection mode that does not decrease immediately.

[SOURCE: IEC 60050-161:1990, 161-02-11, modified – Note 1 to entry has been added.]

3.8

DUT

device under test

device, equipment or system being evaluated

Note 1 to entry: As used in this document, DUT refers to a semiconductor device being tested.

Note 2 to entry: This note applies to the French language only.

3.9 die shrink

reduction of die size by using an advanced fabrication process including finer lithography node and masks

3.10 differential mode current

in a two-conductor cable, or for two particular conductors in a multi-conductor cable, half the magnitude of the difference of the phasors representing the currents in each conductor

[SOURCE: IEC 60050-161:1990, 161-04-38]

3.11 differential mode voltage

voltage between any two of a specified set of active conductors

[SOURCE: IEC 60050-161:1990, 161-04-08, modified – The second preferred term "symmetrical voltage" has been removed.]

3.12 discontinuous disturbance

electromagnetic disturbance, the effects of which on a particular device or equipment can be resolved into a succession of distinct effects

Note 1 to entry: It is recognised that this definition does not characterise the disturbance independently of the effect that it produces. As a practical matter, any measure of a disturbance should be relatable to its effect on a susceptible device.

Note 2 to entry: For counted clicks, disturbance with a duration of less than 200 ms at the IF-output of a measuring receiver, which causes a transient deflection on the meter of a measuring receiver in quasi-peak detection mode.

[SOURCE: IEC 60050-161:1990, 161-02-28, modified – Note 2 to entry has been added.]

3.13 electrically small PCB

printed circuit board with length and width shorter than $\lambda/2$, for example 100 mm to 150 mm at 1 GHz

3.14 EMC electromagnetic compatibility

ability of an apparatus or system to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment

3.15 electromagnetic emission

phenomenon by which electromagnetic energy emanates from a source

3.16 electromagnetic radiation radiated emission

- 1) phenomenon by which energy in the form of electromagnetic waves emanates from a source into space
- 2) energy transferred through space in the form of electromagnetic waves

[SOURCE: IEC 60050-161:1990, 161-01-10, modified – The second preferred term "radiated emission" has been added and the Note to entry has been omitted.]

3.17**emission limit**

<from a disturbing source> specified maximum emission level of a source of electromagnetic disturbance

[SOURCE: IEC 60050-161:1990, 161-03-12]

3.18**ground reference plane**

flat conductive surface whose potential is used as a common reference

[SOURCE: IEC 60050-161:2014, 161-04-36, modified – The term "reference-ground plane" has been changed to "ground reference plane", the definition has been condensed and the notes to entry, omitted.]

3.19**lead frame**

supporting structure for the silicon die that interfaces the external pins to the die

3.20**measuring receiver**

receiver for the measurement of disturbances with different detectors

Note 1 to entry: The bandwidth of the receiver should be as specified in CISPR 16-1-1.

3.21**narrowband emission**

electromagnetic disturbance, or spectral component thereof, which has a bandwidth less than or equal to that of a particular measuring apparatus, receiver or susceptible device

Note 1 to entry: Emission with bandwidth less than that of a particular measuring apparatus or receiver.

[SOURCE: IEC 60050-161:1990, 161-06-13, modified – The term "narrowband disturbance" has been changed to "narrowband emission" and Note 1 to entry has been added.]

3.22**peak detector**

detector, the output voltage of which is the peak value of the applied signal

[SOURCE: IEC 60050-161:1990, 161-04-24]

3.23**preamp noise floor**

inherent thermal noise generated by the first stage amplifier that limits the signal resolution of the measurement system

3.24**receiver terminal voltage****antenna voltage**

voltage generated by a source of radio disturbance and measured in dB (μV) by a radio disturbance measuring instrument conforming to the requirements of CISPR 16

Note 1 to entry: External voltage measured in dB (μV) at the input of a radio interference measuring instrument conforming to the requirements of CISPR 16-1-1.

[SOURCE: CISPR 25:2008, 3.8, modified – Note 1 to entry has been added.]

3.25

reference point

specific port or point on the test set-up where the measurement of the sampled parameter is made

3.26

repetition rate

number of surges, spikes, or pulses per unit of time

3.27

radio frequency ambient

RF ambient

electromagnetic environment

totality of electromagnetic phenomena existing at a given location

[SOURCE: IEC 60050-161:1990, 161-01-01, modified – The preferred terms "radio frequency ambient" and "RF ambient" have been added and Note 1 to entry has been removed.]

3.28

shielded enclosure

mesh or sheet metallic housing designed expressly for the purpose of separating electromagnetically the internal and external environment

[SOURCE: IEC 60050-161:1990, 161-04-37, modified – The second preferred term "screened room" has been omitted.]]

3.29

significant IC change

changes that may influence the electromagnetic emissions of an IC

Note 1 to entry: Examples include changes to a new device, new manufacturer or process line, die shrink, new package type, significant manufacturing process, internal/external clock, I/O drive capability.

3.30

system gain

gain (or attenuation) of the measurement path between the reference point and the input of the RF measuring instrument

3.31

test plan

document provided by the test requester to define the tests to be carried out, the object of the testing, the DUT operating status, the conditions for the test and performance objectives

Note 1 to entry: The test plan completely guides the implementation of the test, by reference to the standard test procedure, or by detailing revisions or additions for the specific DUT.

4 Test conditions

4.1 General

These default test conditions are intended to ensure a consistent test environment. If other values are agreed by the users of this procedure, they shall be documented in the test report.

4.2 Ambient conditions

4.2.1 General

The following ambient conditions shall be met.