IEC 62271-209

Edition 1.0 2007-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear – Part 209: Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV – Fluid-filled and extruded insulation cables – Fluid-filled and dry-type cable-terminations

Appareillage à haute tension – Partie 209: Raccordement de câbles pour appareillage sous enveloppe métallique à isolation gazeuse de tension assignée supérieure à 52 kV – Câbles remplis d'un fluide ou à isolation extrudée – Extrémité de câble sèche ou remplie d'un fluide

IEC 62271-209:2007

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub
The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, withdrawn and replaced publications.
- IEC Just Published: www.iec.ch/online_news/justpub
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.
- Electropedia: www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.
- Customer Service Centre: www.iec.ch/webstore/custserv
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:
Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm
Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,…). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.
- Just Published CEI: www.iec.ch/online_news/justpub
Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.
- Electropedia: www.electropedia.org
Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.
- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:
Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

IEC 62271-209

Edition 1.0 2007-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear – Part 209: Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV – Fluid-filled and extruded insulation cables – Fluid-filled and dry-type cable-terminations

Appareillage à haute tension – Partie 209: Raccordement de câbles pour appareillage sous enveloppe métallique à isolation gazeuse de tension assignée supérieure à 52 kV – Câbles remplis d'un fluide ou à isolation extrudée – Extrémité de câble sèche ou remplie d'un fluide

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.130.10

ISBN 2-8318-9242-2

CONTENTS

FOREWORD 3

1 Scope 5
2 Normative references 5
3 Terms and definitions 6
4 Limits of supply 7
4.1 General 7
4.2 Over-voltage protection 7
5 Rating 7
5.1 General 7
5.2 Rated voltage 7
5.3 Rated insulation level 8
5.4 Rated normal current and temperature rise 8
5.5 Rated short-time and peak withstand currents and rated duration of short circuit 8
5.6 Rated filling pressure of insulating gas in the cable connection enclosure 8
6 Design and construction requirements 9
6.1 Pressure withstand requirements 9
6.2 Mechanical forces on cable-terminations 9
7 Standard dimensions 10
7.1 Fluid-filled cable-terminations 10
7.2 Dry-type cable-terminations 10
7.3 Three-phase cable-termination enclosure 10
8 Tests 10
8.1 General 10
8.2 Dielectric type tests of cable-terminations 11
8.2.1 General 11
8.2.2 Dielectric type test of cable-terminations in a single phase enclosure 11
8.2.3 Dielectric type test of cable-termination in a three phase enclosure 11
8.3 Tests after cable system installation 11
9 Information to be given with enquiries, tenders and orders 12
10 Rules for transport, storage, erection, operation and maintenance 12

Figure 1 – Operating pressure of the gas insulation in the cable connection enclosure 9
Figure 2 – Fluid-filled cable connection assembly – Typical arrangement 13
Figure 3 – Fluid-filled cable connection – Assembly dimensions 14
Figure 4 – Dry-type cable connection assembly – Typical arrangement 15
Figure 5 – Dry-type cable connection assembly – Assembly dimensions 16

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 209: Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV – Fluid-filled and extruded insulation cables – Fluid-filled and dry-type cable-terminations

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62271-209 has been prepared by subcommittee 17C: High-voltage switchgear and controlgear assemblies, of IEC technical committee 17: Switchgear and controlgear.

This first edition of IEC 62271-209 cancels and replaces the second edition of IEC/TS 60859 and constitutes a technical revision. The changes from IEC/TS 60859 are as follows:

– the minimum voltage rating was changed from "72,5 kV" to "above 52 kV";
– the current rating was increased to 3150 A;

– simplifications and modifications of the dimension tables in Figure 2 and Figure 4 such as diameters for 123 kV to 170 kV have been adopted in order to accommodate larger cable cross-sections; new dimensions accept old terminations, new terminations may not meet old GIS standards;

– the following dimensions have been deleted: l1, l3 as well as note 3 on Figure 4;

– in Figure 4, new dimensions have been adopted for the voltage range from 245 kV to 300 kV, interchangeability for 245 kV to 300 kV is not maintained due to reduction in GIS cable termination housing;

– the lengths l7 and l8 have been modified;

– changes in the text in relation to minimum functional pressure for insulation p_{me} (Table 1 has been removed);

– the limit of 170 kV for 3-phase application was deleted (Subclause 5.2);

– Figure 5 was deleted.

The text of this standard is based on the following documents:

FDIS	Report on voting
17C/405/FDIS	17C/412/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62271 series, under the general title *High-voltage switchgear and controlgear*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 209: Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV – Fluid-filled and extruded insulation cables – Fluid-filled and dry-type cable-terminations

1 Scope

This standard covers the connection assembly of fluid-filled and extruded cables to gas-insulated metal enclosed switchgear (GIS), in single- or three-phase arrangements where the cable-terminations are fluid-filled or dry type and there is a separating insulating barrier between the cable insulation and the gas insulation of the switchgear.

The purpose of this standard is to establish electrical and mechanical interchangeability between cable-terminations and the gas-insulated metal-enclosed switchgear and to determine the limits of supply. It complements and amends, if necessary, the relevant IEC standards. For the purpose of this standard the term "switchgear" is used for "gas-insulated metal enclosed switchgear".

It does not cover directly immersed cable terminations, as described in CIGRE brochure 89.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60038:1983, *IEC standard voltages* [1]
Amendment 1 (1994)
Amendment 2 (1997)

IEC 60141 (all parts), *Tests on oil-filled and gas-pressure cables and their accessories*

IEC 60141-1:1993, *Tests on oil-filled and gas-pressure cables and their accessories – Part 1: Oil-filled, paper-insulated, metal-sheathed cables and accessories for alternating voltages up to and including 400 kV*

IEC 60141-2:1963, *Tests on oil-filled and gas-pressure cables and their accessories – Part 2: Internal gas-pressure cables and accessories for alternating voltages up to 275 kV*

IEC 60694:1996, *Common specifications for high-voltage switchgear and controlgear standards*

IEC 60840:2004, *Power cables with extruded insulation and their accessories for rated voltages above 30 kV (U_m = 36 kV) up to 150 kV (U_m = 170 kV) – Test methods and requirements*

---

[1] There exists a consolidated version (2002) including Amendment 1 and 2.