

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Plugs, socket-outlets and ship couplers for high-voltage shore connection systems (HVSC-Systems) – Part 1: General requirements

Prises de courant et connecteurs de navire pour les systèmes haute tension de raccordement des navires à quai – Partie 1: Règles générales



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Plugs, socket-outlets and ship couplers for high-voltage shore connection systems (HVSC-Systems) – Part 1: General requirements

Prises de courant et connecteurs de navire pour les systèmes haute tension de raccordement des navires à quai – Partie 1: Règles générales

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XA**
CODE PRIX

ICS 29.120.30

ISBN 978-2-88912-545-6

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions.....	8
4 General.....	11
5 Standard ratings.....	12
6 Classification.....	13
7 Marking.....	13
8 Dimensions.....	15
9 Protection against electric shock.....	16
10 Provision for Earthing.....	16
11 Terminals and terminations.....	18
12 Locking devices and interlocks.....	23
13 Resistance to ageing of rubber and thermoplastic material.....	24
14 General construction.....	24
15 Construction of socket-outlets and ship inlets.....	26
16 Construction of ship connectors.....	26
17 Construction of plugs.....	26
18 Degrees of protection.....	27
19 Insulation resistance, dielectric withstand and partial discharge tests.....	28
20 Normal operation.....	30
21 Temperature rise.....	31
22 Flexible cables and their connection.....	32
23 Mechanical strength.....	35
24 Screws, current-carrying parts and connections.....	36
25 Resistance to heat, to fire and to tracking.....	38
26 Corrosion and resistance to rusting.....	40
27 Conditional short-circuit current withstand test.....	40
28 Electromagnetic compatibility.....	42
Bibliography.....	52
Figure 1 – Diagram showing the use of the accessories.....	43
Figure 2 – Standard test finger.....	44
Figure 3 – Circuit diagrams for normal operation tests of 3P+E accessories and 3P+E with separate Neutral accessories.....	45
Figure 4 – Apparatus for testing the cable anchorage.....	46
Figure 5 – Arrangement for mechanical strength test for plugs and ship connectors.....	46
Figure 6 – Gauges for testing insertability of round unprepared conductors having the maximum specified cross-section.....	47
Figure 7 – Examples of terminals.....	49
Figure 8 – Test apparatus for checking damage to conductors.....	49

Figure 9 – Diagram of the test circuit for the verification of short-circuit current withstand of a three-pole equipment	50
Figure 10 – Diagram of the test circuit for the verification of short-circuit current withstand of a Three-Phase and separate Neutral accessories	51
Table 1 – Size for connectable conductors	18
Table 2 – Test values for flexing tests for copper conductors	22
Table 3 – Test values for pull-out tests for copper conductors	23
Table 4 – Test voltage for dielectric strength test of pilot contacts	29
Table 5 – Dielectric withstand test voltage	30
Table 6 – Test current and conductor cross-section for temperature rise	32
Table 7 – Maximum surface temperatures	32
Table 8 – Flexible cable types and dimensions, including conductor sizes and wire type	34
Table 9 – Cable secureness test values	34
Table 10 – Screw sizes and torque test values	37

Withdrawn

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PLUGS, SOCKET-OUTLETS AND SHIP COUPLERS
FOR HIGH-VOLTAGE SHORE CONNECTION SYSTEMS
(HVSC-SYSTEMS) –**

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62613-1 has been prepared by subcommittee 23H: Industrial plugs and socket-outlets, of IEC technical committee 23: Electrical accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
23H/254/FDIS	23H/259/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

- requirements proper: in roman type;
- *test specifications: in italic type;*
- notes: in smaller roman type.

A list of all the parts in the IEC 62613 series, under the general title *Plugs, socket-outlets and ship couplers for high-voltage shore connection systems (hvsc-systems)*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

Withdrawn

INTRODUCTION

International Standard IEC 62613-1 has been primarily written to address the needs of the IEC/PAS 60092-510 High Voltage Shore Connection Systems, in terms of plugs, socket-outlets, ship connectors and ship inlets, herein referred to as “accessories”, to deliver electrical power to ships in ports. The purpose of the IEC/PAS 60092-510 is to define requirements that allow compliant ships to connect to compliant high-voltage shore power supplies through a compatible shore-to-ship connection.

Ships that do not require connecting with standardized high-voltage shore power supplies as above may use accessories that are not covered by the standard sheets of IEC 62613-2 but they may find it impossible to connect to these shore supplies.

Other low voltage plugs, socket-outlets, ship connectors and ship inlets used for the connection of certain ship types to low-voltage shore power supplies may be found in the IEC 60309 series.

International Standard IEC 62613 is divided into several parts:

Part 1: General requirements, comprising clauses of a general character.

Part 2: Dimensional compatibility and interchangeability requirements for accessories used for ship-to-shore connections, comprising standard sheets for different types of accessories.

These ships are described in IEC/PAS 60092-510.

Withhold

PLUGS, SOCKET-OUTLETS AND SHIP COUPLERS FOR HIGH-VOLTAGE SHORE CONNECTION SYSTEMS (HVSC-SYSTEMS) –

Part 1: General requirements

1 Scope

This part of IEC 62613 applies to accessories with

- three phases (3 poles and Earth) with up to three pilot contacts,
- one single pole (Neutral).

These accessories have rated currents not exceeding 500 A and rated operating voltages not exceeding 12 kV 50/60 Hz.

NOTE 1 In the USA, the term "Ground" is used instead of "Earth".

These accessories are primarily intended for use outdoors, in a seawater environment, for the shore supply of ships (ship-to-shore connection), in an ambient temperature within the range of -25 °C to +45 °C.

NOTE 2 In some countries, other ambient temperatures may prevail and may need to be taken into account.

These accessories are not intended for use in hazardous areas. In such locations where special conditions prevail, additional requirements may be necessary.

These accessories are intended to be connected to cables of copper or copper alloy only.

Socket-outlets or ship inlets incorporated in or fixed to electrical equipment are within the scope of this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-75, *Environmental testing – Part 2-75: Tests – Test Eh: Hammer tests*

IEC 60092 (all parts), *Electrical installations in ships*

IEC 60092-101:1994, *Electrical installations in ships – Part 101: Definitions and general requirements*

IEC 60092-354, *Electrical installations in ships – Part 354: Single- and three-core power cables with extruded solid insulation for rated voltages 6 kV ($U_m = 7,2$ kV) up to 30 kV ($U_m = 36$ kV)*

IEC 60112:2003, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*

IEC 60228, *Conductors of insulated cables*

IEC 60269-1:2006, *Low-voltage fuses – Part 1: General requirements*

IEC 60269-2:2010, *Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to J*

IEC 60502-4:2010, *Power cables with extruded insulation and their accessories for rated voltages from 1 kV ($U_m = 1,2$ kV) up to 30 kV ($U_m = 36$ kV) – Part 4: Test requirements on accessories for cables with rated voltages from 6 kV ($U_m = 7,2$ kV) up to 30 kV ($U_m = 36$ kV)*

IEC 60529, *Degrees of protection provided by enclosures (IP code)*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 60695-2-11, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products*

IEC 60695-10-2, *Fire hazard testing – Part 10-2: Abnormal heat – Ball pressure test*

IEC 62262, *Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)*

IEC 62271-1, *High voltage Switchgear and Controlgear – Part 1: Common specifications*

IEEE 1580, *Recommended Practice for Marine Cable for use on Shipboard and Fixed or Floating Marine Platforms*

ASTM B117-1985, *Standard practice for operating salt spray (fog) apparatus*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE Where the terms “voltage” and “current” are used, they imply the a.c. r.m.s. values.

3.1

accessory

plugs, socket-outlets, ship connectors and ship inlets

NOTE The application of accessories is shown in Figure 1.

3.2

socket-outlet

the part intended to be installed with the fixed wiring or incorporated in equipment

NOTE A socket-outlet may also be incorporated in the output circuit of an isolating transformer.

3.3

plug

the part intended to be attached directly to one flexible cable

3.4**ship coupler**

a means enabling the connection at will of a flexible cable to the ship. It consists of two parts, a ship connector and ship inlet

3.5**ship connector**

the part intended to be attached to one flexible cable connected to the supply

3.6**ship inlet**

the part incorporated in, or fixed to, the ship

3.7**interlock**

a device, either electrical and/or mechanical, which prevents the contacts of a plug from becoming live before it is in proper engagement with a socket-outlet, and which either prevents the plug or the ship connector from being withdrawn while its contacts are live or makes the contacts dead and Earthed before separation

NOTE In the USA, the term "Grounded" is used instead of "Earthed".

3.8**retaining device**

a mechanical arrangement which holds a plug or ship connector in position when it is in proper engagement, and prevents its unintentional withdrawal

3.9**cap**

a part separated or attached, which may be used to provide the degree of protection of a plug or ship inlet when it is not engaged with a socket-outlet or ship connector

3.10**lid**

a means to ensure the degree of protection on a socket-outlet or a ship connector

3.11**insulation voltage**

the voltage assigned to the accessory by the manufacturer and to which dielectric tests, clearances and creepage distances are referred

3.12**rated current**

the current assigned to the accessory by the manufacturer

3.13**rated operating voltage**

the nominal voltage of the supply for which the accessory is intended to be used

3.14**conditional short-circuit current**

the prospective current that an accessory, protected by a specified short-circuit protective device, can satisfactorily withstand for the total operating time of that device under specified conditions of use and behaviour

NOTE This definition differs from definition 17-20 of IEC 60050-441 by broadening the concept of current-limiting device into a short-circuit protective device, the function of which is not only to limit the current.

3.15

live

a conductor or circuit is live when a difference of potential exists between it and Earth

(IEC 60092-101:1994, definition 1.3.14)

3.16

clamping unit

the part of a terminal necessary for the clamping and the electrical connection of the conductor

3.17

terminal

a conductive part provided for the connection of a conductor to an accessory

3.17.1

pillar terminal

〈pilot conductors〉 a terminal in which the conductor is inserted into a hole or cavity, where it is clamped under the shank of the screw or screws. The clamping pressure may be applied directly by the shank of the screw or through an intermediate clamping member to which pressure is applied by the shank of the screw (see Figure 7a)

3.17.2

screw terminal

〈pilot conductors〉 a terminal in which the conductor is clamped under the head of the screw. The clamping pressure may be applied directly by the head of the screw or through an intermediate part, such as a washer, clamping plate or anti-spread device (see Figures 7b and 7c)

3.17.3

stud terminal

〈pilot conductors〉 a terminal in which the conductor is clamped under a nut. The clamping pressure may be applied directly by a suitably shaped nut or through an intermediate part, such as a washer, clamping plate or anti-spread device (see Figure 7d)

3.17.4

saddle terminal

〈pilot conductors〉 a terminal in which the conductor is clamped under a saddle by means of two or more screws or nuts (see Figure 7e)

3.17.5

lug terminal

a screw terminal or a stud terminal, designed for clamping a cable lug or bar by means of a screw or nut (see Figure 7f)

3.17.6

crimping terminal

a terminal in which the conductor is crimped by means of an adequate tool

3.17.7

soldering terminal

a terminal in which the conductor is soldered

3.17.8

mantle terminal

〈Earth conductor〉 a terminal in which the conductor is clamped against the base of a slot in a threaded stud by means of a nut. The conductor is clamped against the base of the slot by a

suitably shaped washer under the nut, by a central peg if the nut is a cap nut, or by equally effective means for transmitting the pressure from the nut to the conductor within the slot (see Figure 7g)

3.18

non-rewireable accessory

accessory so constructed that the cable or wiring cannot be separated from the accessory without making it permanently useless

3.19

field-rewireable accessory

accessory so constructed that it can be rewired by skilled personnel as qualified by the manufacturer

3.20

non field-rewireable accessory

accessory so constructed that it can only be rewired by the manufacturer's authorised personnel

3.21

user-serviceable accessory

accessory so constructed that parts can be replaced, using commonly available tools

3.22

non user-serviceable accessory

accessory so constructed that parts can only be replaced by the manufacturer's authorised personnel

3.23

(electrically) skilled person

person with technical training and knowledge to enable him or her to perform the assigned task without creating a hazard

[IEC 60050-195, Amendment 1:2001, definition 04-01 modified]

3.24

(electrically) instructed person

person adequately advised or supervised by electrically skilled persons to enable him or her to perceive risks and to avoid hazards which electricity can create

[IEC 60050-195, Amendment 1:2001, definition 04-02]

4 General

4.1 General requirements

Accessories shall be supplied with all the necessary instructions from the manufacturer, e.g. installation, assembling, wiring, commissioning, inspection, preventive maintenance, replacement of consumable parts, etc., including the levels of ability of the personnel to perform such operations.

Accessories shall be so designed and constructed that in normal use their performance is reliable and without danger to the user or surroundings.

Accessories constructed in accordance with this standard shall be suitable for the environment conditions in the space(s) where they are intended to operate. Accessories located on ships shall comply with the applicable part(s) of IEC 60092.