

## INFORMATION TECHNOLOGY EQUIPMENT – RADIO DISTURBANCE CHARACTERISTICS – LIMITS AND METHODS OF MEASUREMENT

### INTERPRETATION SHEET 3

This interpretation sheet has been prepared by subcommittee 1: Electromagnetic compatibility of information technology equipment, multimedia equipment and receivers, of IEC technical committee CISPR: International special committee on radio interference.

The text of this interpretation sheet is based on the following documents:

ISH	Report on voting
CISPR/1/402/ISH	CISPR/1/408/RVD

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

#### Introduction:

At the CISPR SC 1 plenary, held on the 19th October 2011, it was noted that some laboratories and manufacturers are having difficulty understanding Figure C.5 in the standard and are applying the wrong branch in the decision tree to identify the correct method for testing different types of equipment with a telecommunication port.

This information does not change the standard; it serves only to clarify the point noted.

CISPR SC 1 WG3 hopes that these clarifications will be of use to users and especially laboratories testing to CISPR 22, Edition 6.0 or Edition 5. The document is based on the comments received on CISPR/1/402/ISH.

#### Interpretation:

Figure C.5 provides a flowchart to correctly identify the process and limits for measuring conducted emissions on a telecommunication port.

The first question to be answered is “*Is the EUT port a telecommunication port as defined in clause 3.6?*” The following interpretation assumes the response to this first question is “yes”.

The intention of the next part of the flow chart is to relate the telecommunication port being measured to the type of cable or network to which it is to be connected. The purpose here is to guide the user to the appropriate test method(s) that are defined in the standard for these cable/network types.

The user should determine which of the options given best describes the type of cable or network that the telecommunication port is ultimately connected to. The following interpretations provide further guidance on the cable or network options given: