

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Low-voltage switchgear and controlgear –
Part 5-2: Control circuit devices and switching elements – Proximity switches**

**Appareillage à basse tension –
Partie 5-2: Appareils et éléments de commutation pour circuits de commande –
DéTECTEURS DE PROXIMITÉ**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Low-voltage switchgear and controlgear –
Part 5-2: Control circuit devices and switching elements – Proximity switches**

**Appareillage à basse tension –
Partie 5-2: Appareils et éléments de commutation pour circuits de commande –
DéTECTEURS de proximité**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XD

CONTENTS

FOREWORD.....	6
1 General.....	8
1.1 Scope and object.....	8
1.2 Normative references.....	8
2 Definitions.....	10
2.1 Basic definitions.....	12
2.2 Parts of a proximity switch.....	13
2.3 Operation of a proximity switch.....	15
2.4 Switching element characteristics.....	17
3 Classification.....	20
3.1 Classification according to sensing means.....	20
3.2 Classification according to the mechanical installation.....	20
3.3 Classification according to the construction form and size.....	20
3.4 Classification according to switching element function.....	20
3.5 Classification according to type of output.....	20
3.6 Classification according to method of connection.....	20
4 Characteristics.....	20
4.1 Summary of characteristics.....	20
4.2 Operating conditions.....	21
4.3 Rated and limiting values for the proximity switch and switching element(s).....	23
4.4 Utilization categories for the switching element.....	24
5 Product information.....	25
5.1 Nature of information – Identification.....	25
5.2 Marking.....	26
5.3 Instruction for installation, operation and maintenance.....	26
6 Normal service, mounting and transport conditions.....	26
6.1 Normal service conditions.....	26
6.2 Conditions during transport and storage.....	27
6.3 Mounting.....	27
7 Constructional and performance requirements.....	27
7.1 Constructional requirements.....	27
7.2 Performance requirements.....	30
7.3 Physical dimensions.....	40
7.4 Shock and vibration.....	40
8 Tests.....	40
8.1 Kinds of tests.....	41
8.2 Compliance with constructional requirements.....	41
8.3 Performances.....	41
8.4 Testing of operating distances.....	50
8.5 Testing for the frequency of operating cycles.....	54
8.6 Verification of the electromagnetic compatibility.....	58
8.7 Test results and test report.....	59

Annex A (informative) Typical dimensions and operating distances of proximity

switches.....	60
Annex B (normative) Class II proximity switches insulated by encapsulation – Requirements and tests	86
Annex C (normative) Additional requirements for proximity switches with integrally connected cables	90
Annex D (normative) Integral connectors for plug-in proximity switches.....	93
Annex E (normative) Additional requirements for proximity switches suitable for use in strong magnetic fields	97
Annex F (informative) Symbols for proximity switches.....	102
Figure 1 – Sensing range and operating range of photoelectric proximity switches (see 7.2.1.3 and 8.4).....	16
Figure 2 – Ultrasonic proximity switch operating distances.....	18
Figure 3 – Relationship between operating distances of inductive and capacitive proximity switches (see 4.2.1, 7.2.1.3 and 8.4.1)	22
Figure 4 – Relationship between operating distances of ultrasonic proximity switches (see 4.2.2, 7.2.1.3 and 8.4.1)	22
Figure 5 – Method of measuring the operating distance (8.3.2.1 and 8.4.1).....	43
Figure 6 – Test circuit for the verification of time delay before availability (see 7.2.1.7 and 8.3.3.2.1).....	44
Figure 7 – Signal output across load in Figure 6 (see 8.3.3.2.1).....	45
Figure 8 – Test circuit for the verification of minimum operational current OFF-state current, voltage drop and independent snap action (see 8.3.3.2.2, 8.3.3.2.3, 8.3.3.2.4 and 8.3.3.2.5).....	46
Figure 9 – Test circuit for the verification of making and breaking capability (see 8.3.3.5)	49
Figure 10 – Short-circuit testing (see 8.3.4.2).....	50
Figure 11 – Testing of the sensing range (see 8.4)	53
Figure 12 – Methods for measuring the operating frequency of inductive, capacitive and non-mechanical magnetic proximity switches (if applicable)	54
Figure 13 – Methods for measuring the operating frequency f , ultrasonic proximity switch	55
Figure 14 – Output signal of direct current proximity switch during the measurement of operating frequency f	55
Figure 15 – Measurement means for turn-on time t_{on} and turn-off time t_{off}	56
Figure 16 – Turn-on time t_{on} measurement.....	57
Figure 17 – Turn-off time t_{off} measurement	57
Figure A.1 (IA) – Dimensions.....	60
Figure A.2 (IA) – Installation (mounting)	62
Figure A.1 (IB) – Dimensions.....	63
Figure A.2 (IB) – Installation in damping material.....	64
Figure A.1 (IC) – Dimensions in millimetres	65
Figure A.1.2 (IC) – Dimensions in millimetres	66
Figure A.1.3 (IC) – Dimensions in millimetres	66
Figure A.1.4 (IC) – Dimensions in millimetres	67
Figure A.2 (IC) – Installation of a I1C proximity switch in damping material	68
Figure A.3 (IC) – Installation of I2C35 in damping material.....	69
Figure A.1 (ID) – Dimensions	70

Figure A.2 (ID) – Installation of I2D in damping material	71
Figure A.1 (CA) – Dimensions	72
Figure A.2 (CA) – Installation (mounting)	73
Figure A.1 (CC) a – Dimensions, type C30 in millimetres	75
Figure A.1 (CC) b – Dimensions, type C40 in millimetres	76
Figure A.2 (CC) – Installation (mounting)	77
Figure A.1 (CD) – Dimensions in millimetres	78
Figure A.2 (CD) – Installation (mounting)	79
Figure A.1 (UA) – Dimensions	80
Figure A.1 (UC) – Dimensions of type U3C40	82
Figure A.1 (UD) – Dimensions of type U3D80 in millimetres	84
Figure B.1 – Encapsulated device	87
Figure B.2 – Test device	89
Figure D.1 – M12 Ø 3-pin integral connector for a.c. proximity switches	93
Figure D.2 – M12 Ø 5-pin integral connector for d.c. proximity switches	94
Figure D.3 – 8 mm Ø 3-pin integral connector for d.c. proximity switches	94
Figure D.4 – 8 mm Ø 4-pin integral connector for d.c. proximity switches	95
Figure D.5 – M12 Ø 4-pin integral connector for a.c. proximity switches	95
Figure D.6 – M12 Ø 5-pin integral connector for a.c. proximity switches	96
Figure D.7 – M12 Ø 6-pin integral connector for a.c. proximity switches	96
Figure E.1 – Examples of test configuration for verification of the immunity to an alternating field	100
Figure E.2 – Example of test configuration for verification of the immunity in a constant magnetic field	101
Figure F.1 – Examples of symbols for proximity switches	102
Table 1 – Classification of proximity switches	19
Table 2 – Utilization categories for switching elements	25
Table 3 – Connection and wiring identification	29
Table 4 – Verification of making and breaking capacities of switching elements under normal conditions corresponding to the utilization categories ^a	35
Table 5 – Verification of making and breaking capacities of switching elements under abnormal conditions corresponding to the utilization categories ^a	36
Table 7 – Acceptance criteria	37
Table 8 – Immunity tests	38
Table 6 – Test voltages	48
Table A.1 (IA) – Dimensions in millimetres	61
Table A.2 (IA) – Rated operating distances in millimetres	61
Table A.1 (IB) – Dimensions in millimetres	63
Table A.2 (IB) – Rated operating distance in millimetres	64
Table A.2 (IC) – Rated operating distance in millimetres	67
Table A.1 (ID) – Dimensions in millimetres	70
Table A.2 (ID) – Rated operating distances in millimetres	71
Table A.1 (CA) – Dimensions in millimetres	72

Table A.2 (CA) – Rated operating distances in millimetres	73
Table A.2 (CC) – Rated operational distance in millimetres	76
Table A.1 (UA) – Dimensions in millimetres	80
Table A.2 (UA) – Requirements for sensing range in millimetres	81
Table A.1 (UC) – Requirements for sensing range in millimetres	82
Table A.2 (UD) – Requirements for sensing range in millimetres	85

Withdrawn