

INTERNATIONAL STANDARD

**Adjustable speed electrical power drive systems –
Part 7-204: Generic interface and use of profiles for power drive systems –
Profile type 4 specification**

Withhold



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Adjustable speed electrical power drive systems –
Part 7-204: Generic interface and use of profiles for power drive systems –
Profile type 4 specification**

Withhold

IEC 61800-7-204 Ed. 1.0 - Preview only Copy via ILNAS e-Shop

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

CONTENTS

FOREWORD.....	35
INTRODUCTION.....	37
1 Scope.....	40
2 Normative references	40
3 Terms, definitions and abbreviated terms	40
3.1 Terms and definitions	40
3.2 Abbreviated terms	45
4 General	46
5 Data types.....	46
6 Short description of SERCOS data exchange	46
6.1 General.....	46
6.2 Synchronisation.....	47
7 Application function groups	47
7.1 General.....	47
7.2 Scaling of operation data.....	48
7.2.1 General	48
7.2.2 Scaling of position data	48
7.2.3 Scaling of velocity data.....	49
7.2.4 Scaling of torque/force data.....	51
7.2.5 Scaling of acceleration data and jerk data	53
7.2.6 Scaling of temperature data.....	55
7.3 Drive parameters.....	55
7.3.1 Velocity loop parameters	55
7.3.2 Position loop parameters.....	56
7.3.3 Current loop parameters.....	57
7.3.4 Drive limit values	57
7.3.5 General drive parameters	57
7.3.6 Spindle parameters	58
7.3.7 Spindle synchronous operation.....	58
7.4 Mechanics.....	59
7.4.1 Feedback systems.....	59
7.4.2 Feed constant.....	59
7.4.3 Gear train	60
7.4.4 Polarities	60
7.4.5 Parameter sets and gear ratios.....	61
7.4.6 Switching of parameter sets and gear ratio	62
7.5 Drive operation modes	62
7.5.1 General	62
7.5.2 Selection of the operation mode	63
7.5.3 Switching of the operation mode.....	64
7.6 Homing.....	66
7.6.1 General	66
7.6.2 Drive controlled homing procedure command	66
7.6.3 Control unit controlled homing procedure command	68
7.7 Measurements.....	71

7.8	Position spindle procedure command	72
7.8.1	General	72
7.8.2	Spindle Positioning when the function is started	73
7.8.3	New position values while the procedure command is active	74
7.8.4	Switching the positioning mode angle position/relative offset while the procedure command is active	74
7.9	Velocity window	75
7.10	Position switches	76
7.10.1	General	76
7.10.2	Position switch mode	77
7.10.3	Cam switch mode	77
7.11	PDS state machine control	78
7.11.1	Control and status word	78
7.11.2	Starting/stopping functions (State machine)	80
7.12	Park axis procedure command	83
7.13	Positive stop drive procedure command	83
7.14	Drive controlled synchronous operation procedure command	84
7.14.1	General	84
7.14.2	Synchronisation of the synchronous spindle to the lead spindle with a fixed angular offset	84
7.14.3	New synchronous position offset after synchronisation	85
7.14.4	New speed ratio after synchronisation	85
7.15	Drive controlled gear engaging procedure command	86
8	Identification numbers in numerical order	87
9	Description of identification numbers	100
9.1	IDN S-0-0005 Minimum feedback processing time (t_5)	100
9.1.1	Attributes	100
9.1.2	Description	101
9.2	IDN S-0-0007 Feedback acquisition capture point (t_4)	101
9.2.1	Attributes	101
9.2.2	Description	101
9.3	IDN S-0-0011 Class 1 diagnostic (C1D)	101
9.3.1	Attributes	101
9.3.2	Description	102
9.4	IDN S-0-0012 Class 2 diagnostic (C2D)	103
9.4.1	Attributes	103
9.4.2	Description	103
9.5	IDN S-0-0013 Class 3 diagnostic (C3D)	104
9.5.1	Attributes	104
9.5.2	Description	104
9.6	IDN S-0-0016 Configuration list of AT	105
9.6.1	Attributes	105
9.6.2	Description	105
9.7	IDN S-0-0017 IDN-list of all operation data	105
9.7.1	Attributes	105
9.7.2	Description	105
9.8	IDN S-0-0018 IDN-list of operation data for CP2	105
9.8.1	Attributes	105
9.8.2	Description	106

9.9	IDN S-0-0019 IDN-list of operation data for CP3.....	106
9.9.1	Attributes.....	106
9.9.2	Description.....	106
9.10	IDN S-0-0020 IDN-list of operation data for CP4.....	106
9.10.1	Attributes.....	106
9.10.2	Description.....	107
9.11	IDN S-0-0021 IDN-list of invalid operation data for CP2.....	107
9.11.1	Attributes.....	107
9.11.2	Description.....	107
9.12	IDN S-0-0022 IDN-list of invalid operation data for CP3.....	107
9.12.1	Attributes.....	107
9.12.2	Description.....	108
9.13	IDN S-0-0023 IDN-list of invalid operation data for CP4.....	108
9.13.1	Attributes.....	108
9.13.2	Description.....	108
9.14	IDN S-0-0025 IDN-list of all procedure commands.....	108
9.14.1	Attributes.....	108
9.14.2	Description.....	109
9.15	IDN S-0-0026 Configuration list for signal status word.....	109
9.15.1	Attributes.....	109
9.15.2	Description.....	109
9.16	IDN S-0-0027 Configuration list for signal control word.....	109
9.16.1	Attributes.....	109
9.16.2	Description.....	110
9.17	IDN S-0-0030 Manufacturer version.....	110
9.17.1	Attributes.....	110
9.17.2	Description.....	110
9.18	IDN S-0-0031 Hardware version.....	110
9.18.1	Attributes.....	110
9.18.2	Description.....	111
9.19	IDN S-0-0032 to S-0-0035 Primary operation mode, secondary operation modes 1 to 3.....	111
9.19.1	Attributes.....	111
9.19.2	Description.....	111
9.20	IDN S-0-0036 Velocity command value.....	111
9.20.1	Attributes.....	111
9.20.2	Description.....	112
9.21	IDN S-0-0037 Additive velocity command value.....	112
9.21.1	Attributes.....	112
9.21.2	Description.....	112
9.22	IDN S-0-0038 Positive velocity limit value.....	112
9.22.1	Attributes.....	112
9.22.2	Description.....	113
9.23	IDN S-0-0039 Negative velocity limit value.....	113
9.23.1	Attributes.....	113
9.23.2	Description.....	113
9.24	IDN S-0-0040 Velocity feedback value 1.....	113
9.24.1	Attributes.....	113
9.24.2	Description.....	114

9.25	IDN S-0-0041 Homing velocity.....	114
9.25.1	Attributes.....	114
9.25.2	Description.....	114
9.26	IDN S-0-0042 Homing acceleration.....	114
9.26.1	Attributes.....	114
9.26.2	Description.....	115
9.27	IDN S-0-0043 Velocity polarity parameter.....	115
9.27.1	Attributes.....	115
9.27.2	Description.....	115
9.28	IDN S-0-0044 Velocity data scaling type.....	116
9.28.1	Attributes.....	116
9.28.2	Description.....	116
9.29	IDN S-0-0045 Velocity data scaling factor.....	117
9.29.1	Attributes.....	117
9.29.2	Description.....	117
9.30	IDN S-0-0046 Velocity data scaling exponent.....	117
9.30.1	Attributes.....	117
9.30.2	Description.....	118
9.31	IDN S-0-0047 Position command value.....	118
9.31.1	Attributes.....	118
9.31.2	Description.....	118
9.32	IDN S-0-0048 Additive position command value.....	118
9.32.1	Attributes.....	118
9.32.2	Description.....	119
9.33	IDN S-0-0049 Positive position limit value.....	119
9.33.1	Attributes.....	119
9.33.2	Description.....	119
9.34	IDN S-0-0050 Negative position limit value.....	120
9.34.1	Attributes.....	120
9.34.2	Description.....	120
9.35	IDN S-0-0051 Position feedback value 1 (motor feedback).....	120
9.35.1	Attributes.....	120
9.35.2	Description.....	121
9.36	IDN S-0-0052 Reference distance 1.....	121
9.36.1	Attributes.....	121
9.36.2	Description.....	121
9.37	IDN S-0-0053 Position feedback value 2 (external feedback).....	121
9.37.1	Attributes.....	121
9.37.2	Description.....	122
9.38	IDN S-0-0054 Reference distance 2.....	122
9.38.1	Attributes.....	122
9.38.2	Description.....	122
9.39	IDN S-0-0055 Position polarity parameters.....	122
9.39.1	Attributes.....	122
9.39.2	Description.....	123
9.40	IDN S-0-0057 Position window.....	123
9.40.1	Attributes.....	123
9.40.2	Description.....	124
9.41	IDN S-0-0058 Reversal clearance.....	124

9.41.1	Attributes.....	124
9.41.2	Description.....	124
9.42	IDN S-0-0059 Position switch flag parameter.....	125
9.42.1	Attributes.....	125
9.42.2	Description.....	125
9.43	IDN S-0-0060 to S-0-0075 Position switch points on 1-16.....	125
9.43.1	Attributes.....	125
9.43.2	Description.....	126
9.44	IDN S-0-0076 Position data scaling type.....	126
9.44.1	Attributes.....	126
9.44.2	Description.....	126
9.45	IDN S-0-0077 Linear position data scaling factor.....	127
9.45.1	Attributes.....	127
9.45.2	Description.....	127
9.46	IDN S-0-0078 Linear position data scaling exponent.....	127
9.46.1	Attributes.....	127
9.46.2	Description.....	128
9.47	IDN S-0-0079 Rotational position resolution.....	128
9.47.1	Attributes.....	128
9.47.2	Description.....	128
9.48	IDN S-0-0080 Torque command value.....	129
9.48.1	Attributes.....	129
9.48.2	Description.....	129
9.49	IDN S-0-0082 Positive torque limit value.....	129
9.49.1	Attributes.....	129
9.49.2	Description.....	129
9.50	IDN S-0-0083 Negative torque limit value.....	130
9.50.1	Attributes.....	130
9.50.2	Description.....	130
9.51	IDN S-0-0084 Torque feedback value.....	130
9.51.1	Attributes.....	130
9.51.2	Description.....	130
9.52	IDN S-0-0085 Torque polarity parameter.....	131
9.52.1	Attributes.....	131
9.52.2	Description.....	131
9.53	IDN S-0-0086 Torque/force data scaling type.....	131
9.53.1	Attributes.....	131
9.53.2	Description.....	132
9.54	IDN S-0-0091 Bipolar velocity limit value.....	132
9.54.1	Attributes.....	132
9.54.2	Description.....	133
9.55	IDN S-0-0092 Bipolar torque limit value.....	133
9.55.1	Attributes.....	133
9.55.2	Description.....	133
9.56	IDN S-0-0093 Torque/force data scaling factor.....	133
9.56.1	Attributes.....	133
9.56.2	Description.....	134
9.57	IDN S-0-0094 Torque/force data scaling exponent.....	134
9.57.1	Attributes.....	134