

INTERNATIONAL STANDARD

**Electrical installations in ships –
Part 350: General construction and test methods of power, control
and instrumentation cables for shipboard and offshore applications**





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



IEC 60092-350

Edition 5.0 2020-01

INTERNATIONAL STANDARD

**Electrical installations in ships –
Part 350: General construction and test methods of power, control
and instrumentation cables for shipboard and offshore applications**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.060.20; 47.020.60

ISBN 978-2-8322-7783-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	7
1 Scope	9
2 Normative references	9
3 Terms and definitions	11
3.31 tests	15
4 Constructional requirements	16
4.1 General requirements	16
4.1.1 General	16
4.1.2 Voltage designation	16
4.1.3 Cable marking	16
4.1.4 Core identification.....	17
4.1.5 Halogen-free cables.....	17
4.2 Conductors	17
4.2.1 Material	17
4.2.2 Metal coating and separator	17
4.2.3 Class and form	18
4.2.4 Resistance	18
4.3 Insulation system	19
4.3.1 Material	19
4.3.2 Application.....	19
4.3.3 Insulation thickness	19
4.4 Screens	19
4.4.1 Conductor and insulation screens for high-voltage cables.....	19
4.4.2 Screens (shields) for low voltage cables	20
4.5 Cabling	20
4.5.1 Multi-core cables	20
4.5.2 Multi-unit cables	20
4.6 Inner coverings, fillers and binders	21
4.7 Inner sheath.....	21
4.7.1 Material	21
4.7.2 Application.....	21
4.7.3 Thickness of inner sheath.....	21
4.8 Metal braid armour.....	21
4.8.1 Material	21
4.8.2 Application.....	22
4.9 Outer sheath	22
4.9.1 Material	22
4.9.2 Application.....	22
4.9.3 Thickness of outer sheath.....	22
4.9.4 Calculation of lower and upper limits for the outer dimensions of cables	23
5 Test methods.....	23
5.1 Test conditions	23
5.1.1 Ambient temperature	23
5.1.2 Frequency, waveform and magnitude of power-frequency test voltages	23
5.2 Routine tests.....	23
5.2.1 General	23

5.2.2	Measurement of the electrical resistance of the conductors	23
5.2.3	Voltage test	24
5.2.4	Partial discharge test	25
6	Sample tests	26
6.1	General.....	26
6.2	Frequency of sample tests	26
6.3	Repetition of tests	26
6.4	Conductor examination	26
6.5	Measurement of thickness of insulation.....	27
6.5.1	General	27
6.5.2	Procedure.....	27
6.5.3	Requirements	27
6.6	Measurements of thickness of non-metallic sheaths.....	27
6.6.1	General	27
6.6.2	Procedure.....	27
6.6.3	Requirements	27
6.7	Measurement of external diameter	27
6.8	Hot-set test for insulations and sheaths	27
6.8.1	General procedure.....	27
6.8.2	Requirements	28
6.9	Insulation resistance test (volume resistivity determination).....	28
7	Type tests, electrical.....	29
7.1	General.....	29
7.2	Insulation resistance measurement.....	29
7.2.1	Measurement at ambient temperature.....	29
7.2.2	Measurement at maximum rated temperature	29
7.3	Increase in AC capacitance after immersion in water	30
7.3.1	General	30
7.3.2	Preparation of test specimens.....	30
7.3.3	Apparatus.....	30
7.3.4	Procedure.....	30
7.3.5	Requirements	30
7.4	High-voltage test for 4 h for cables rated up to 1,8/3 kV	31
7.4.1	General	31
7.4.2	Requirement.....	31
7.5	Mutual capacitance (control and instrumentation cables only).....	31
7.6	Inductance to resistance ratio (control and instrumentation cables only)	31
7.7	High voltage sequence test (cables having a voltage rating higher than 3,6/6 (7,2) kV).....	31
7.7.1	General	31
7.7.2	Special provisions	31
7.7.3	Partial discharge test.....	32
7.7.4	Bending test	32
7.7.5	Tan δ measurement as a function of the voltage	32
7.7.6	Tan δ measurement as a function of the temperature.....	32
7.7.7	Heating cycle test plus partial discharge test	33
7.7.8	Impulse withstand test, followed by a power-frequency voltage test.....	33
7.7.9	High-voltage test for 4 h	33
8	Type tests (non-electrical)	33

8.1	General.....	33
8.2	Measurement of thickness of insulation.....	34
8.3	Measurement of thickness of non-metallic sheaths (excluding inner coverings).....	34
8.4	Tests for determining the mechanical properties of insulation before and after ageing	34
8.4.1	Sampling	34
8.4.2	Ageing treatments	34
8.4.3	Conditioning and mechanical tests.....	34
8.4.4	Requirements	34
8.5	Tests for determining the mechanical properties of sheaths before and after ageing.....	34
8.5.1	Sampling	34
8.5.2	Ageing treatments	34
8.5.3	Conditioning and mechanical tests.....	34
8.5.4	Requirements	34
8.6	Additional ageing test on pieces of completed cables (compatibility test)	35
8.6.1	General	35
8.6.2	Sampling	35
8.6.3	Ageing treatment	35
8.6.4	Mechanical tests.....	35
8.6.5	Requirements	35
8.7	Loss of mass test on PVC ST 2 sheath	35
8.7.1	Procedure.....	35
8.7.2	Requirements	35
8.8	Test for the behaviour of PVC ST 2 and halogen-free SHF 1 sheaths at high temperature (hot pressure test).....	35
8.8.1	Procedure.....	35
8.8.2	Requirements	35
8.9	Test for the behaviour of PVC sheath ST 2 and halogen-free SHF 1 and SHF 2 sheaths at low temperature	36
8.9.1	Procedure.....	36
8.9.2	Requirements	36
8.10	Special test for low temperature behaviour (when required)	36
8.11	Test of the metal coating of copper wires	36
8.12	Galvanizing test	36
8.13	Test for resistance of PVC ST 2 and halogen-free SHF 1 sheaths to cracking (heat shock test).....	36
8.13.1	Procedure.....	36
8.13.2	Requirements	36
8.14	Ozone resistance test for insulation and for sheaths	36
8.14.1	Procedure.....	36
8.14.2	Requirements	36
8.15	Hot oil immersion test and enhanced hot oil immersion test for sheaths	37
8.15.1	Hot oil immersion test	37
8.15.2	Enhanced hot oil immersion test (when required).....	37
8.16	Mud drilling fluid test (when required)	37
8.17	Fire tests	37
8.17.1	Flame-spread test on single cables.....	37
8.17.2	Flame-spread test on bunched cables.....	37

8.17.3	Smoke emission test.....	37
8.17.4	Acid gas emission test.....	37
8.17.5	pH and conductivity test.....	37
8.17.6	Fluorine content test.....	38
8.17.7	Fire-resistance test (test for circuit integrity cables).....	38
8.18	Determination of hardness for HEPR.....	38
8.19	Determination of elastic modulus for HEPR.....	38
8.20	Durability of print	38
Annex A (normative) Fictitious calculation method for determination of dimensions of protective coverings.....		39
A.1	Overview.....	39
A.2	General.....	39
A.3	Method	39
A.3.1	Conductors	39
A.3.2	Cores	40
A.3.3	Diameter over laid-up cores.....	41
A.3.4	Inner coverings.....	43
A.3.5	Sheath.....	43
A.3.6	Braid armour.....	44
Annex B (informative) Recommended minimum spark test voltage levels (according to IEC 62230)		45
B.1	General.....	45
B.2	Test voltages	45
B.2.1	General	45
B.2.2	Contact electrodes.....	45
B.2.3	Non-contact electrodes.....	46
Annex C (normative) Rounding of numbers.....		47
C.1	Rounding of numbers for the purpose of the fictitious calculation method.....	47
C.1.1	Rules.....	47
C.1.2	Illustrations.....	47
C.2	Rounding of numbers for other purposes	47
Annex D (normative) Calculation of the lower and upper limits for the outer dimensions of cables with circular copper conductors		48
D.1	General.....	48
D.2	Lower limit for the outer diameter.....	48
D.3	Upper limit for the outer diameter.....	48
D.4	Thickness of the mandatory or optional coverings other than the insulation and the sheath(s).....	49
Annex E (normative) Cold bend test and impact test for low temperature behaviour.....		50
E.1	Cold bend test at any specified low temperature	50
E.1.1	Method no. 1	50
E.1.2	Method no. 2	50
E.1.3	Examination and requirements.....	51
E.2	Impact test at any specified low temperature.....	51
E.2.1	Apparatus	51
E.2.2	Procedures	51
E.2.3	Requirements	51
Bibliography.....		52

Table 1 – Minimum size of conductors	18
Table 2 – Routine test voltage	25
Table 3 – Number of samples according to cable length	26
Table 4 – Tan δ versus voltage	32
Table 5 – Tan δ versus temperature	33
Table 6 – Impulse withstand voltages	33
Table 7 – Test methods and requirements for halogen-free components	38
Table A.1 – Fictitious diameter of conductor	40
Table A.2 – Increase of diameter for concentric conductors and metallic screens made of tape or wire.....	40
Table A.3 – Assembly coefficient k for laid-up	42
Table A.4 – Coefficient c_f	43
Table B.1 – Recommended minimum spark-test voltages for cables having rated voltage (U_0) between 150 V and 1 800 V	45
Table D.1 – Lower and upper limits of circular copper conductors for cables for fixed installations	49
Table E.1 – Details of low temperature bending test	50

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRICAL INSTALLATIONS IN SHIPS –**Part 350: General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60092-350 has been prepared by subcommittee 18A: Electric cables for ships and mobile and fixed offshore units, of IEC technical committee 18: Electrical installations of ships and of mobile and fixed offshore units.

This fifth edition cancels and replaces the fourth edition published in 2014 and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) more detailed description of the test procedures in 7.7.6 and 7.7.7;
- b) description of the relationship between Annex A and Annex D.

The text of this International Standard is based on the following documents:

CDV	Report on voting
18A/420/FDIS	18A/423/RVC

Full information on the voting for the approval of this document can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60092 series, under the general title *Electrical installations in ships*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

ELECTRICAL INSTALLATIONS IN SHIPS –

Part 350: General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications

1 Scope

This part of IEC 60092 provides the general constructional requirements and test methods for use in the manufacture of electric power, control and instrumentation cables with copper conductors intended for fixed electrical systems at voltages up to and including 18/30(36) kV on board ships and offshore (mobile and fixed) units.

The reference to fixed systems includes those that are subjected to vibration (due to the movement of the ship or installation) or movement (due to motion of the ship or installation) and not to those that are intended for frequent flexing. Cables suitable for frequent or continual flexing use are detailed in other IEC standards, for example IEC 60227 (all parts) and IEC 60245 (all parts), and their uses are restricted to those situations which do not directly involve exposure to a marine environment, for example, portable tools and domestic appliances.

The following types of cables are not included:

- optical fibre;
- sub-sea and umbilical cables;
- data and communication cables;
- coaxial cables.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-461, *International Electrotechnical Vocabulary – Part 461: Electric cables* (available at www.electropedia.org)

IEC 60092-360:2014, *Electrical installations in ships – Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables*

IEC 60228, *Conductors of insulated cables*

IEC 60230, *Impulse tests on cables and their accessories*

IEC 60331-1, *Tests for electric cables under fire conditions – Circuit integrity – Part 1: Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0,6/1,0 kV and with an overall diameter exceeding 20 mm*

IEC 60331-2, *Tests for electric cables under fire conditions – Circuit integrity – Part 2: Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0,6/1,0 kV and with an overall diameter not exceeding 20 mm*

IEC 60331-11, *Tests for electric cables under fire conditions – Circuit integrity – Part 11: Apparatus – Fire alone at a flame temperature of at least 750 °C*

IEC 60331-21, *Tests for electric cables under fire conditions – Circuit integrity – Part 21: Procedures and requirements – Cables of rated voltage up to and including 0,6/1,0 kV*

IEC 60332-1-2, *Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW pre-mixed flame*

IEC 60332-3-22, *Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A*

IEC 60684-2, *Flexible insulating sleeving – Part 2: Methods of test*

IEC 60754-1, *Test on gases evolved during combustion of materials from cables – Part 1: Determination of the halogen acid gas content*

IEC 60754-2, *Test on gases evolved during combustion of materials from cables – Part 2: Determination of acidity (by pH measurement) and conductivity*

IEC 60811-201, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 201: General tests – Measurement of insulation thickness*

IEC 60811-202, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 202: General tests – Measurement of thickness of non-metallic sheath*

IEC 60811-203, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions*

IEC 60811-401, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 401: Miscellaneous tests – Thermal ageing methods – Ageing in an air oven*

IEC 60811-403, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 403: Miscellaneous tests – Ozone resistance test on cross-linked compounds*

IEC 60811-404, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 404: Miscellaneous tests – Mineral oil immersion tests for sheaths*

IEC 60811-409, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 409: Miscellaneous tests – Loss of mass test for thermoplastic insulations and sheaths*

IEC 60811-501, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds*

IEC 60811-504, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 505: Mechanical tests – Bending tests at low temperature for insulations and sheaths*

IEC 60811-505, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 505: Mechanical tests – Elongation at low temperature for insulations and sheaths*

IEC 60811-506, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 505: Mechanical tests – Impact test at low temperature for insulations and sheaths*

IEC 60811-507, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 507: Mechanical tests – Hot set test for cross-linked materials*

IEC 60811-508, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 508: Mechanical tests – Pressure test at high temperature for insulation and sheaths*

IEC 60811-509, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 509: Mechanical tests – Test for resistance of insulations and sheaths to cracking (heat shock test)*

IEC 60885-3, *Electrical test methods for electric cables – Part 3: Test methods for partial discharge measurements on lengths of extruded power cables*

IEC 61034-1, *Measurement of smoke density of cables burning under defined conditions – Part 1: Test apparatus*

IEC 61034-2, *Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements*

ISO 7989-2:2007, *Steel wire and wire products – Non-ferrous metallic coatings on steel wire – Part 2: Zinc or zinc-alloy coating*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-461 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

approximate value

value which is neither guaranteed nor checked

Note 1 to entry: It is used, for example, for the calculation of other dimensional values.

3.2

braid

covering formed from braided metallic or non-metallic material

[SOURCE: IEC 60050-461:2008, 461-05-10]

3.3

braid armour

covering formed from braided metal wires used to protect a cable from external mechanical effects

Note 1 to entry: Where the rules of the applicable national, regulatory or approval body permit the practice, it is also possible to use the braid armour as an earth conductor.

Note 2 to entry: Copper-wire braid armour may also provide a limited function of an electrostatic collective screen, provided it is effectively earthed.

3.4 compatibility test

test intended to check that the insulation and sheath are not liable to deteriorate in operation due to contact either with each other or with other components in the cable

3.5 conductor

<of a cable> part of a cable which has the specific function of carrying current

[SOURCE: IEC 60050-461:2008, 461-01-01]

3.6 conductor screen

non-metallic conducting layer applied between the conductor and insulation to equalise the electrical stress between these components

Note 1 to entry: It may also provide smooth surfaces at the boundaries of the insulation and assist in the elimination of spaces at these boundaries

3.7 core-insulated conductor, US

assembly comprising a conductor and its own insulation (and screens, if any)

Note 1 to entry: In North American usage, the core of a cable has been defined as the assembly of components of a cable lying under a common covering such as the sheath (jacket).

3.8 drain wire

un-insulated wire laid in contact with an electrical screen or an electrical shield which has the specific function of earthing an electrostatic screen by ensuring a low resistive path throughout the length of the cable

3.9 electrostatic screen electrostatic shield, US

earthed metallic layer surrounding a cable which confines the electric field generated by the cable within the cable cores, pair(s), triples(s) or quad(s), and/or protects the core(s), pair(s), triple(s) or quad(s) from external influence

Note 1 to entry: Metallic sheaths, foils, braids, armours and earthed concentric conductors may also serve as an electrostatic screen, provided they are effectively grounded or earthed.

3.10 fictitious value

value calculated according to the "fictitious method" described in Annex A

3.11 filler

material used to fill the interstices between the cores of a multi-conductor cable

[SOURCE: IEC 60050-461:2008, 461-04-05]

3.12 fire resistance circuit integrity

ability of an electric cable to continue to operate in a designated manner whilst subjected to a specified flame source for a specified period of time under specified conditions

3.13**flexible cable**

cable which is required to be capable of being flexed while in service and of which the structure and materials are such as to fulfil this requirement

[SOURCE: IEC 60050-461:2008, 461-06-14]

3.14**individually screened cable
radial field cable**

cable in which each core is covered with an individual screen

[SOURCE: IEC 60050-461:2008, 461-06-12]

3.15**inner covering**

non-metallic covering which surrounds the core or the assembly of the cores or the cabling elements (and fillers, if any) of a multi-conductor cable and over which further layers are applied and which has no mechanical or electrical functions

Note 1 to entry: The inner covering can be either extruded or taped, and in either case forms a continuous layer, which has only an approximate value of thickness and no defined mechanical requirements.

Note 2 to entry: Taped inner coverings are also sometimes called "lapped beddings".

3.16**inner sheath
inner jacket, US**

non-metallic sheath generally applied under a metallic sheath, reinforcement or armour

Note 1 to entry: The inner sheath shall have the following properties:

- it shall be extruded;
- it may be used to fill the interstices;
- it shall be of a material listed in IEC 60092-360;
- it shall have a defined nominal thickness (value).

[SOURCE: IEC 60050-461:2008, 461-05-13, modified – The note to entry has been added.]

3.17**insulated cable**

assembly consisting of

- one or more cores;
- their individual covering(s) (if any);
- assembly protection (if any);
- protective covering(s) (if any).

Note 1 to entry: Additional un-insulated conductor(s) may be included in the cable.

Note 2 to entry: The assembly protection may consist of fillers, binders or inner coverings.

Note 3 to entry: The protective covering(s) consists of one or more "constituent elements" such as a metallic braid, wire or a metallic screen, thermosetting or thermoplastic sheaths, (impregnated) fibrous braid or woven tape, bedding for metal armour or paint for metal armour.

[SOURCE: IEC 60050-461:2008, 461-06-01, modified – Notes 2 and 3 to entry have been added.]

3.18**insulation screen****core screen**

electrical screen of non-metallic semi-conducting layer in combination with a metallic layer

3.19**length of lay**

axial length of one complete turn of the helix formed by one cable component in a twisted construction

[SOURCE: IEC 60050-461:2008, 461-04-01, modified – The words "in a twisted construction" have been added.]

3.20**median value**

middle value, when several results have been obtained and ordered in increasing (or decreasing) succession, if the number of available values is odd, and the mean of the two middle values if the number is even

3.21**multi-unit cable**

cable consisting of more than one pair, triple or quad unit either unscreened or with an individual electrostatic screen around each unit or having an electrostatic screen applied around the assembly of units (a collective screen) in a twisted construction

3.22**nominal value**

value by which quantity is designated, and which is often used in tables

Note 1 to entry: Usually, in this document, nominal values refer to values which are to be checked by measurements, taking into account specified tolerances.

3.23**oversheath****outer sheath****protective overall jacket, US****protective jacket**

non metallic sheath applied over a covering, generally metallic, ensuring the protection of the cable from the outside

Note 1 to entry: The outer sheath shall have the following properties:

- it shall be extruded;
- it may be used to fill the interstices;
- it shall be of a material listed in IEC 60092-360;
- it shall have a defined nominal thickness (value).

Note 2 to entry: In North-America, the term sheath is generally used for metallic coverings, whereas the term jacket is used only for non-metallic coverings.

[SOURCE: IEC 60050-461:2008, 461-05-04, modified – Note 2 to entry has been replaced by a new note.]

3.24**pair unit**

two cores laid up with or without interstitial fillers or binder tape(s)

3.25**quad unit**

four cores laid up with or without interstitial fillers or binder tape(s)

3.26**separator**

thin layer used as a barrier to prevent mutually detrimental effects between different components of a cable, such as between the conductor and insulation or between insulation and sheath

[SOURCE: IEC 60050-461:2008, 461-05-01]

3.27**single unit cable**

cable consisting of either one pair, triple or quad unit, either unscreened or with an individual electrostatic screen

3.28**stranded conductor**

conductor consisting of a number of individual wires all or some of which generally have a helical form

Note 1 to entry: The cross section of a stranded conductor may be circular or otherwise shaped.

Note 2 to entry: The term "strand" is also used to designate a single wire.

[SOURCE: IEC 60050-461:2008, 461-01-07, modified – The words "or strands" have been deleted from the definition.]

3.29**SZ cabling**

method of cabling in which the direction of lay of the cable components is periodically reversed

[SOURCE: IEC 60050-461:2008, 461-04-07]

3.30**triple unit**

three cores laid up with or without interstitial fillers or binder(s)

3.31 tests**3.31.1****routine test**

test made by the manufacturer on each manufactured length of cable to check that each length meets the specified requirements

3.31.2**sample test**

test made by the manufacturer on samples of completed cable or components taken from a completed cable, at a specified frequency, so as to verify that the finished product meets the specified requirements

3.31.3**type test**

test made before supplying, on a general commercial basis, a type of cable covered by this document, in order to demonstrate satisfactory performance characteristics to meet the intended application

Note 1 to entry: These tests are of such a nature that, after they have been made, they need not be repeated unless changes are made in the cable materials or design or manufacturing process which might change the performance characteristics.