



IEC 61588

Edition 2.0 2009-02

INTERNATIONAL STANDARD

IEEE 1588™

Precision clock synchronization protocol for networked measurement and control systems

Withdrawn

IEC 61588 Ed. 2.0 - Preview only Copy via ILNAS e-Shop

IEC 61588:2009(E) IEEE Std. 1588(E):2008



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2008 IEEE

All rights reserved. IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Inc.

Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the IEC Central Office.

Any questions about IEEE copyright should be addressed to the IEEE. Enquiries about obtaining additional rights to this publication and other information requests should be addressed to the IEC or your local IEC member National Committee.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

The Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue
US-New York, NY10016-5997
USA
Email: stds-info@ieee.org
Web: www.ieee.org

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11



IEC 61588

Edition 2.0 2009-02

INTERNATIONAL STANDARD

IEEE 1588™

IEC 61588 Ed. 2.0 - Preview only Copy via ILNAS e-Shop

Precision clock synchronization protocol for networked measurement and control systems

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 25.040.40; 35.110; 35.240.50

ISBN 978-2-88910-546-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Foreword.....	xi
IEEE introduction.....	xiv
1. Overview	1
1.1 Scope	1
1.2 Purpose	2
1.3 Layout of the document.....	2
2. Normative references.....	3
3. Definitions, acronyms, and abbreviations	4
3.1 Definitions	4
3.2 Acronyms and abbreviations	7
4. Conventions.....	8
4.1 Descriptive lexical form syntax	8
4.2 Word usage.....	9
4.3 Behavioral specification notation	10
5. Data types and on-the-wire formats in a PTP system.....	11
5.1 General	11
5.2 Primitive data type specifications.....	11
5.3 Derived data type specifications.....	12
5.4 On-the-wire formats	15
6. Clock synchronization model.....	16
6.1 General	16
6.2 Principle assumptions about the network and implementation recommendations.....	16
6.3 PTP systems.....	17
6.4 PTP message classes.....	17
6.5 PTP device types	18
6.6 Synchronization overview.....	29
6.7 PTP communications overview.....	37
7. Characterization of PTP entities	41
7.1 Domains.....	41
7.2 PTP timescale	41
7.3 PTP communications.....	42
7.4 PTP communication media.....	46
7.5 PTP ports	47
7.6 PTP device characterization	53
7.7 PTP timing characterization	61
8. PTP data sets	63
8.1 General specifications for data set members	63
8.2 Data sets for ordinary and boundary clocks.....	65
8.3 Data sets for transparent clocks	74
9. PTP for ordinary and boundary clocks	76
9.1 General protocol requirements for PTP ordinary and boundary clocks.....	76
9.2 State protocol.....	76
9.3 Best master clock algorithm	83
9.4 Grandmaster clocks	92
9.5 Message processing semantics	93
9.6 Changes in the local clock	107
10. PTP for transparent clocks.....	107
10.1 General requirements for both end-to-end and peer-to-peer transparent clocks.....	107
10.2 End-to-end transparent clock requirements	108

IEC 61588 Ed. 2.0 - Preview only Copy via ILNAS e-Shop

10.3 Peer-to-peer transparent clock requirements.....	108
11. Clock offset, path delay, residence time, and asymmetry corrections.....	108
11.1 General specifications.....	108
11.2 Computation of clock offset in ordinary and boundary clocks.....	109
11.3 Delay request-response mechanism.....	110
11.4 Peer delay mechanism.....	112
11.5 Transparent clock residence time correction for PTP version 2 events.....	117
11.6 Asymmetry correction for PTP version 2 event messages.....	120
12. Synchronization and syntonization of clocks.....	122
12.1 Syntonization.....	122
12.2 Synchronization.....	123
13. PTP message formats.....	124
13.1 General.....	124
13.2 General message format requirements.....	124
13.3 Header.....	124
13.4 Suffix.....	128
13.5 Announce message.....	128
13.6 Sync and Delay_Req messages.....	130
13.7 Follow_Up message.....	130
13.8 Delay_Resp message.....	130
13.9 Pdelay_Req message.....	131
13.10 Pdelay_Resp message.....	131
13.11 Pdelay_Resp_Follow_Up message.....	132
13.12 Signaling message.....	132
13.13 Management message.....	133
14. TLV entity specifications.....	133
14.1 General requirements.....	133
14.2 Experimental TLVs.....	134
14.3 Vendor and standard organization extension TLVs.....	135
15. Management.....	135
15.1 General.....	135
15.2 PTP management mechanism.....	136
15.3 Processing of management messages.....	136
15.4 Management message format.....	137
15.5 Management TLVs.....	138
16. General optional features.....	158
16.1 Unicast message negotiation (optional).....	158
16.2 Path trace (optional).....	163
16.3 Alternate timescales (optional).....	165
17. State configuration options.....	169
17.1 General.....	169
17.2 Data types for options.....	169
17.3 Grandmaster clusters (optional).....	170
17.4 Alternate master (optional).....	172
17.5 Unicast discovery (optional).....	173
17.6 Acceptable master table (optional).....	175
18. Compatibility requirements.....	177
18.1 Compatibility between version 2 and future versions.....	177
18.2 Compatibility between version 1 and version 2.....	177
18.3 Message formats and data types.....	178
18.4 Naming changes.....	183
18.5 Restrictions on mixed version 1 and version 2 systems.....	183

19. Conformance	184
19.1 Conformance objective	184
19.2 PTP conformance requirements	184
19.3 PTP profiles	185
Annex A (informative) Using PTP	187
Annex B (informative) Timescales and epochs in PTP	197
Annex C (informative) Examples of residence and asymmetry corrections	200
Annex D (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 4 ..	219
Annex E (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 6 ..	221
Annex F (normative) Transport of PTP over IEEE 802.3 /Ethernet	223
Annex G (normative) Transport of PTP over DeviceNET	225
Annex H (normative) Transport of PTP over ControlNET	228
Annex I (normative) Transport of PTP over IEC 61158 Type 10	230
Annex J (normative) Default PTP profiles	237
Annex K (informative) Security protocol (experimental)	241
Annex L (informative) Transport of cumulative frequency scale factor offset (experimental)	264
Annex M (informative) Bibliography	268
Annex N (informative) List of participants	270

Withdrawing

TABLES

Table 1	—Primitive PTP data types	12
Table 2	—domainNumber	41
Table 3	—networkProtocol enumeration	46
Table 4	—Non-EUI-64 addressTechnology enumeration	51
Table 5	—clockClass specifications	55
Table 6	—clockAccuracy enumeration	56
Table 7	—timeSource enumeration	57
Table 8	—PTP state enumeration	73
Table 9	—Delay mechanism enumeration	74
Table 10	—PTP portState definition	77
Table 11	—Event applicability in boundary clocks	83
Table 12	—Information sources for data set comparison algorithm	88
Table 13	—Updates for state decision code M1 and M2	91
Table 14	—Updates for state decision code M3	91
Table 15	—Updates for state decision code P1, and P2	91
Table 16	—Updates for state decision code S1	92
Table 17	—Source identity comparisons	95
Table 18	—Common message header	124
Table 19	—Values of messageType field	125
Table 20	—Values of flagField	126
Table 21	—correctionField semantics	127
Table 22	—References for sequenceId value exceptions	127
Table 23	—controlField enumeration	128
Table 24	—Values of logMessageInterval field	128
Table 25	—Announce message fields	129
Table 26	—Sync and Delay_Req message fields	130
Table 27	—Follow_Up message fields	130
Table 28	—Delay_Resp message fields	130
Table 29	—Pdelay_Req message fields	131
Table 30	—Pdelay_Resp message fields	131
Table 31	—Pdelay_Resp_Follow_Up message fields	132
Table 32	—Acceptance of signaling messages	132
Table 33	—Signaling message fields	133

Table 34	—tlvType values	134
Table 35	—Organization specific TLV fields	135
Table 36	—Acceptance of management messages	136
Table 37	—Management message fields	137
Table 38	—Values of the actionField	138
Table 39	—Management TLV fields	139
Table 40	—managementId values	140
Table 41	—CLOCK_DESCRIPTION management TLV data field	141
Table 42	—clockType specification	142
Table 43	—USER_DESCRIPTION management TLV data field	144
Table 44	—INITIALIZE management TLV data field	145
Table 45	—INITIALIZATION_KEY enumeration	145
Table 46	—Fault log severityCode enumeration	145
Table 47	—FAULT_LOG management TLV data field	146
Table 48	—TIME management TLV data field	147
Table 49	—CLOCK_ACCURACY management TLV data field	147
Table 50	—DEFAULT_DATA_SET management TLV data field	148
Table 51	—PRIORITY1 management TLV data field	148
Table 52	—PRIORITY2 management TLV data field	149
Table 53	—DOMAIN management TLV data field	149
Table 54	—SLAVE_ONLY management TLV data field	149
Table 55	—CURRENT_DATA_SET management TLV data field	149
Table 56	—PARENT_DATA_SET management TLV data field	150
Table 57	—TIME_PROPERTIES_DATA_SET management TLV data field	151
Table 58	—UTC_PROPERTIES management TLV data field	152
Table 59	—TRACEABILITY_PROPERTIES management TLV data field	152
Table 60	—TIMESCALE_PROPERTIES management TLV data field	152
Table 61	—PORT_DATA_SET management TLV data field	153
Table 62	—LOG_ANNOUNCE_INTERVAL management TLV data field	154
Table 63	—ANNOUNCE_RECEIPT_TIMEOUT management TLV data field	154
Table 64	—LOG_SYNC_INTERVAL management TLV data field	154
Table 65	—DELAY_MECHANISM management TLV data field	155
Table 66	—LOG_MIN_PDELAY_REQ_INTERVAL management TLV data field	155
Table 67	—VERSION_NUMBER management TLV data field	155
Table 68	—TRANSPARENT_CLOCK_DEFAULT_DATA_SET management TLV data field	156

Table 69	—PRIMARY_DOMAIN management TLV data field.....	156
Table 70	—TRANSPARENT_CLOCK_PORT_DATA_SET management TLV data field.....	157
Table 71	—MANAGEMENT_ERROR_STATUS TLV format.....	157
Table 72	—managementErrorId enumeration.....	158
Table 73	—REQUEST_UNICAST_TRANSMISSION TLV format.....	160
Table 74	—GRANT_UNICAST_TRANSMISSION TLV format.....	161
Table 75	—CANCEL_UNICAST_TRANSMISSION TLV format.....	161
Table 76	—ACKNOWLEDGE_CANCEL_UNICAST_TRANSMISSION TLV format.....	162
Table 77	—UNICAST_NEGOTIATION_ENABLE management TLV data field.....	162
Table 78	—PATH_TRACE TLV format.....	164
Table 79	—PATH_TRACE_LIST management TLV data field.....	164
Table 80	—PATH_TRACE_ENABLE management TLV data field.....	164
Table 81	—ALTERNATE_TIME_OFFSET_INDICATOR TLV format.....	166
Table 82	—ALTERNATE_TIME_OFFSET_ENABLE management TLV data field.....	167
Table 83	—ALTERNATE_TIME_OFFSET_NAME management TLV data field.....	167
Table 84	—ALTERNATE_TIME_OFFSET_MAX_KEY management TLV data field.....	168
Table 85	—ALTERNATE_TIME_OFFSET_PROPERTIES management TLV data field.....	168
Table 86	—GRANDMASTER_CLUSTER_TABLE management TLV data field.....	171
Table 87	—Alternate master attributes.....	173
Table 88	—ALTERNATE_MASTER management TLV data field.....	173
Table 89	—UNICAST_MASTER_TABLE management TLV data field.....	174
Table 90	—UNICAST_MASTER_MAX_TABLE_SIZE management TLV data field.....	175
Table 91	—Operation of acceptable master table option.....	176
Table 92	—ACCEPTABLE_MASTER_TABLE management TLV data field.....	176
Table 93	—ACCEPTABLE_MASTER_MAX_TABLE_SIZE management TLV data field.....	177
Table 94	—ACCEPTABLE_MASTER_TABLE_ENABLED management TLV data field.....	177
Table 95	—Version 1 stratum to version 2 class.....	178
Table 96	—Version 2 clockClass to version 1 stratum.....	178
Table 97	—Version 1 to version 2 translation of grandmasterIsPreferred field.....	179
Table 98	—Version 2 to version 1 translation of the priority1 field.....	179
Table 99	—Version 1 clock identifier to version 2 clockAccuracy.....	179
Table 100	—Version 2 clockAccuracy to version 1 clock identifier.....	179
Table 101	—Version 1 to version 2 translation of grandmasterIsBoundaryClock field.....	180
Table 102	—Version 2 to version 1 translation of the priority2 field.....	180
Table 103	—Version 1 control field and version 2 messageType field mappings.....	180
Table 104	—Translation of flagField from version 1 to version 2.....	181

Table 105	—Translation of flagField from version 2 to version 1	181
Table 106	—Version 2 fields with no version 1 counterpart.....	182
Table 107	—Version 1 fields with no version 2 counterpart.....	183
Table 108	—Name correspondence.....	183
Table 109	—Mixed system restrictions	184
Table B.1	—Relationships between timescales.....	199
Table C.1	—Interpretation of Figure C.1 key values	202
Table C.2	—Interpretation of Figure C.2 key values	203
Table C.3	—Interpretation of Figure C.3 key values	205
Table C.4	—Interpretation of Figure C.4 key values	207
Table C.5	—Interpretation of Figure C.5 key values	209
Table C.6	—Interpretation of Figure C.6 key values	210
Table C.7	—Interpretation of Figure C.7 key values	211
Table C.8	—Interpretation of Figure C.8 key values	213
Table C.9	—Interpretation of Figure C.9 key values	215
Table C.10	—Interpretation of Figure C.10 key values.....	217
Table C.11	—Interpretation of Figure C.11 key values.....	218
Table D.1	—IPv4 multicast addresses.....	219
Table D.2	—transportSpecific field values.....	220
Table E.1	—IPv6 multicast addresses	222
Table F.1	—Multicast MAC addresses	223
Table F.2	—Ethernet transport specific field.....	224
Table G.1	—DeviceNet clockIdentity octets 0 through 7.....	226
Table G.2	—DeviceNet headers for all PTP message packets	226
Table H.1	—ControlNet clockIdentity octets 2 through 7.....	228
Table I.1	—Mapping of messages.....	231
Table I.2	—IEEE 802.3 DL PDU syntax	232
Table I.3	—Multicast MAC address.....	233
Table I.4	—LT (Length/Type).....	234
Table I.6	—Mapping of the parameter and attribute names	235
Table I.7	—Translation of flagField from PTP version 2 to PROFINET.....	236
Table K.1	—flagField.SECURE flag	242
Table K.2	—AUTHENTICATION TLV	260
Table K.3	—algorithmId values	261
Table K.4	—ICV and pad length.....	261
Table K.5	—AUTHENTICATION_CHALLENGE TLV	262

Table K.6—challengeType values	262
Table K.7—SECURITY_ASSOCIATION_UPDATE TLV	263
Table K.8—addressType values	263
Table L.1—CUM_FREQ_SCALE_FACTOR_OFFSET TLV format	266

Withdrawn

FIGURES

Figure 1	—Mealy state transition diagram	10
Figure 2	—Model of an ordinary clock	19
Figure 3	—Model of a boundary clock.....	21
Figure 4	—Model of an end-to-end transparent clock.....	22
Figure 5	—End-to-end residence time correction model.....	23
Figure 6	—Combined ordinary and end-to-end transparent clock.....	25
Figure 7	—Model of a peer-to-peer transparent clock.....	27
Figure 8	—Peer-to-peer residence time and link delay correction model.....	28
Figure 9	—Combined ordinary and peer-to-peer transparent clock.....	30
Figure 10	—Simple master–slave clock hierarchy	32
Figure 11	—Pruned mesh topology	33
Figure 12	—Basic synchronization message exchange	34
Figure 13	—Link delay measurement.....	35
Figure 14	—Timestamp generation model.....	36
Figure 15	—Hierarchical topology	37
Figure 16	—Linear topology.....	38
Figure 17	—Multiply connected topology.....	39
Figure 18	—Bridging disparate technologies.....	40
Figure 19	—Definition of latency constants.....	45
Figure 20	—Propagation asymmetry	47
Figure 21	—Port model	48
Figure 22	—Scaled log variance hysteresis	60
Figure 23	—State machine for a full implementation.....	78
Figure 24	—State machine for a slave-only implementation.....	79
Figure 25	—STATE_DECISION_EVENT logic	81
Figure 26	—State decision algorithm	87
Figure 27	—Data set comparison algorithm, part 1	89
Figure 28	—Data set comparison algorithm, part 2	90
Figure 29	—Receipt of Announce message logic.....	96
Figure 30	—Receipt of Sync message logic	98
Figure 31	—Receipt of Follow_Up message logic	100
Figure 32	—Receipt of Delay_Req message logic	101
Figure 33	—Receipt of Delay_Resp message logic.....	103
Figure 34	—Delay request-response path length measurement.....	110

Figure 35	—Peer delay link measurement	113
Figure 36	—Permitted mixed system configuration	183
Figure 37	—Profile print form	186
Figure C.1	—Master, end-to-end, and slave one-step clocks; no asymmetry correction	201
Figure C.2	—Master, end-to-end, and slave one-step clocks; with asymmetry correction	202
Figure C.3	—Master two-step and end-to-end transparent and slave one-step clocks; with asymmetry correction.....	204
Figure C.4	—Master and end-to-end transparent, two-step, and one-step, slave clocks; with asymmetry correction.....	206
Figure C.5	—One-step master, two-step end-to-end transparent, and one-step slave clocks; with asymmetry correction.....	208
Figure C.6	—One-step peer responder, end-to-end transparent, and peer requestor clocks; with asymmetry correction.....	210
Figure C.7	—One-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks; with asymmetry correction	211
Figure C.8	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 1; with asymmetry correction.....	212
Figure C.9	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction.....	214
Figure C.10	—Two-step peer responder, one-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction.....	216
Figure C.11	—One-step peer master, two-step peer-to-peer transparent, and one-step peer slave clocks; time computation.....	217
Figure G.1	—Event message timestamp point	225
Figure I.1	—PROFINET region combined with domains.....	231
Figure K.1	—PTP secure message processing	252
Figure K.2	—Challenge processing.....	254
Figure K.3	—Secure transmit processing.....	256
Figure K.4	—Secure event processing	258

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PRECISION CLOCK SYNCHRONIZATION PROTOCOL
FOR NETWORKED MEASUREMENT AND CONTROL SYSTEMS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC/IEEE 61588 has been processed through subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2004. It constitutes a technical revision.

The text of this standard is based on the following documents:

IEEE Std	FDIS	Report on voting
1588 (2008)	65C/510/FDIS	65C/517/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this publication will remain unchanged until 2013.

IEC/IEEE Dual Logo International Standards

This Dual Logo International Standard is the result of an agreement between the IEC and the Institute of Electrical and Electronics Engineers, Inc. (IEEE). The original IEEE Standard was submitted to the IEC for consideration under the agreement, and the resulting IEC/IEEE Dual Logo International Standard has been published in accordance with the ISO/IEC Directives.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEC/IEEE Dual Logo International Standard is wholly voluntary. The IEC and IEEE disclaim liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEC or IEEE Standard document.

The IEC and IEEE do not warrant or represent the accuracy or content of the material contained herein, and expressly disclaim any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEC/IEEE Dual Logo International Standards documents are supplied "AS IS".

The existence of an IEC/IEEE Dual Logo International Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEC/IEEE Dual Logo International Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEC and IEEE are not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Neither the IEC nor IEEE is undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEC/IEEE Dual Logo International Standards or IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations – Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments for revision of IEC/IEEE Dual Logo International Standards are welcome from any interested party, regardless of membership affiliation with the IEC or IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA and/or General Secretary, IEC, 3, rue de Varembe, PO Box 131, 1211 Geneva 20, Switzerland.

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

NOTE – Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.