

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Digital addressable lighting interface –
Part 102: General requirements – Control gear**

**Interface d'éclairage adressable numérique –
Partie 102: Exigences générales – Appareillages de commande**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Digital addressable lighting interface –
Part 102: General requirements – Control gear**

**Interface d'éclairage adressable numérique –
Partie 102: Exigences générales – Appareillages de commande**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XH**
CODE PRIX

ICS 29.140, 29.140.50

ISBN 978-2-8322-1906-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	12
INTRODUCTION.....	14
1 Scope.....	15
2 Normative references	15
3 Terms and definitions	15
4 General	18
4.1 General.....	18
4.2 Version number	18
5 Electrical specification.....	18
6 Interface power supply	18
7 Transmission protocol structure.....	19
7.1 General.....	19
7.2 16 bit forward frame encoding.....	19
7.2.1 General	19
7.2.2 Address byte	19
7.2.3 Opcode byte	19
8 Timing	19
9 Method of operation.....	20
9.1 General.....	20
9.2 Control gear.....	20
9.3 Dimming curve.....	20
9.4 Calculating “ <i>targetLevel</i> ”	23
9.5 Fading	23
9.5.1 General	23
9.5.2 Fade time	24
9.5.3 Fade rate.....	25
9.5.4 Extended fade time.....	26
9.5.5 Using the fade time.....	28
9.5.6 Using the fade rate	28
9.5.7 Behaviour during a fade.....	28
9.5.8 Behaviour during startup.....	28
9.5.9 Stopping a fade	28
9.6 Min and max level.....	29
9.7 Commands	29
9.7.1 General	29
9.7.2 Level instructions without fade.....	30
9.7.3 Level instructions initiating a fade.....	30
9.7.4 Configuration instructions	30
9.7.5 Queries	30
9.7.6 Special commands	31
9.7.7 Application extended commands.....	31
9.8 Command iterations.....	31
9.8.1 General	31
9.8.2 Command iteration of “UP” and “DOWN” commands.....	31
9.8.3 DAPC SEQUENCE (deprecated)	31

9.9	Modes of operation	32
9.9.1	General	32
9.9.2	Operating mode 0x00: standard mode	32
9.9.3	Operating mode 0x01 to 0x7F: reserved	32
9.9.4	Operating mode 0x80 to 0xFF: manufacturer specific modes	32
9.10	Memory banks	33
9.10.1	General	33
9.10.2	Memory map.....	33
9.10.3	Selecting a memory bank location	34
9.10.4	Memory bank reading	34
9.10.5	Memory bank writing.....	34
9.10.6	Memory bank 0.....	35
9.10.7	Memory bank 1.....	37
9.10.8	Manufacturer specific memory banks.....	39
9.10.9	Reserved memory banks	39
9.11	Reset.....	39
9.11.1	Reset operation	39
9.11.2	Reset memory bank operation	39
9.12	System failure.....	39
9.13	Power on	40
9.14	Assigning short addresses	41
9.14.1	General	41
9.14.2	Random address allocation.....	41
9.14.3	Identification of a device.....	42
9.14.4	Direct address allocation.....	43
9.15	Failure state behaviour	43
9.16	Status information.....	43
9.16.1	General	43
9.16.2	Bit 0: Control gear failure.....	43
9.16.3	Bit 1: Lamp failure	44
9.16.4	Bit 2: Lamp on	44
9.16.5	Bit 3: Limit error.....	44
9.16.6	Bit 4: Fade running	44
9.16.7	Bit 5: Reset state.....	44
9.16.8	Bit 6: Missing short address.....	44
9.16.9	Bit 7: Power cycle seen	45
9.17	Non-volatile memory.....	45
9.18	Device types and features.....	45
9.19	Using scenes	46
10	Declaration of variables.....	47
11	Definition of commands	49
11.1	General.....	49
11.2	Overview Sheets.....	49
11.3	Level instructions.....	55
11.3.1	DAPC (<i>level</i>)	55
11.3.2	OFF.....	55
11.3.3	UP.....	55
11.3.4	DOWN.....	55
11.3.5	STEP UP.....	55

11.3.6	STEP DOWN	56
11.3.7	RECALL MAX LEVEL	56
11.3.8	RECALL MIN LEVEL	56
11.3.9	STEP DOWN AND OFF	57
11.3.10	ON AND STEP UP	57
11.3.11	ENABLE DAPC SEQUENCE	57
11.3.12	GO TO LAST ACTIVE LEVEL	58
11.3.13	GO TO SCENE (<i>sceneNumber</i>)	58
11.4	Configuration instructions	58
11.4.1	General	58
11.4.2	RESET	58
11.4.3	STORE ACTUAL LEVEL IN DTR0	58
11.4.4	SAVE PERSISTENT VARIABLES	58
11.4.5	SET OPERATING MODE (<i>DTR0</i>)	59
11.4.6	RESET MEMORY BANK (<i>DTR0</i>)	59
11.4.7	IDENTIFY DEVICE	59
11.4.8	SET MAX LEVEL (<i>DTR0</i>)	60
11.4.9	SET MIN LEVEL (<i>DTR0</i>)	60
11.4.10	SET SYSTEM FAILURE LEVEL (<i>DTR0</i>)	60
11.4.11	SET POWER ON LEVEL (<i>DTR0</i>)	61
11.4.12	SET FADE TIME (<i>DTR0</i>)	61
11.4.13	SET FADE RATE (<i>DTR0</i>)	61
11.4.14	SET EXTENDED FADE TIME (<i>DTR0</i>)	61
11.4.15	SET SCENE (<i>DTR0, sceneX</i>)	62
11.4.16	REMOVE FROM SCENE (<i>sceneX</i>)	62
11.4.17	ADD TO GROUP (<i>group</i>)	62
11.4.18	REMOVE FROM GROUP (<i>group</i>)	62
11.4.19	SET SHORT ADDRESS (<i>DTR0</i>)	62
11.4.20	ENABLE WRITE MEMORY	63
11.5	Queries	63
11.5.1	General	63
11.5.2	QUERY STATUS	63
11.5.3	QUERY CONTROL GEAR PRESENT	63
11.5.4	QUERY CONTROL GEAR FAILURE	63
11.5.5	QUERY LAMP FAILURE	63
11.5.6	QUERY LAMP POWER ON	63
11.5.7	QUERY LIMIT ERROR	63
11.5.8	QUERY RESET STATE	63
11.5.9	QUERY MISSING SHORT ADDRESS	63
11.5.10	QUERY VERSION NUMBER	64
11.5.11	QUERY CONTENT DTR0	64
11.5.12	QUERY DEVICE TYPE	64
11.5.13	QUERY NEXT DEVICE TYPE	64
11.5.14	QUERY PHYSICAL MINIMUM	64
11.5.15	QUERY POWER FAILURE	64
11.5.16	QUERY CONTENT DTR1	64
11.5.17	QUERY CONTENT DTR2	64
11.5.18	QUERY OPERATING MODE	65
11.5.19	QUERY LIGHT SOURCE TYPE	65

11.5.20	QUERY ACTUAL LEVEL	65
11.5.21	QUERY MAX LEVEL.....	65
11.5.22	QUERY MIN LEVEL.....	66
11.5.23	QUERY POWER ON LEVEL.....	66
11.5.24	QUERY SYSTEM FAILURE LEVEL	66
11.5.25	QUERY FADE TIME/FADE RATE	66
11.5.26	QUERY EXTENDED FADE TIME.....	66
11.5.27	QUERY MANUFACTURER SPECIFIC MODE	66
11.5.28	QUERY SCENE LEVEL (<i>sceneX</i>).....	66
11.5.29	QUERY GROUPS 0-7	66
11.5.30	QUERY GROUPS 8-15.....	66
11.5.31	QUERY RANDOM ADDRESS (H)	67
11.5.32	QUERY RANDOM ADDRESS (M).....	67
11.5.33	QUERY RANDOM ADDRESS (L).....	67
11.5.34	READ MEMORY LOCATION (<i>DTR1, DTR0</i>).....	67
11.6	Application extended commands.....	67
11.6.1	General	67
11.6.2	QUERY EXTENDED VERSION NUMBER	67
11.7	Special commands.....	68
11.7.1	General	68
11.7.2	TERMINATE.....	68
11.7.3	DTR0 (<i>data</i>).....	68
11.7.4	INITIALISE (<i>device</i>).....	68
11.7.5	RANDOMISE.....	68
11.7.6	COMPARE.....	69
11.7.7	WITHDRAW.....	69
11.7.8	SEARCHADDRH (<i>data</i>).....	69
11.7.9	SEARCHADDRM (<i>data</i>).....	69
11.7.10	SEARCHADDRL (<i>data</i>).....	69
11.7.11	PROGRAM SHORT ADDRESS (<i>data</i>).....	70
11.7.12	VERIFY SHORT ADDRESS (<i>data</i>).....	70
11.7.13	QUERY SHORT ADDRESS	70
11.7.14	ENABLE DEVICE TYPE (<i>data</i>).....	70
11.7.15	DTR1 (<i>data</i>).....	71
11.7.16	DTR2 (<i>data</i>).....	71
11.7.17	WRITE MEMORY LOCATION (<i>DTR1, DTR0, data</i>)	71
11.7.18	WRITE MEMORY LOCATION – NO REPLY (<i>DTR1, DTR0, data</i>)	71
11.7.19	PING	72
12	Test procedures	72
12.1	General notes on test.....	72
12.1.1	Abbreviations.....	72
12.1.2	Test execution.....	72
12.1.3	Data transmission.....	72
12.1.4	Test setup	73
12.1.5	Test output	73
12.1.6	Fade time measurements based on light output	73
12.1.7	Description of test scheme for fast fade times on PWM dimmer	74
12.1.8	Test notation	75
12.1.9	Test execution limitation	75

12.1.10	Test results	75
12.1.11	Exception handling	75
12.1.12	Unexpected answer	75
12.2	Preamble	77
12.2.1	Test preamble	77
12.3	Physical operational parameters	94
12.3.1	Polarity test	94
12.3.2	Maximum and minimum system voltage	94
12.3.3	Overvoltage protection test	95
12.3.4	Current rating test	96
12.3.5	Transmitter voltages	97
12.3.6	Transmitter rising and falling edges	99
12.3.7	Transmitter bit timing	101
12.3.8	Transmitter frame timing	103
12.3.9	Receiver start-up behavior	104
12.3.10	Receiver threshold	105
12.3.11	Receiver bit timing	106
12.3.12	Extended receiver bit timing	110
12.3.13	Receiver forward frame violation	112
12.3.14	Receiver settling timing	112
12.3.15	Receiver frame timing FF-FF send twice	113
12.4	Configuration instructions	115
12.4.1	RESET	115
12.4.2	RESET: timeout / command in-between	119
12.4.3	Send-twice timeout	121
12.4.4	Commands in-between	129
12.4.5	STORE ACTUAL LEVEL IN DTR0	135
12.4.6	SAVE PERSISTENT VARIABLES	136
12.4.7	SET OPERATING MODE	136
12.4.8	SET MAX LEVEL	137
12.4.9	SET MIN LEVEL	137
12.4.10	SET SYSTEM FAILURE LEVEL	138
12.4.11	SET POWER ON LEVEL	139
12.4.12	SET FADE TIME	143
12.4.13	SET FADE RATE	143
12.4.14	SET SCENE / REMOVE FROM SCENE	144
12.4.15	ADD TO GROUP / REMOVE FROM GROUP	145
12.4.16	SET SHORT ADDRESS	146
12.4.17	SET EXTENDED FADE TIME	147
12.4.18	Reset/Power-on values	148
12.4.19	DTR0 / DTR1 / DTR2	154
12.5	Memory banks	154
12.5.1	READ MEMORY LOCATION on Memory Bank 0	154
12.5.2	READ MEMORY LOCATION on Memory Bank 1	159
12.5.3	READ MEMORY LOCATION on other Memory Banks	161
12.5.4	Memory bank writing	163
12.5.5	ENABLE WRITE MEMORY: writeEnableState	168
12.5.6	ENABLE WRITE MEMORY: timeout / command in-between	171
12.5.7	RESET MEMORY BANK: timeout / command in-between	172

12.5.8	RESET MEMORY BANK.....	175
12.6	Level instructions.....	176
12.6.1	Level instructions: Basic behaviour.....	176
12.6.2	FADE TIME: possible values.....	181
12.6.3	FADE TIME: transitions.....	182
12.6.4	FADE TIME: fading to 0.....	184
12.6.5	FADE TIME: small steps fading.....	186
12.6.6	FADE TIME: extended fade time.....	189
12.6.7	FADE RATE: possible values.....	191
12.6.8	FADE RATE: transitions.....	194
12.6.9	FADE RATE: extended fade time.....	195
12.6.10	FADE TIME/FADE RATE: stop fading by setting MIN/MAX levels.....	196
12.6.11	FADE TIME/FADE RATE: stop fading.....	201
12.6.12	FADE TIME/FADE RATE: stop fading when a command is sent, check timing.....	204
12.6.13	FADE TIME/FADE RATE: stop fading during startup.....	210
12.6.14	Level instructions: combined instructions.....	211
12.6.15	Power On Level - System Failure Level combined.....	213
12.6.16	ENABLE DAPC SEQUENCE.....	218
12.6.17	GO TO LAST ACTIVE LEVEL.....	219
12.6.18	GO TO SCENE.....	221
12.6.19	Power on: level control commands.....	222
12.6.20	Logarithmic dimming curve.....	224
12.6.21	Dimming curve: DAPC.....	225
12.6.22	Dimming curve: UP / DOWN.....	226
12.6.23	Dimming curve: STEP UP / STEP DOWN.....	227
12.6.24	FADE TIME/EXTENDED FADE TIME: light output behaviour.....	228
12.6.25	EXTENDED FADE TIME: light output behaviour.....	229
12.6.26	Behaviour during a fade.....	230
12.7	Special commands.....	232
12.7.1	INITIALISE – timer.....	232
12.7.2	TERMINATE.....	234
12.7.3	INITIALISE - device addressing.....	234
12.7.4	RANDOMISE.....	235
12.7.5	COMPARE.....	236
12.7.6	WITHDRAW.....	237
12.7.7	SEARCHADDRH / SEARCHADDRM / SEARCHADDRL.....	238
12.7.8	PROGRAM SHORT ADDRESS.....	239
12.7.9	VERIFY SHORT ADDRESS.....	241
12.7.10	QUERY SHORT ADDRESS.....	242
12.7.11	IDENTIFY DEVICE.....	244
12.7.12	IDENTIFY DEVICE THROUGH RECALL MIN/MAX LEVEL.....	246
12.8	Queries and reserved commands.....	250
12.8.1	QUERY STATUS - lampFailure/lampOn.....	250
12.8.2	QUERY STATUS - lampOn.....	253
12.8.3	QUERY STATUS - limitError/lampOn.....	254
12.8.4	QUERY STATUS - powerCycleSeen.....	258
12.8.5	QUERY CONTROL GEAR PRESENT.....	259
12.8.6	QUERY VERSION NUMBER.....	259

12.8.7	PING	260
12.8.8	Broadcast unaddressed	260
12.8.9	Reserved commands: standard commands	262
12.8.10	Reserved commands: special commands	262
12.8.11	Application extended commands	263
12.8.12	Not supported device types	264
12.8.13	Removed functionality	264
12.9	Cross contamination	266
12.9.1	DTR0	266
12.9.2	NVM variables	266
12.9.3	Random address generation	268
12.9.4	Addressing 1	269
12.9.5	Addressing 2	270
12.9.6	Addressing 3	272
12.10	General subsequences	273
12.10.1	GetVersionNumber	273
12.10.2	GetExtendedVersionNumber	273
12.10.3	GetSupportedDeviceTypes	274
12.10.4	GetSupportedLightSources	274
12.10.5	WaitForPowerOnPhaseToFinish	276
12.10.6	WaitForLampOn	276
12.10.7	WaitForLampOnAddressed	277
12.10.8	WaitForLampLevel	277
12.10.9	WaitForFadeToFinish	277
12.10.10	SetShortAddress	278
12.10.11	GetRandomAddress	278
12.10.12	GetLimitedRandomAddress	279
12.10.13	SetSearchAddress	279
12.10.14	ReadMemBankMultibyteLocation	279
12.10.15	FindImplementedMemoryBank	280
12.10.16	FindAllImplementedMemoryBanks	280
12.10.17	GetNumberOfLogicalUnits	280
12.10.18	GetIndexOfLogicalUnit	281
12.10.19	ConnectLamps	281
12.10.20	DisconnectLamps	281
12.10.21	PowerCycle	282
12.10.22	PowerCycleAndWaitForBusPower	282
12.10.23	PowerCycleAndWaitForDecoder	283
Annex A (informative)	Examples of algorithms	284
A.1	Random address allocation	284
A.2	One single control gear connected to the control device	284
A.3	Using application extended commands	285
Annex B (normative)	High resolution dimmer	286
Bibliography	288
Figure 1	– IEC 62386 graphical overview	14
Figure 2	– Control gear directly operating a light source	20
Figure 3	– Dimming curve	21

Figure 4 – Level over time, fading up and down	24
Figure 5 – Timing and response when receiving a command iteration	31
Figure 6 – Fading from MIN LEVEL to MAX LEVEL	74
Figure 7 – Fading from MAX LEVEL to off	74
Figure 8 – Normal fading for a PWM dimmer	74
Figure 9 – Fading from MAX LEVEL to off for a PWM dimmer	75
Figure 10 – Current rating test	97
Figure B.1 – Level behaviour in cases of off-grid starting points	287
Table 1 – 16-bit command frame encoding	19
Table 2 – Dimming curve tolerance (% , rounded to two decimals)	21
Table 3 – Dimming curve	22
Table 4 – Fade times	25
Table 5 – Fade rates	26
Table 6 – Extended fade time - base value	27
Table 7 – Extended fade time - multiplier	27
Table 8 – Basic memory map of memory banks	33
Table 9 – Memory map of memory bank 0	36
Table 10 – Memory map of memory bank 1	38
Table 11 – Power on timing	41
Table 12 – Control gear status	43
Table 13 – Scenes	46
Table 14 – Declaration of variables	47
Table 15 – Standard commands	49
Table 16 – Special commands	53
Table 17 – Light source type encoding	65
Table 18 – Device addressing with “INITIALISE”	68
Table 19 – Unexpected outcome	76
Table 20 – Parameters for test sequence CheckFactoryDefault102	82
Table 21 – Parameters for test sequence CheckFactoryDefault201	86
Table 22 – Parameters for test sequence CheckFactoryDefault202	87
Table 23 – Parameters for test sequence CheckFactoryDefault203	88
Table 24 – Parameters for test sequence CheckFactoryDefault204	88
Table 25 – Parameters for test sequence CheckFactoryDefault205	89
Table 26 – Parameters for test sequence CheckFactoryDefault206	89
Table 27 – Parameters for test sequence CheckFactoryDefault207	90
Table 28 – Parameters for test sequence CheckFactoryDefault208	90
Table 29 – Parameters for test sequence CheckFactoryDefault209	91
Table 30 – Parameters for test sequence Maximum and minimum system voltage	95
Table 31 – Parameters for test sequence Transmitter voltages	99
Table 32 – Parameters for test sequence Transmitter rising and falling edges	100
Table 33 – Parameters for test sequence Transmitter rising and falling edges	101
Table 34 – Parameters for test sequence Transmitter bit timing	102

Table 35 – Parameters for test sequence Receiver frame timing 104

Table 36 – Parameters for test sequence Receiver start-up behavior 105

Table 37 – Parameters for test sequence Receiver bit timing 107

Table 38 – Parameters for test sequence Extended receiver bit timing 111

Table 39 – Parameters for test sequence Receiver frame violation and recovering after frame size violation 112

Table 40 – Parameters for test sequence Receiver frame timing 113

Table 41 – Parameters for test sequence RESET 117

Table 42 – Parameters for test sequence Send twice timeout 122

Table 43 – Parameters for test sequence Commands in-between 131

Table 44 – Parameters for test sequence SET MAX LEVEL 137

Table 45 – Parameters for test sequence SET MIN LEVEL 138

Table 46 – Parameters for test sequence SET SYSTEM FAILURE LEVEL 139

Table 47 – Parameters for test sequence SET POWER ON LEVEL 142

Table 48 – Parameters for test sequence SET FADE TIME 143

Table 49 – Parameters for test sequence SET FADE RATE 144

Table 50 – Parameters for test sequence SET SCENE / REMOVE FROM SCENE 145

Table 51 – Parameters for test sequence ADD TO GROUP / REMOVE FROM GROUP 146

Table 52 – Parameters for test sequence SET SHORT ADDRESS 147

Table 53 – Parameters for test sequence SET EXTENDED FADE TIME 148

Table 54 – Parameters for test sequence Reset/Power-on values 151

Table 55 – Parameters for test sequence DTR0 / DTR1 / DTR2 154

Table 56 – Parameters for test sequence READ MEMORY LOCATION on Memory Bank 0 158

Table 57 – Parameters for test sequence READ MEMORY LOCATION on Memory Bank 1 161

Table 58 – Parameters for test sequence Memory bank writing 166

Table 59 – Parameters for test sequence ENABLE WRITE MEMORY: writeEnableState 169

Table 60 – Parameters for test sequence ENABLE WRITE MEMORY: timeout / command in-between 172

Table 61 – Parameters for test sequence RESET MEMORY BANK: timeout / command in-between 174

Table 62 – Parameters for test sequence RESET MEMORY BANK 176

Table 63 – Parameters for test sequence Level instructions: Basic behaviour 178

Table 64 – Parameters for test sequence FADE TIME: possible values 181

Table 65 – Parameters for test sequence FADE TIME: transitions 184

Table 66 – Parameters for test sequence FADE TIME: fading to 0 186

Table 67 – Parameters for test sequence FADE TIME: small steps fading 189

Table 68 – Parameters for test sequence FADE TIME: extended fade time 190

Table 69 – Parameters for test sequence FADE RATE: possible values 193

Table 70 – Parameters for test sequence FADE RATE: possible values 194

Table 71 – Parameters for test sequence FADE RATE: transitions 195

Table 72 – Parameters for test sequence FADE RATE: extended fade time 196

Table 73 – Parameters for test sequence FADE TIME/FADE RATE: stop fading by setting MIN/MAX levels 199

Table 74 – Parameters for test sequence FADE TIME/FADE RATE: stop fading	203
Table 75 – Parameters for test sequence FADE TIME/FADE RATE: stop fading when a command is sent, check timing	205
Table 76 – Parameters for test sequence FADE TIME/FADE RATE: stop fading during startup	210
Table 77 – Parameters for test sequence Level instructions: combined instructions	212
Table 78 – Parameters for test sequence PowerOnLevel and SystemFailureLevel	217
Table 79 – Parameters for test sequence ENABLE DAPC SEQUENCE	219
Table 80 – Parameters for test sequence GO TO LAST ACTIVE LEVEL	220
Table 81 – Parameters for test sequence GO TO SCENE	222
Table 82 – Parameters for test sequence Power on: level control commands	224
Table 83 – Parameters for test sequence Logarithmic dimming curve	225
Table 84 – Parameters for test sequence Dimming curve: DAPC	226
Table 85 – Parameters for test sequence FADE TIME/EXTENDED FADE TIME: light output behaviour	229
Table 86 – Parameters for test sequence Behaviour during a fade	232
Table 87 – Parameters for test sequence INITIALISE - device addressing	235
Table 88 – Parameters for test sequence COMPARE	237
Table 89 – Parameters for test sequence WITHDRAW	238
Table 90 – Parameters for test sequence PROGRAM SHORT ADDRESS	241
Table 91 – Parameters for test sequence VERIFY SHORT ADDRESS	242
Table 92 – Parameters for test sequence QUERY SHORT ADDRESS	243
Table 93 – Parameters for test sequence IDENTIFY DEVICE	246
Table 94 – Parameters for test sequence IDENTIFY DEVICE THROUGH RECALL MIN/MAX LEVEL	250
Table 95 – Parameters for test sequence QUERY STATUS - lampFailure/lampOn	253
Table 96 – Parameters for test sequence QUERY STATUS - lampOn	254
Table 97 – Parameters for test sequence QUERY STATUS - limitError/lampOn	256
Table 98 – Parameters for test sequence QUERY STATUS - powerCycleSeen	258
Table 99 – Parameters for test sequence QUERY CONTROL GEAR PRESENT	259
Table 100 – Parameters for test sequence Broadcast unaddressed	261
Table 101 – Parameters for test sequence Reserved commands: standard commands	262
Table 102 – Parameters for test sequence Reserved commands: special commands	263
Table 103 – Parameters for test sequence Addressing 2	272

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIGITAL ADDRESSABLE LIGHTING INTERFACE –**Part 102: General requirements –
Control gear**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62386-102 has been prepared by subcommittee 34C: Auxiliaries for lamps, of IEC technical committee 34: Lamps and related equipment.

This second edition cancels and replaces the first edition published in 2009. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) elimination of all non-control gear relevant definitions,
- b) improvement of the requirements for control gear by clarifying the description,
- c) improvement of the test command iterations to increase the compatibility,
- d) addition of new commands, and
- e) the deletion of the requirements for:

- 1) timing;
- 2) control devices.

The requirements for timing are now in Part 101 and the requirements for control devices are in Part 103.

The text of this standard is based on the following documents:

FDIS	Report on voting
34C/1099/FDIS	34C/1112/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 102 is intended to be used in conjunction with Part 101, which contains general requirements for the relevant product type (system), and with the appropriate Part 2xx (particular requirements for control gear) containing clauses to supplement or modify the corresponding clauses in Parts 101 and 102 in order to provide the relevant requirements for each type of product.

A list of all parts of the IEC 62386 series, under the general title: *Digital addressable lighting interface*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC website under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 62386 contains several parts, referred to as series. The 1xx series includes the basic specifications. Part 101 contains general requirements for system components, Part 102 extends this information with general requirements for control gear and Part 103 extends it further with general requirements for control devices.

The 2xx parts extend the general requirements for control gear with lamp specific extensions (mainly for backward compatibility with Edition 1 of IEC 62386) and with control gear specific features.

The 3xx parts extend the general requirements for control devices with input device specific extensions describing the instance types as well as some common features that can be combined with multiple instance types.

This second edition of IEC 62386-102 is published in conjunction with IEC 62386-101:2014 and with the various parts that make up the IEC 62386-2xx series for control gear, together with IEC 62386-103:2014 and the various parts that make up the IEC 62386-3xx series of particular requirements for control devices. The division into separately published parts provides for ease of future amendments and revisions. Additional requirements will be added as and when a need for them is recognised.

The setup of the standard is graphically represented in Figure 1 below.




Figure 1 – IEC 62386 graphical overview

When this part of IEC 62386 refers to any of the clauses of the other two parts of the IEC 62386-1xx series, the extent to which such a clause is applicable and the order in which the tests are to be performed are specified. The other parts also include additional requirements, as necessary.

All numbers used in this International Standard are decimal numbers unless otherwise noted. Hexadecimal numbers are given in the format 0xVV, where VV is the value. Binary numbers are given in the format XXXXXXXXb or in the format XXXX XXXX, where X is 0 or 1 and "x" in binary numbers means "don't care".

The following typographic expressions are used:

Variables: *variableName* or *variableName*[3:0], giving only bits 3 to 0 of *variableName*

Range of values: [lowest, highest]

Command: "COMMAND NAME"