

INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –
Part 3-2: Data-link layer service definition – Type 2 elements**





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



IEC 61158-3-2

Edition 3.0 2023-03

INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –
Part 3-2: Data-link layer service definition – Type 2 elements**

IEC 61158-3-2 Ed.3.0 - Preview only Copy via ILNAS e-Shop

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.040.40; 35.100.20; 35.110

ISBN 978-2-8322-6558-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
1.1 General.....	9
1.2 Specifications	9
1.3 Conformance	9
2 Normative references	10
3 Terms, definitions, symbols, abbreviated terms and conventions	10
3.1 Reference model terms and definitions	10
3.2 Service convention terms and definitions	12
3.3 Common data-link service terms and definitions	12
3.4 Additional Type 2 data-link specific definitions	14
3.5 Common symbols and abbreviations	16
3.6 Additional Type 2 symbols and abbreviations.....	17
3.7 Common conventions.....	17
4 Connection-mode and connectionless-mode data-link service	18
4.1 Overview.....	18
4.1.1 Data transfer services.....	18
4.1.2 DL-management services	22
4.1.3 Timing services	22
4.2 Facilities of the data-link service	22
4.3 Model of the data-link service	23
4.3.1 General	23
4.3.2 DLS-instance identification	23
4.3.3 Model of abstract queue concepts	23
4.3.4 QoS features	24
4.3.5 DLS-TxStatus	25
4.3.6 Receive queues	25
4.4 Sequence of primitives.....	25
4.4.1 Constraints on sequence of primitives	25
4.4.2 Relation of primitives at DLSAPs	26
4.4.3 Sequence of primitives at one DLSAP.....	27
4.5 Connection-mode data transfer	27
4.5.1 General	27
4.5.2 Function	27
4.5.3 Types of primitives and parameters	27
4.5.4 Sequence of primitives	29
4.6 Connectionless-mode data transfer.....	29
4.6.1 General	29
4.6.2 Function	29
4.6.3 Types of primitives and parameters	30
4.6.4 Sequence of primitives	32
4.7 Queue maintenance.....	32
4.7.1 Function	32
4.7.2 Types of primitives and parameters	32
4.7.3 Request primitive.....	33
4.7.4 Confirmation primitive.....	33

4.7.5	Sequence of primitives	33
4.8	Tag filter	34
4.8.1	Function	34
4.8.2	Types of primitives and parameters	34
4.8.3	Sequence of primitives	35
5	DL-management services	35
5.1	Sequence of primitives	35
5.2	Link synchronization	36
5.2.1	Function	36
5.2.2	Types of primitives and parameters	36
5.2.3	Sequence of primitives	37
5.3	Synchronized parameter change	37
5.3.1	Function	37
5.3.2	Types of primitives and parameters	37
5.3.3	Sequence of primitives	39
5.4	Event reports	40
5.4.1	Function	40
5.4.2	Types of primitives and parameters	40
5.4.3	Sequence of primitives	41
5.5	Bad FCS	41
5.5.1	Function	41
5.5.2	Types of primitives and parameters	41
5.5.3	Sequence of primitives	41
5.6	Current moderator	42
5.6.1	Function	42
5.6.2	Types of primitives and parameters	42
5.6.3	Sequence of primitives	42
5.7	Enable moderator	42
5.7.1	Function	42
5.7.2	Types of primitives and parameters	42
5.7.3	Sequence of primitives	43
5.8	Power-up and online	43
5.8.1	Function	43
5.8.2	Types of primitives and parameters	43
5.8.3	Sequence of primitives	44
5.9	Listen only	44
5.9.1	Function	44
5.9.2	Types of primitives and parameters	45
5.9.3	Sequence of primitives	45
5.10	Time distribution	45
5.10.1	Function	45
5.10.2	Types of primitives and parameters	45
	Bibliography	48
	Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses	13
	Figure 2 – NUT structure	19
	Figure 3 – Medium access during scheduled time	20
	Figure 4 – Medium access during unscheduled time	21

Figure 5 – Queue model for the peer and multipoint DLS, DLSAPs and their DLCEPs	22
Figure 6 – Queue model of a multipoint DLS between a sending DLS-user and one or more receiving DLS-users	24
Figure 7 – DLS primitive time-sequence diagram	26
Figure 8 – State transition diagram for sequences of DLS primitives at one DLSAP	27
Figure 9 – Sequence of primitives for a successful connection-mode transfer	29
Figure 10 – Sequence of primitives for an unsuccessful connection-mode transfer	29
Figure 11 – Sequence of primitives for a successful connectionless-mode transfer	32
Figure 12 – Sequence of primitives for an unsuccessful connectionless-mode transfer	32
Figure 13 – Sequence of primitives for a queue maintenance request	34
Figure 14 – Sequence of primitives for a tag filter request	35
Figure 15 – Sequence of primitives for a local link synchronization	37
Figure 16 – Sequence of primitives for a DLM-get/set parameters request	39
Figure 17 – Sequence of primitives for a DLM-tMinus change request	39
Figure 18 – Sequence of primitives for a DLM-event indication	41
Figure 19 – Sequence of primitives for a DLM-bad-FCS indication	42
Figure 20 – Sequence of primitives for a DLM-current-moderator indication	42
Figure 21 – Sequence of primitives for a DLM-enable-moderator request	43
Figure 22 – Sequence of primitives for a DLM-power-up indication	44
Figure 23 – Sequence of primitives for a DLM-online request	44
Figure 24 – Sequence of primitives for a DLM-listen-only request	45
Table 1 – Summary of connection-mode and connectionless-mode primitives and parameters	26
Table 2 – DL-connection-mode transfer primitives and parameters	28
Table 3 – DL-connectionless-mode transfer primitives and parameters	30
Table 4 – Fixed tag services available to the DLS-user	31
Table 5 – DL-queue maintenance primitives and parameters (single flush)	33
Table 6 – DL-queue maintenance primitives and parameters (flush by QoS)	33
Table 7 – DL-connectionless-mode tag filter primitives and parameters	34
Table 8 – Summary of DL-management primitives and parameters	36
Table 9 – Link synchronization primitives and parameters	37
Table 10 – Synchronized parameter change primitives and parameters (set configuration)	38
Table 11 – Synchronized parameter change primitives and parameters (get configuration)	38
Table 12 – Synchronized parameter change primitives and parameters (start countdown)	38
Table 13 – Synchronized parameter change primitives and parameters (tMinus)	38
Table 14 – DLMS-configuration-data	39
Table 15 – Event report primitives and parameters	40
Table 16 – DLMS events being reported	40
Table 17 – Bad FCS primitives and parameters	41
Table 18 – Current moderator primitives and parameters	42
Table 19 – Enable moderator primitives and parameters	43

Table 20 – Power-up primitives and parameters.....43
Table 21 – Online primitives and parameters44
Table 22 – Listen-only primitives and parameters45
Table 23 – DLMS time and time quality parameters46
Table 24 – Time distribution source quality46

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 3-2: Data-link layer service definition –
Type 2 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in the IEC 61784-1 series and the IEC 61784-2 series.

IEC 61158-3-2 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This third edition cancels and replaces the second edition published in 2014 and Amendment 1:2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of normative and bibliographic references;
- b) use of more inclusive terminology ("master" replaced by "active" or "supervisor");
- c) miscellaneous editorial corrections.

The text of this International Standard is based on the following documents:

Draft	Report on voting
65C/1201/FDIS	65C/1242/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC 61158-1.

Throughout the set of fieldbus standards, the term "service" refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the data-link layer service defined in this document is a conceptual architectural service, independent of administrative and implementation divisions.