

INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications –
Part 5-10: Application layer service definition – Type 10 elements**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications –
Part 5-10: Application layer service definition – Type 10 elements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 25.04.40; 35.100.70; 35.110

ISBN 978-2-88912-107-6

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 Scope.....	17
1.1 Overview	17
1.2 Specifications	18
1.3 Conformance.....	18
2 Normative references	18
3 Terms, definitions, abbreviations, symbols and conventions	20
3.1 Referenced terms and definitions	20
3.2 Additional terms and definitions for distributed automation	21
3.3 Additional terms and definitions for decentralized periphery	23
3.4 Additional terms and definitions for media redundancy	31
3.5 Abbreviations and symbols	32
3.6 Additional abbreviations and symbols for distributed automation	33
3.7 Additional abbreviations and symbols for decentralized periphery	33
3.8 Additional abbreviations and symbols for media redundancy	34
3.9 Conventions	34
4 Concepts.....	37
5 Data type ASE.....	37
5.1 General	37
5.2 Formal definition of data type objects	40
5.3 FAL defined data types	41
5.4 Data type ASE service specification	84
6 Communication model for common services.....	84
6.1 Concepts.....	84
6.2 ASE data types.....	84
6.3 ASEs.....	85
7 Communication model for distributed automation.....	185
7.1 Concepts.....	185
7.2 ASE data types.....	191
7.3 ASEs.....	195
7.4 ARs.....	412
7.5 Summary of FAL classes	416
7.6 Summary of FAL services.....	417
8 Communication model for decentralized periphery.....	419
8.1 Concepts.....	419
8.2 ASE data types.....	436
8.3 ASEs.....	436
8.4 Behavior of an IO device	709
8.5 Behavior of an IO controller	753
8.6 Application characteristics	756
Annex A (informative) Device instances	759
Annex B (informative) Components of an Ethernet interface	761
Annex C (informative) Scheme of MAC address assignment	765
Annex D (informative) Collection of objects.....	766
Annex E (informative) Measurement of the fast startup time	767
Bibliography.....	768

Figure 1 – Data type class hierarchy example	38
Figure 2 – NetworkTime date relation	63
Figure 3 – PTCP applications.....	98
Figure 4 – Clock drift measurement	109
Figure 5 – Multiple synchronization.....	110
Figure 6 – MRP stack	112
Figure 7 – Ring topology with one manager and clients.....	123
Figure 8 – MRM in an open ring	123
Figure 9 – More than one MRM in the ring	124
Figure 10 – Media redundancy diagnosis dependencies	125
Figure 11 – Locating the destination for redundant RT frames	165
Figure 12 – Example of periods at a local port	172
Figure 13 – FAL ASEs communication architecture.....	187
Figure 14 – Runtime object model.....	188
Figure 15 – Relationship between engineering and runtime.....	189
Figure 16 – Navigation in the runtime object model.....	190
Figure 17 – Operating state block diagram.....	229
Figure 18 – Device status model for the common diagnosis	230
Figure 19 – ACCO ASE structure	261
Figure 20 – Productive operation of data connections	262
Figure 21 – Quality code transfer – standard behavior	274
Figure 22 – Startup of a connection	275
Figure 23 – Quality code with communication fault.....	275
Figure 24 – Quality code when a connection is cleared	276
Figure 25 – Quality code when a connection is deactivated	276
Figure 26 – Quality code during the transfer of "incorrect" connection data	277
Figure 27 – Quality code for provider in "CBARReady" state	278
Figure 28 – Quality code when clearing an object from the provider	278
Figure 29 – Quality code when a connection is forced.....	279
Figure 30 – Quality code at QoS violation	279
Figure 31 – Push mode.....	286
Figure 32 – Pull mode overview	287
Figure 33 – Detailed sequence chart of the pull mode	288
Figure 34 – QoS and ORPC communication channel	289
Figure 35 – QoS Violation within Pull Mode	290
Figure 36 – Monitoring the providers heartbeat	291
Figure 37 – State machine RemoteACCO	293
Figure 38 – State machine RemoteACCOPROVIDER	293
Figure 39 – State machine RemoteACCOPROVIDER _{ORPC}	294
Figure 40 – State machine AR _{ORPC} – Provider.....	294
Figure 41 – State machine GetConnectionData – Provider.....	295
Figure 42 – State machine ProviderConnection.....	295
Figure 43 – State machine ProvConnActivation.....	296
Figure 44 – State machine WorkerORPC	296
Figure 45 – Communication stack of distributed automation devices	297
Figure 46 – Application relations between devices	298
Figure 47 – Communication relations	298
Figure 48 – RT communication channel	300

Figure 49 – Interaction between provider and consumer	302
Figure 50 – State machine AR _{SRT} – Consumer	304
Figure 51 – State machine AR _{SRT} – Provider	305
Figure 52 – State machine AccoDataCR – Consumer	306
Figure 53 – State machine AccoDataCR – Provider	306
Figure 54 – RT frame layout	307
Figure 55 – Establishing an AccoDataCR	308
Figure 56 – Flowchart of the copy cycle for local connections	309
Figure 57 – State machine connect attempt	313
Figure 58 – Productive operation of data connections (ORPC channel)	320
Figure 59 – Productive operation of data connections (RT channel)	321
Figure 60 – Productive operation of data connections (Local channel)	321
Figure 61 – Data flow for cyclic RT	322
Figure 62 – Failure of the provider in productive operation (ORPC push mode)	324
Figure 63 – Failure of the provider in productive operation (ORPC pull mode)	325
Figure 64 – Scenario 1: Provider failure in productive operation (RT)	326
Figure 65 – Scenario 2: Recovery from provider failure in productive operation (RT)	327
Figure 66 – Failure of the consumer (push mode)	327
Figure 67 – Failure of the consumer (pull mode)	328
Figure 68 – Failure of the consumer	329
Figure 69 – Failure of the provider when setting up connections	331
Figure 70 – Information levels	332
Figure 71 – ACCO ASE status model for the common diagnosis	332
Figure 72 – ACCO ASE status model for the detailed diagnosis	333
Figure 73 – Structure of the transmitted connection data	375
Figure 74 – Example of communication between controlling devices and field devices	421
Figure 75 – Example of communication between an engineering station and several controlling and field devices	421
Figure 76 – Example of communication between field devices and a server station	422
Figure 77 – Example of communication between field devices	422
Figure 78 – Structural units of one arbitrary API of an IO device (general)	424
Figure 79 – Example 1 structural units for interfaces and ports within API 0	425
Figure 80 – Example 2 structural units for interfaces and ports within API 0	426
Figure 81 – Overview of application processes	428
Figure 82 – IO device with APs, slots and subslots	429
Figure 83 – Application Process with application process objects (APOs)	432
Figure 84 – Access to a remote APO	433
Figure 85 – Access to a remote APO for provider/consumer association	434
Figure 86 – Example of one AR with two AREPs	435
Figure 87 – Relation of a record data object to one real object	437
Figure 88 – Relation of a record data object to two real objects	438
Figure 89 – Overview IO ASE service interactions	448
Figure 90 – Example of a resource model at the alarm source	524
Figure 91 – General isochronous application model (example)	588
Figure 92 – ASE relations in an IO device operating in isochronous mode	594
Figure 93 – State machine relations in an IO device operating in isochronous mode	594
Figure 94 – SyncCtl state diagram	598
Figure 95 – Output state diagram	600
Figure 96 – Input state diagram	605

Figure 97 – Assignment of communication relationship to application relationship	687
Figure 98 – Implicit application relationship	691
Figure 99 – Example IO application relationship (one-to-one)	692
Figure 100 – Example IO application relationship one-to-many	693
Figure 101 – Overview ASE state machines for IO device	709
Figure 102 – State diagram application startup IO device	711
Figure 103 – State diagram neighborhood check	719
Figure 104 – State diagram PD parameter check IO device	728
Figure 105 – State diagram for a submodule.....	738
Figure 106 – State diagram IO controller during startup	754
Figure 107 – Example of network topology including slower wireless segments	757
Figure 108 – Example of media redundancy including wireless segments	758
Figure A.1 – Instance model	759
Figure B.1 – Scheme of an Ethernet interface	761
Figure B.2 – Scheme of an Ethernet interface with bridging ability	762
Figure B.3 – Scheme of an Ethernet interface with optical ports	763
Figure B.4 – Scheme of an Ethernet interface with bridging ability using radio communication.....	764
Figure B.5 – Scheme of an Ethernet interface with radio communication.....	764
Figure C.1 – Scheme of MAC address assignment.....	765
Figure D.1 – Example for an intersection of IO device, slot, and AR	766
Figure E.1 – Measurement of the fast startup time	767
Table 1 – V2 octets	42
Table 2 – L2 octets	42
Table 3 – PERSISTDEF	45
Table 4 – VARTYPE	45
Table 5 – ITEMQUALITYDEF	46
Table 6 – STATEDEF	49
Table 7 – GROUPEXCEPTIONDEF	49
Table 8 – ACCESSRIGHTSDEF	50
Table 9 – HRESULT	50
Table 10 – E2 octets	52
Table 11 – E2 value range	53
Table 12 – Unipolar2.16 octets	53
Table 13 – Unipolar2.16 value range	53
Table 14 – N2 value range	55
Table 15 – N4 value range	55
Table 16 – X2 value range	56
Table 17 – X4 value range	57
Table 18 – C4 value range	57
Table 19 – T2 value range	59
Table 20 – T2 value range	59
Table 21 – D2 value range	60
Table 22 – R2 value range	60
Table 23 – UUID for decentralized peripherals	61
Table 24 – UUID for distributed automation	62
Table 25 – NetworkTime values	63
Table 26 – NetworkTime octets	63

Table 27 – UNICODEString values	65
Table 28 – UTF-8 character encoding scheme	65
Table 29 – OctetString2+Unsigned8 octets	76
Table 30 – Float32+Unsigned8 octets	77
Table 31 – Unsigned8+Unsigned8 octets	77
Table 32 – Data Types for Value in a VARIANT	80
Table 33 – Unsigned16_S octets	81
Table 34 – Unsigned16_S meaning	81
Table 35 – Integer16_S octets	81
Table 36 – Integer16_S meaning	82
Table 37 – Unsigned8_S octets	82
Table 38 – Unsigned8_S meaning	82
Table 39 – OctetString_S octets	83
Table 40 – OctetString_S status bits	83
Table 41 – F message trailer with 4 octets	83
Table 42 – F message trailer with 5 octets	84
Table 43 – Get	90
Table 44 – Set	92
Table 45 – Identify	95
Table 46 – Hello	96
Table 47 – Start bridge	103
Table 48 – Start slave	104
Table 49 – Start master	105
Table 50 – Stop bridge	106
Table 51 – Stop slave	107
Table 52 – Stop master	107
Table 53 – Sync state change	108
Table 54 – Start MRM	117
Table 55 – Stop MRM	118
Table 56 – Redundancy state change	119
Table 57 – Start MRC	120
Table 58 – Stop MRC	121
Table 59 – Neighborhood changed	121
Table 60 – MRP network/connection parameters	126
Table 61 – MRM parameters	127
Table 62 – MRC parameters	127
Table 63 – Set Prov Data	128
Table 64 – Set Prov Status	129
Table 65 – PPM Activate	130
Table 66 – Close	131
Table 67 – Start	131
Table 68 – Error	132
Table 69 – Get Cons Data	132
Table 70 – Get cons status	133
Table 71 – Set RedRole	133
Table 72 – CPM activate	134
Table 73 – APMS Activate	138
Table 74 – APMR Activate	139
Table 75 – APMS A Data	140