

INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications – WIA-PA
communication network and communication profile**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



IEC 62601

Edition 1.0 2011-11

INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications – WIA-PA
communication network and communication profile**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 25.040.40; 35.100.05

ISBN 978-2-88912-788-7

IEC 62601 Ed. 1.0 - Preview only Copy via ILNAS e-Shop

CONTENTS

FOREWORD.....	13
1 Scope.....	15
2 Normative references	15
3 Terms, definitions and abbreviations	15
3.1 Terms and definitions	15
3.2 Abbreviations	19
4 Specification of data types.....	21
4.1 Representation of boolean type	21
4.2 Representation of unsigned integer type	21
4.3 Representation of octet type.....	21
4.4 Representation of floating point number type.....	21
5 WIA-PA overview.....	22
5.1 Device types	22
5.2 Network topology.....	22
5.3 Protocol architecture	24
5.4 Interconnection	25
6 System management.....	25
6.1 General.....	25
6.2 Framework of system management	27
6.3 Joining process	28
6.3.1 Joining process of routing device.....	28
6.3.2 Joining process of field device.....	30
6.3.3 Addressing and address assignment	31
6.4 Virtual Communication Relationship (VCR).....	31
6.4.1 Definition.....	31
6.4.2 Protocol support for VCR.....	32
6.4.3 VCR establishment	33
6.4.4 VCR release.....	33
6.5 Routing configuration and communication resource allocation	33
6.5.1 Routing configuration.....	33
6.5.2 Framework of communication resource allocation.....	33
6.5.3 DLPPDU priority and scheduling rules	34
6.5.4 Communication resource allocation to routing device	35
6.5.5 Communication resource allocation to field device.....	35
6.6 Aggregation and disaggregation	36
6.6.1 Aggregation.....	36
6.6.2 Disaggregation	38
6.6.3 An example of the two level aggregation process	39
6.6.4 Management of aggregation and disaggregation objects.....	41
6.7 Performance monitoring	43
6.7.1 Path failure report.....	43
6.7.2 Device status report	43
6.7.3 Channel condition report.....	44
6.8 Leaving process	44
6.8.1 General	44
6.8.2 Leaving process of routing device.....	44

6.8.3	Leaving process of field device	46
6.9	Management information base and services	47
6.9.1	Management information base	47
6.9.2	MIB services	59
7	Physical Layer	61
8	Data link layer	62
8.1	General	62
8.2	Protocol stack	62
8.3	MAC overview and function extension	62
8.3.1	MAC overview	62
8.3.2	MAC function extension	63
8.4	DLSL function description	66
8.4.1	General	66
8.4.2	Coexistence	67
8.4.3	Timeslot communication	67
8.4.4	WIA-PA superframe	68
8.4.5	Frequency hopping	68
8.4.6	Transmission of long cycle data	70
8.4.7	Retry strategy	71
8.4.8	Management service	71
8.4.9	Radio link quality and channel condition measurement	71
8.4.10	Security	71
8.4.11	DLSL state machine	71
8.5	Data link sub-layer data services	73
8.5.1	General	73
8.5.2	DLDE-DATA.request	73
8.5.3	DLDE-DATA.confirm	74
8.5.4	DLDE-DATA.indication	75
8.5.5	Time sequence of DLSL data service	76
8.6	Data link sub-layer management services	77
8.6.1	General	77
8.6.2	Network discovery services	77
8.6.3	Device joining services	79
8.6.4	Device leaving services	81
8.6.5	DLME-CHANNEL-CONDITION.indication	82
8.6.6	DLME-NEIGHBOR-INFO.indication	83
8.6.7	DLME-COMM-STATUS.indication	83
8.6.8	Keep-alive services	84
8.6.9	Time synchronization services	85
8.7	DLSL frame formats	86
8.7.1	General frame format	86
8.7.2	Date frame format	86
8.7.3	Command frame format	87
9	Network layer	87
9.1	General	87
9.2	Protocol stack	87
9.3	Function description	88
9.3.1	General	88
9.3.2	Addressing	88

9.3.3	Routing.....	89
9.3.4	Packet lifecycle management	89
9.3.5	Joining and leaving network of device	89
9.3.6	End-to-end network performance monitoring.....	89
9.3.7	Fragmentation and reassembly.....	90
9.3.8	Network layer state machine.....	90
9.4	Network layer data services	91
9.4.1	General	91
9.4.2	NLDE-DATA.request.....	91
9.4.3	NLDE-DATA.confirm.....	91
9.4.4	NLDE-DATA.indication	92
9.4.5	Time sequence of NL data services	92
9.5	Network layer management services	93
9.5.1	General	93
9.5.2	Network communication status report services	93
9.5.3	Network joining services.....	95
9.5.4	Network leaving services	101
9.5.5	Cluster member report services	107
9.5.6	Neighbor information report services	109
9.5.7	Route allocation services.....	110
9.5.8	Communication resource allocation services	116
9.5.9	Aggregation and disaggregation services	131
9.5.10	Device status report services.....	132
9.5.11	Channel condition report services.....	134
9.5.12	Failure path report services	136
9.5.13	Network attribute getting services.....	137
9.5.14	Network attribute setting services	140
9.6	Network layer packet formats	143
9.6.1	Common packet format.....	143
9.6.2	Data packet format	144
9.6.3	Aggregated packet format.....	144
9.6.4	Command packet format.....	145
10	Application Layer.....	160
10.1	Overview	160
10.1.1	General	160
10.1.2	AL structure.....	160
10.1.3	Functions of UAP.....	161
10.1.4	Functions of ASL	161
10.2	UAP	161
10.2.1	General	161
10.2.2	UAO	162
10.2.3	Method definition	163
10.3	Application sub-layer.....	166
10.3.1	General	166
10.3.2	Application sub-layer data entity.....	166
10.4	Application sub-layer packet formats	171
10.4.1	General	171
10.4.2	ASL general packet format	172
10.4.3	Packet formats	173

11	Security	175
11.1	General	175
11.2	Security management framework	175
11.3	Secure communication protocol stack	176
11.3.1	General	176
11.3.2	MAC layer security	177
11.3.3	Data link sub-layer security	177
11.3.4	Application sub-layer security	179
11.4	Key management	180
11.4.1	Key type	180
11.4.2	Key distribution	181
11.4.3	Key update	181
11.4.4	Key status	182
11.5	Secure joining process	182
11.5.1	Secure joining process of a new WIA-PA device	182
11.5.2	Device security material getting services	183
11.6	Secure transportation	187
11.6.1	Process of secure transportation from field device to host configuration computer	187
11.6.2	Process of secure transportation from host configuration computer to field device	188
Annex A (informative)	Security strategy for WIA-PA network	189
Annex B (informative)	Format description for WIA-PA standard	191
Annex C (informative)	Example of UAO	193
Bibliography		195
Figure 1	– Example of WIA-PA physical topology (combination of star and mesh)	23
Figure 2	– Example of WIA-PA physical topology (star-only)	23
Figure 3	– OSI basic reference model mapped to WIA-PA	24
Figure 4	– The architecture of WIA-PA gateway	25
Figure 5	– DMAP in system management	26
Figure 6	– Hybrid centralized and distributed system management scheme	28
Figure 7	– Joining process of routing device through the gateway device	29
Figure 8	– Joining process of routing device through an online routing device	29
Figure 9	– Joining process of field device through a gateway device	30
Figure 10	– Joining process of field device through a routing device	30
Figure 11	– Long address structure of device	31
Figure 12	– Short address structure of routing device	31
Figure 13	– Short address structure of field device	31
Figure 14	– An example of resource allocation	34
Figure 15	– Allocation process of routing device's communication resources	35
Figure 16	– Allocation process of field device's communication resources	36
Figure 17	– Example of aggregation and disaggregation	40
Figure 18	– Process of path failure report	43
Figure 19	– Device status report process of field device	43
Figure 20	– Device status report process of routing device	44

Figure 21 – Process of channel condition report	44
Figure 22 – Active leaving process of routing device	45
Figure 23 – Passive leaving process of routing device	45
Figure 24 – Active leaving process of field device (leaving from gateway device).....	46
Figure 25 – Active leaving process of field device (leaving from routing device).....	46
Figure 26 – Passive leaving process of field device (leaving from gateway device).....	47
Figure 27 – Passive leaving process of field device (leaving from routing device)	47
Figure 28 – WIA-PA DLL protocol stack	62
Figure 29 – WIA-PA DLSL reference model	67
Figure 30 – WIA-PA superframe	68
Figure 31 – R1, R2 and R3 superframe structures	70
Figure 32 – An example of long cycle data transmission	70
Figure 33 – DLSL state machine	72
Figure 34 – Time sequence of data service	76
Figure 35 – Time sequence of network discovery	79
Figure 36 – General frame format	86
Figure 37 – WIA-PA network layer protocol stack.....	87
Figure 38 – WIA-PA Network layer reference model.....	88
Figure 39 – Network layer state machine.....	90
Figure 40 – Time sequence of NL data services.....	93
Figure 41 – Time sequence for field device joining through routing device	98
Figure 42 – One-hop joining process for routing device.....	99
Figure 43 – Multi-hop join process of routing device	100
Figure 44 – Active leaving process of field device (leaving routing device).....	103
Figure 45 – Passive leaving of field device	104
Figure 46 – Active leaving process of routing device	105
Figure 47 – Passive leaving process of routing device	106
Figure 48 – Cluster member reporting process.....	108
Figure 49 – Neighbor information reporting process	110
Figure 50 – Time sequence for route adding	112
Figure 51 – Time sequence for route updating	114
Figure 52 – Time sequence for route deleting	116
Figure 53 – Adding a link originated from gateway device to routing device	119
Figure 54 – Adding a link originated from routing device to field device.....	119
Figure 55 – Updating a link originated by gateway device to routing device	121
Figure 56 – Updating a link originated from routing device to field device	121
Figure 57 – Releasing a link originated from gateway device to routing device.....	123
Figure 58 – Releasing a link originated from routing device to field device.....	124
Figure 59 – Adding a superframe originated from gateway device to routing device	126
Figure 60 – Adding a superframe originated from routing device to field device	126
Figure 61 – Updating a superframe originated from gateway device to routing device	128
Figure 62 – Updating a superframe originated from routing device to field device	128
Figure 63 – Releasing a superframe originated from gateway device to routing device	130