

INTERNATIONAL STANDARD

Specification of the Radio Data System (RDS) for VHF/FM sound broadcasting in the frequency range from 87,5 MHz to 108,0 MHz

Withhold



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

Specification of the Radio Data System (RDS) for VHF/FM sound broadcasting in
the frequency range from 87,5 MHz to 108,0 MHz

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XG**

ICS 33.060.20; 33.170; 35.240.99

ISBN 978-2-88910-620-2

CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references	10
3 Abbreviations and conventions	10
4 Modulation characteristics of the data channel (physical layer).....	11
4.1 General.....	11
4.2 Subcarrier frequency.....	11
4.3 Subcarrier phase.....	13
4.4 Subcarrier level	13
4.5 Method of modulation	13
4.6 Clock-frequency and data-rate	13
4.7 Differential coding	13
4.8 Data-channel spectrum shaping	14
5 Baseband coding (data-link layer)	17
5.1 Baseband coding structure.....	17
5.2 Order of bit transmission	17
5.3 Error protection	18
5.4 Synchronisation of blocks and groups	19
6 Message format (session and presentation layers).....	19
6.1 Addressing	19
6.1.1 Design principles.....	19
6.1.2 Principal features	20
6.1.3 Group types.....	21
6.1.4 Open data channel/Applications Identification.....	23
6.1.5 Coding of the Group types.....	25
6.2 Coding of information	41
6.2.1 Coding of information for control.....	42
6.2.2 Coding and use of information for display	50
6.2.3 Coding of Clock Time and date (CT).....	51
6.2.4 Coding of information for Transparent Data Channels (TDC).....	51
6.2.5 Coding of information for In House applications (IH).....	51
6.2.6 Coding of Radio Paging (RP).....	51
6.2.7 Coding of Emergency Warning Systems (EWS).....	52
7 Description of features	53
7.1 Alternative Frequencies list (AF).....	53
7.2 Clock Time and date (CT).....	53
7.3 Decoder Identification (DI) and dynamic PTY Indicator (PTYI).....	53
7.4 Extended Country Code (ECC).....	53
7.5 Enhanced Other Networks information (EON).....	53
7.6 Emergency Warning System (EWS).....	54
7.7 In House application (IH).....	54
7.8 Music Speech switch (MS)	54
7.9 Open Data Applications (ODA).....	54
7.10 Programme Identification (PI).....	54
7.11 Programme Item Number (PIN)	55
7.12 Programme Service name (PS)	55

7.13	Programme TYpe (PTY)	55
7.14	Programme TYpe Name (PTYN).....	55
7.15	Radio Paging (RP)	55
7.16	RadioText (RT).....	56
7.17	Enhanced RadioText (eRT)	56
7.18	RadioText Plus (RT+).....	56
7.19	Traffic Announcement identification (TA)	56
7.20	Transparent Data Channels (TDC)	56
7.21	Traffic Message Channel (TMC).....	56
7.22	Traffic Programme identification (TP)	56
8	Marking	56
Annex A (normative)	Offset words to be used for group and block synchronisation	58
Annex B (informative)	Theory and implementation of the modified shortened cyclic code	59
Annex C (informative)	Implementation of group and block synchronisation using the modified shortened cyclic code	65
Annex D (normative)	Programme identification codes and Extended country codes	68
Annex E (normative)	Basic and extended RDS character sets.....	72
Annex F (normative)	Programme type codes.....	86
Annex G (informative)	Conversion between time and date conventions.....	89
Annex H (informative)	ARI (Autofahrer-Rundfunk-Information) system – Discontinuation.....	91
Annex J (normative)	Language identification.....	92
Annex K (informative)	RDS logo	94
Annex L (informative)	Open data registration.....	95
Annex M (normative)	Coding of Radio Paging (RP).....	98
Annex N (normative)	Country codes and extended country codes for countries outside the European Broadcasting Area	130
Annex P (normative)	Coding of RadioText Plus information (RT+)	135
Annex Q (normative)	Coding of enhanced RadioText (eRT)	147
Annex R (informative)	RBDS in the USA	152
Annex S (normative)	List of RDS specific abbreviations	153
Bibliography	154
Figure 1	– Block diagram of radio-data equipment at the transmitter	12
Figure 2	– Block diagram of a typical radio-data receiver/decoder.....	12
Figure 3	– Amplitude response of the specified transmitter or receiver data-shaping filter	15
Figure 4	– Amplitude response of the combined transmitter and receiver data-shaping filters	15
Figure 5	– Spectrum of biphase coded radio-data signals	16
Figure 6	– Time-function of a single biphase symbol.....	16
Figure 7	– 57 kHz radio-data signals.....	16
Figure 8	– Structure of the baseband coding.....	17
Figure 9	– Message format and addressing.....	18
Figure 10	– ODA version A groups.....	24

Figure 11 – ODA version B groups.....	25
Figure 12 – Basic tuning and switching information – Type 0A group.....	25
Figure 13 – Basic tuning and switching information – Type 0B group.....	26
Figure 14 – Programme Item Number and slow labelling codes – Type 1A group.....	27
Figure 15 – Programme Item Number – Type 1B group.....	28
Figure 16 – RadioText – Type 2A group.....	28
Figure 17 – RadioText – Type 2B group.....	29
Figure 18 – Application Identification for Open data – Type 3A group.....	30
Figure 19 – Open data – Type 3B group.....	31
Figure 20 – Clock-time and date transmission – Type 4A group.....	32
Figure 21 – Open data – Type 4B group.....	32
Figure 22 – Transparent data channels – Type 5A group.....	33
Figure 23 – Transparent data channels – Type 5B group.....	33
Figure 24 – In-house applications – Type 6A and 6B group.....	34
Figure 25 – Radio Paging – Type 7A group.....	34
Figure 26 – Type 7B group.....	35
Figure 27 – Traffic Message Channel – Type 8A group.....	35
Figure 28 – Open data – Type 8B group.....	35
Figure 29 – Allocation of EWS message bits – Type 9A group.....	36
Figure 30 – Open data – Type 9B group.....	36
Figure 31 – Programme Type Name PTYN – Type 10A group.....	37
Figure 32 – Open data – Type 10B group.....	37
Figure 33 – Open data – Type 11A and 11B groups.....	38
Figure 34 – Open data – Type 12A and 12B groups.....	38
Figure 35 – Enhanced Paging information – Type 13A group.....	39
Figure 36 – Open data – Type 13B group.....	40
Figure 37 – Enhanced Other Networks information – Type 14A groups.....	40
Figure 38 – Enhanced Other Networks information – Type 14B groups.....	40
Figure 39 – Open data – Type 15A group.....	41
Figure 40 – Fast basic tuning and switching information – Type 15B group.....	41
Figure 41 – Structure of Block 3 of Type 1A groups.....	48
Figure 42 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – National link.....	49
Figure 43 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – International link.....	50
Figure 44 – Structure of Variant 7 of Block 3 of type 1A groups for Identification of a programme carrying EWS information.....	53
Figure B.1 – Generator matrix of the basic shortened cyclic code in binary notation.....	60
Figure B.2 – Shift-register implementation of the encoder.....	61
Figure B.3 – Parity-check matrix of the basic shortened cyclic code.....	62
Figure B.4 – Shift-register implementation of the decoder.....	63
Figure C.1 – Group and block synchronisation detection circuit.....	66
Figure D.1 – PI structure.....	68

Figure D.2 – Structure of Variant 0 of Block 3 of Type 1A groups (Extended Country Codes).....	69
Figure D.3 – Correspondence between geographical locations and the symbols used for the various countries within the European Broadcasting Area as an example	69
Figure G.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC)	89
Figure J.1 – Language identification code allocation	92
Figure M.1 – Group type 7A message format for Radio Paging	101
Figure M.2 – Group type 7A paging without an additional message.....	102
Figure M.3 – Group type 7A paging with an additional 10 digit message	103
Figure M.4 – Group type 7A paging with an additional 18 digit message	103
Figure M.5 – Group type 7A paging with an additional alphanumeric message.....	104
Figure M.6 – Group type 7A paging with an additional international 15 digit message	105
Figure M.7 – Functions message in international paging	106
Figure M.8 – Variant 0 of 1A group with PIN	108
Figure M.9 – Variant 2 of 1A group with PIN	109
Figure M.10 – Variants of 1A group without PIN.....	110
Figure M.11 – Group type 13A	116
Figure M.12 – Tone-only message	118
Figure M.13 – First 7A group of a variable-length message.....	118
Figure M.14 – Group type 7A national paging with additional alphanumeric message	120
Figure M.15 – Group type 7A national paging with additional variable-length numeric message	121
Figure M.16 – Group type 7A national paging with additional variable-length functions message	122
Figure M.17 – The two first 7A groups of an international alphanumeric message.....	124
Figure M.18 – The two first 7A groups of an international variable-length numeric message	124
Figure M.19 – The two first 7A groups of an international variable-length functions message	124
Figure M.20 – Traffic handling capacity, busy hour, call rate = 0,10 calls/pager/hour	128
Figure M.21 – Traffic handling capacity, busy hour, call rate = 0,067 calls/pager/hour	129
Figure M.22 – Traffic handling capacity, busy hour, call rate = 0,05 calls/pager/hour	129
Figure P.1 – RT+ information of the category 'Item' (see Table P.2) will be attached to the programme elements Item 1 and Item 2	140
Figure P.2 – RT+ information of the category 'Item' will be attached to the programme elements Item 1 and Item 2, but not to the programme element News.....	140
Figure P.3 – RT+ information of the category 'Item' will be attached only to the programme element Item 1, but not to the programme element Talk	140
Figure P.4 – Bit allocation for group 3A (message bits and AID)	141
Figure P.5 – Coding of the message bits of the application group	142
Figure Q.1 – eRT information elements.....	147
Figure Q.2 – Bit allocation for group 3A (message bits and AID)	148
Figure Q.3 – Coding of the message bits of the application group	149

Table 1 – Encoding rules	13
Table 2 – Decoding rules	14
Table 3 – Group types	21
Table 4 – Main feature repetition rates	22
Table 5 – Group repetition rates	23
Table 6 – ODA group availability signalled in type 3A groups	24
Table 7 – STY codes	39
Table 8 – Codes for TP and TA	42
Table 9 – Bit d_0 to d_3 meanings	42
Table 10 – VHF code table	43
Table 11 – Special meanings code table	43
Table 12 – Code tables according to ITU regions	43
Table A.1 – Offset word codes	58
Table B.1 – Offset word syndromes using matrix of Figure B.3	63
Table C.1 – Offset word syndromes for group and block synchronisation	67
Table D.1 – PI code structure	68
Table D.2 – Symbols used for ECC and PI country codes for the countries in the European Broadcasting Area	70
Table D.3 – Area coverage codes	71
Table D.4 – Programme reference number codes	71
Table D.5 – PI codes for short range transmitting devices	71
Table E.1 – Basic RDS character set	72
Table E.2 – Extended RDS character set, for eRT only	73
Table F.1 – Programme type codes and corresponding terms for display	86
Table G.1 – Symbols used	89
Table J.1 – Language identification codes	92
Table M.1 – Pager group codes	99
Table M.2 – Codes for additional message contents	102
Table M.3 – Paging segment address codes for 10 and 18 digit messages	104
Table M.4 – Paging segment address codes for alphanumeric messages	105
Table M.5 – Paging segment address codes for international 15 digit messages	106
Table M.6 – Paging segment address codes for functions message	107
Table M.7 – Sub-usage codes	110
Table M.8 – Group designation codes	114
Table M.9 – Cycle selection codes	115
Table M.10 – Message sorting codes	115
Table M.11 – Codes for message types	117
Table M.12 – Description of the control byte	119
Table M.13 – Use of paging call repetition flag	119
Table M.14 – Paging segment address codes for alphanumeric message	120
Table M.15 – Paging segment address codes for variable length numeric message	121
Table M.16 – Paging segment address codes for variable length functions message	123
Table M.17 – Address notification (50 bits)	126