

INTERNATIONAL STANDARD

**Industrial communication networks – High availability automation networks –
Part 2: Media Redundancy Protocol (MRP)**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Industrial communication networks – High availability automation networks –
Part 2: Media Redundancy Protocol (MRP)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XB**

ICS 25.040, 35.040


ISBN 978-2-88910-705-6

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references.....	8
3 Terms, definitions, abbreviations, acronyms, and conventions.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations and acronyms.....	8
3.3 Conventions.....	9
4 MRP Overview.....	9
5 MRP Media redundancy behavior.....	10
5.1 Ring ports.....	10
5.2 Media Redundancy Manager (MRM).....	11
5.3 Media Redundancy Client (MRC).....	12
5.4 Redundancy domain.....	12
5.5 Usage with diagnosis and alarms.....	12
5.6 Ring diagnosis.....	13
5.7 Multiple MRM in a single ring.....	13
5.8 BLOCKED not supported (option).....	13
6 MRP Class specification.....	14
6.1 General.....	14
6.2 Template.....	14
6.3 Attributes.....	14
7 MRP service specification.....	17
7.1 Start MRM.....	17
7.2 Stop MRM.....	18
7.3 State Change.....	19
7.4 Start MRC.....	20
7.5 Stop MRC.....	21
7.6 Read MRM.....	22
7.7 Read MRC.....	24
8 MRP protocol specification.....	25
8.1 PDU description.....	25
8.1.1 Basic data types.....	25
8.1.2 DLPDU abstract syntax reference.....	25
8.1.3 Coding of the DLPDU field SourceAddress.....	26
8.1.4 Coding of the DLPDU field DestinationAddress.....	26
8.1.5 Coding of the field TagControlInformation.....	27
8.1.6 Coding of the field LT.....	27
8.1.7 MRP APDU abstract syntax.....	27
8.1.8 Coding of the field MRP_TLVHeader.....	28
8.1.9 Coding of the field MRP_Version.....	29
8.1.10 Coding of the field MRP_SequenceID.....	29
8.1.11 Coding of the field MRP_SA.....	29
8.1.12 Coding of the field MRP_Prio.....	29
8.1.13 Coding of the field MRP_PortRole.....	29
8.1.14 Coding of the field MRP_RingState.....	29

8.1.15	Coding of the field MRP_Interval	30
8.1.16	Coding of the field MRP_Transition	30
8.1.17	Coding of the field MRP_TimeStamp	30
8.1.18	Coding of the field MRP_Blocked	30
8.1.19	Coding of the field MRP_ManufacturerOUI	31
8.1.20	Coding of the field MRP_ManufacturerData	31
8.1.21	Coding of the field MRP_DomainUUID	31
8.2	Protocol machines	31
8.2.1	MRM protocol machine	31
8.2.2	MRC protocol machine	41
8.2.3	MRM and MRC functions	48
8.2.4	FDB clear timer	51
8.2.5	Topology change timer	51
9	MRP installation, configuration and repair	51
9.1	Ring port parameters	51
9.2	Ring topology parameters	52
9.3	MRM parameters	52
9.4	MRC parameters and constraints	52
9.5	Calculation of MRP ring recovery time	53
9.5.1	Overview	53
9.5.2	Deduction of formula	53
9.5.3	Worst case calculation for recovery time of 10 ms	55
9.5.4	Worst case calculation for 50 devices	56
10	MRP Management Information Base (MIB)	56
10.1	General	56
10.2	MRP MIB with a monitoring view	56
10.3	MRP MIB with a management and monitoring view	64
	Bibliography	73
	Figure 1 – MRP stack	10
	Figure 2 – MRP ring topology with one manager and clients	11
	Figure 3 – MRP open ring with MRM	11
	Figure 4 – MRP ring with more than one MRM	13
	Figure 5 – MRP protocol machine for MRM	32
	Figure 6 – MRP protocol machine for MRC	42
	Table 1 – MRP Start MRM	17
	Table 2 – MRP Stop MRM	18
	Table 3 – MRP Change State	19
	Table 4 – MRP Start MRC	20
	Table 5 – MRP Stop MRC	21
	Table 6 – MRP Read MRM	22
	Table 7 – MRP Read MRC	24
	Table 8 – MRP DLPDU syntax for ISO/IEC 8802-3 (IEEE 802.3)	26
	Table 9 – MRP OUI	26
	Table 10 – MRP MulticastMACAddress	27

Table 11 – MRP TagControllInformation.Priority field.....	27
Table 12 – MRP LT field	27
Table 13 – MRP APDU syntax	28
Table 14 – MRP Substitutions.....	28
Table 15 – MRP_TLVHeader.Type.....	28
Table 16 – MRP_Version	29
Table 17 – MRP_Prio.....	29
Table 18 – MRP_PortRole	29
Table 19 – MRP_RingState.....	30
Table 20 – MRP_Interval	30
Table 21 – MRP_Transition.....	30
Table 22 – MRP_TimeStamp	30
Table 23 – MRP_Blocked.....	31
Table 24 – MRP_DomainUUID.....	31
Table 25 – MRP Local variables of MRM protocol machine.....	33
Table 26 – MRM State machine	34
Table 27 – MRP Local variables of MRC protocol machine.....	43
Table 28 – MRC state machine.....	43
Table 29 – MRP functions.....	49
Table 30 – MRP FDB clear timer.....	51
Table 31 – MRP topology change timer.....	51
Table 32 – MRP Network/Connection parameters	52
Table 33 – MRP MRM parameters	52
Table 34 – MRP MRC parameters.....	53



INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
HIGH AVAILABILITY AUTOMATION NETWORKS –****Part 2: Media Redundancy Protocol (MRP)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard 62439-2 has been prepared by subcommittee 65C: Industrial Networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This standard cancels and replaces IEC 62439 published in 2008. This first edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62439 (2008):

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to IEC 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to IEC 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to IEC 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to IEC 62439-4 with minor editorial changes, and

- moving Clause 8 (BRP) was to IEC 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to IEC 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to IEC 62439-3 as Clause 5, and
- introducing the DRP protocol as IEC 62439-6.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/583/FDIS	65C/589/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This International Standard is to be read in conjunction with IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*.

A list of the IEC 62439 series can be found, under the general title *Industrial communication networks – High availability automation networks*, on the IEC website.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3 (IEEE 802.3) compatible, reliable data communication, and preserve determinism of real-time data communication. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the typical Ethernet communication capabilities as used in the office world, so that the software involved remains applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, matching diverse application requirements. These solutions support different redundancy topologies and mechanisms which are introduced in IEC 62439-1 and specified in the other Parts of the IEC 62439 series. IEC 62439-1 also distinguishes between the different solutions, giving guidance to the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning ring protocol given in Clause 5.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

Siemens AG A&D
Gleiwitzerstr. 555
Nürnberg 90475
Germany

and

Hirschmann Automation and Control GmbH
Stuttgarter Strasse 45-51
Neckartenzlingen 72654
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.